MIL-I-7906A(AS)
AMENDMENT 2
10 January 1980
SUPERSEDING
AMENDMENT 1
15 August 1962

MILITARY SPECIFICATION

INDICATOR, GYRO HORIZON, MANUALLY
CAGED, ELECTRIC, TYPE MB-1

This amendment forms a part of Military Specification MIL-I-7906, dated 15 June 1961.

Delete "(WEP)" from title and wherever it appears in this specification and substitute "(AS)".

PAGE 1

Add to the bottom of the page:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Air Engineering Center, ESSD, Code 9312, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

2.1 SPECIFICATIONS

Federal

Delete "DD-G-451" in its entirety and substitute "DD-G-451 Glass, Flat or Plate, Sheet, Figured (Flat, for Glazing Mirrors and Other Things)".

Military

Delete "MIL-P-116" in its entirety and substitute "MIL-P-116 Preservation-Packaging Methods of"

PAGE 2

Delete "MIL-P-7936 Parts and Equipment, Aeronautical, Preparation for Delivery".

Delete "MIL-D-70327" in its entirety and substitute "DoD-D-1000 Drawings, Engineering and Associated Lists".

U S GOVERNMENT PRINTING OFFICE 1981—703 023/4400

FSC 6610

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

Add "MIL-STD-794 Parts and Equipment, Procedures for Packaging and Packing of".

Add "MIL-STD-889 Dissimilar Metals".

Delete "MS33586 Dissimilar Metals".

Delete parenthetical source paragraph in its entirety and substitute the following:

"(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

3.1 Delete paragraph in its entirety and substitute:

"3.1 First article. When specified (see 6.5), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.3.1 and 6.5)."

PAGE 3

3.3.2.1 Dissimilar metals - Delete "MS33586" and substitute "MIL-STD-889".

PAGE 7

3.7.3 Interchangeability - Delete "MIL-D-70327" and substitute "MIL-D-1000".

Delete 4.1, 4.2, 4.3, 4.3.1, and 4.3.2 and substitute the following:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any or all of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection of the indicator shall be classified as follows:

(a) First article inspection (4.3)
(b) Quality conformance inspection (4.4)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. First article inspection shall consist of all the examinations and tests of this specification.

4.3.1 First article samples. Unless otherwise specified, as soon as practicable after award of contract or order, the manufacturer shall submit three indicators of each part number for first article testing. The samples shall be representative of the construction, workmanship, components, and materials to be used during production. When a manufacturer is in continuous production of these indicators from contract to contract, submission of further first article samples on the new contract may be waived at the discretion of the procuring activity (see 6.5). Approval of the first article samples or the waiving of the first article inspection does not preclude the requirements of submitting to the quality conformance inspection. The first article sample shall be furnished to the Government as directed by the contracting officer (see 6.5). Each sample shall be plainly identified by a securely attached durable tag marked with the following information:

Samples for first article inspection
Submitted by (name) (date) for tests in accordance with the requirements of specification MIL-I-7906A under authorization (reference letter authorizing test).
Indicator, Gyro Horizon, Manually Caged, Electric, Type MB-1
Manufacturer's part number
MS Part Number
Name of Manufacturer

4.3.1.1 Upon completion of the first article inspection, all the applicable inspection reports, and when applicable, recommendations and comments pertinent for use in monitoring production will be forwarded to the Government quality assurance representative. The samples may be consumed or destroyed in the first article inspection and shall not be considered as part of the quantity to be delivered under contract (see 6.5)."

PAGE 8

4.4 Delete in its entirety and substitute the following:

"4.4 Quality conformance inspection. The quality conformance inspection of the indicator shall consist of the individual tests and the sampling plan of this specification."

PAGE 12

4.6.8 Loop and Roll - Delete in its entirety and substitute:

"4.6.8 Loop and roll. The indicator shall be mounted in a level position on a test fixture permitting rotation about the horizontal and lateral axis and allowed to reach equilibrium. The indicator shall be a looped through one complete revolution (inside loop) at a rate of 10 ±1 degrees per second. The indicator shall indicate zero roll and pitch within one degree immediately after this manuever."



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.

PAGE 15

5.1.1 Level A Delete "MIL-P-7936) and substitute "MIL-STD-794"

5.2.1 Levels A and B Delete "MIL-P-7936" and substitute "MIL-STD-794".

5.3 Marking Delete "MIL-P-7936" and substitute "MIL-STD-794".

6.2 Drawing requirements Delete "MIL-D-70327" and substitute "DoD-D-1000".

6.3 Ordering data. Add subparagraph (e) as follows:

"(e) Whether first article is required and where the samples should be delivered (4.3.1 and 4.3.1.1)"

PAGE 16

6.4 Delete in its entirety and substitute:

"6.4 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of 7-104.9(n) of the Defense Acquisition Regulations, the data requirements identified below will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR-7-104.9(n) are not invoked the data specified below will be delivered by the contractor in accordance with the contract requirements. Deliverable data required by this specification is cited in the following paragraphs:

| Paragraph | Data Requirement | Applicable DID |
|---|---|---|
| 4.3.1.1 | First Article Inspection Reports | DI-T-5329 - Inspection Test Reports |

6.5 Add the following new paragraph:

"6.5 When a first article is required, it shall be tested under the appropriate provisions of 7-104.55 of the Defense Acquisition Regulations. The first article should be a preproduction sample. The contracting officer should include specific instructions for examinations, tests, and approval of the first article."

Preparing activity:
Navy - AS
(Project No. 6610-N091)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.