INCH-POUND

MIL-PRF-7908D
AMENDMENT 1
28 September 1998

PERFORMANCE SPECIFICATION

VALVES, CHECK, AIRCRAFT LOW PRESSURE OXYGEN SYSTEMS

This amendment forms a part of MIL-PRF-7908D, dated 26 November 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.3: Delete and substitute:

AMERICAN NATIONAL STANDARDS INSTITUTE/AMERICAN SOCIETY FOR QUALITY (ANSI/ASQ)

ANSI/ASQ Z1.4 - Sampling Procedures and Tables for Inspection by Attributes (DoD-adopted)

(Application for copies should be addressed to American Society for Quality, P.O. Box 3066, Milwaukee, WI 53201-3066, or to the American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036.)

PAGE 5

3.5.9: Delete and substitute:

"3.5.9 Cleanliness. All surfaces shall be free of visible particulates (50 microns and larger), free of visible fluorinated lubricants, and free of hydrocarbon contamination to a level not greater than 3 milligrams per square foot (mg/ft^2)(see 6.4)."

PAGE 6

4.3.2: Delete "ANSI/ASQC Z1.4" and substitute with "ANSI/ASQ Z1.4."

PAGE 7

4.6.3: Delete and substitute:

"4.6.3 Cleanliness. All surfaces shall be free of visible particulates (50 microns and larger), free of visible fluorinated lubricants, and free of hydrocarbon contamination to a level not greater than 3 mg/ft^2 (see 6.4). Cleanliness of the surfaces shall be demonstrated by industrially accepted methods and these cleaning and verification methods shall be identified (see 6.2 and 6.4)."

PAGE 9

6.2g: Delete and substitute:

"6.2g. The requirement for the vendor to identify proposed cleaning and verification methods (see 4.6.3)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:36Z
Check the source to verify that this is the current version before use.

PAGE 9

6.4: Delete and substitute:

"6.4 Cleaning. See MIL-STD-1330 and MIL-STD-1359 for guidance on proven cleaning methods and verifications. Visible inspections are typically conducted using white light and ultraviolet light to detect particulates and some types of hydrocarbons. The non-volatile residue (NVR) test in MIL-STD-1359 may be used to baseline the hydrocarbon verification at an acceptable contamination level, however, other cleaning and verification methods that do not contain class I and II ODC solvents should be used for production."

PAGE 10

Move Custodians, Reviewing activity, Preparing activity, and Project number data from page 10 to new page 19.

Custodians:
Army - AV
Navy - AS
Air Force – 99

Preparing activity:
Air Force - 71

(Project 4820-0795)

Reviewing activity:
Air Force - 11

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:36Z
Check the source to verify that this is the current version before use.