

MILITARY SPECIFICATION SHEET

Ⓐ TERMINALS, LUG AND SPLICES, CONDUCTOR, CRIMP STYLE, COPPER
TERMINAL, LUG, INSULATED, RING TONGUE, BELL-MOUTHED, TYPE II, CLASS 1
(FOR 150°C TOTAL CONDUCTOR TEMPERATURE)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for acquiring the terminal described herein shall consist of this document and the latest issue of Specification MIL-T-7928





REQUIREMENTS

1 INSULATION MATERIAL SEE MIL-T-7928

2 FINISH:
TIN-PLATED IN ACCORDANCE WITH MIL-T-10727 OR NICKEL-PLATED IN ACCORDANCE WITH QQ-N-290, CLASS 1 WITH A THICKNESS OR GRADE SUFFICIENT TO MEET THE PERFORMANCE REQUIREMENTS OF THE ACQUISITION SPECIFICATION.
VALIDATION OF CORROSION PROTECTION REQUIREMENTS SHALL BE MADE FOR EACH LOT AS SPECIFIED IN THE ABOVE COATING SPECIFICATIONS.

3. QUALIFICATION. FOR QUALIFICATION, TERMINALS SHALL BE TESTED WITH ANY ONE OF THE FOLLOWING. MIL-W-81044/6, /7, /8, /9, /10, /12, /13, OR MIL-W-22759/16, /17, /18, /19 WIRE AND TOOLING AS FOLLOWS

Ⓐ MIL-C-22520/5-01 TOOLING WITH MIL-C-22520/5-100 DIES INSTALLED FOR SIZES 22 THROUGH 10 TERMINALS, OR MIL-C-22520/10-01 TOOLING WITH MIL-C-22520/10-101 DIES INSTALLED FOR SIZES 26 THRU 14 TERMINALS AND MIL-C-22520/10-100 DIES INSTALLED FOR SIZES 12 THRU 10 TERMINALS MS23002 CRIMPING DIES TO BE USED WITH MS25441 TOOL FOR SIZES 8 THRU 2/0 EXISTING MS90413 AND MS3316 TOOLS IN THE FIELD MAY BE USED UNTIL WORN OUT

4 COLORS INSULATING SLEEVE COLOR SHALL BE CLEAR, UNCOLORED COLOR OF CIRCULAR RING OR LONGITUDINAL STRIPES SHALL BE AS SPECIFIED IN TABLE I AND SHALL BE IN ACCORDANCE WITH EIA STANDARD RS359

5 PART NUMBER THE PART NUMBER SHALL CONSIST OF THE LETTER "M", SPECIFICATION SHEET NUMBER AND DASH NUMBER EXAMPLE OF PART NUMBER M7928/4-103 TERMINAL FOR SIZE 22-18 WIRE WITH A .190 STUD HOLE

Ⓐ DENOTES CHANGES

FSC 5940

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:37Z
Check the source to verify that this is the current version before use.

Ⓐ TABLE I Dash numbers and characteristics

Dash no	Terminal size	Stud size	A Max	B Ref	C Min Rad	D Max	D Min	E dia	F dia	G dia Max	G dia Min	J min dia	W Max	W Min	Color of circular ring or longitudinal stripes
143	26-24	2 (086)	740	126	133	028	022	215/190	033/027	098	090	084	210	133	Yellow
144		4 (112)	.755		171					122	114		260	193	
145		6 (138)	855		.202					152	142			245	
146		8 (164)			227					.178	168		330		
147		10 (190)	865							203	193				
139	22-18	2 (086)	755	156	.115	035	027	215/190	073/052	.098	090	120	230	.198	Red
148		4 (112)			125					122	114			.210	
101		6 (138)								152	142		.260	245	
102		6 (138)	865		202					178	168		320	305	
149		8 (164)	910							203	193				
103		10 (190)			234					275	260		473	450	
150		1/4 (.250)	1 090		.265					338	323				
104		5/16 (312)			.296					400	.385		540	520	
105		3/8 (375)	1 320		.328					525	510		720	.705	
151		1/2 (.500)	1 320		.453										
152	16-14	4 (112)	774	156	125	035	029	260/210	095/081	122	114	153	260	240	Blue
106		6 (138)								152	142				
107		6 (138)	910		202					178	168		317	302	
153		8 (164)								203	193				
108		10 (190)	915		234					275	260		473	450	
154		1/4 (250)	1 085		265					338	323				
109		5/16 (312)			296					.400	385		540	520	
110		3/8 (375)	1 225		328					525	510		720	705	
155		1/2 (500)	1 320		453										
111	12-10	6 (138)	1 120	234	202	043	037	300/275	13°/129	152	142	.210	380	.365	Yellow
156		8 (164)			234					178	168				
112		10 (190)			.265					203	193		536	516	
157		1/4 (.250)	1 322		296					275	.260		598	573	
113		5/16 (312)			328					338	323		720	705	
114		3/8 (375)	1 414		453					400	385				
158		1/2 (500)								525	510				
115	8	10 (190)	1 402	315	.234	.084	.038	350/319	186/176	203	193	.357	429	386	Red
116		1/4 (250)	1 466		.265					275	.260		478	435	
117		5/16 (312)	1 544		.296					338	323		590	.547	
118		3/8 (375)			328					400	385				
119	6	10 (190)	1 599	375	234	087	.043	419/360	232/222	.285	.295	300	503	460	Blue
120		1/4 (250)			265					275	260		.623	580	
121		5/16 (312)	1 762		305					338	323				
122		3/8 (375)			328					400	385				
123	4	1/4 (250)	1 817	437	276	096	047	509/425	299/239	275	260	370	570	480	Yellow
124		5/16 (312)	1 879		308					338	323		648	605	
125		3/8 (375)			328					400	385				
126	2	1/4 (250)	2 069	505	343	109	054	540/510	365/355	275	260	453	711	668	Red
127		3/8 (375)								.400	.385				
128		1/2 (500)	2.269		453					525	.510		804	.740	
129	1	1/4 (.250)	2.150	565	383	125	070	.620/.560	392/388	.275	.260	590	793	.740	White
130		3/8 (375)								.400	.385				
131		1/2 (.500)	2.370		.453					.525	.510		.987	.748	
132	0	1/4 (.250)	2.401	.630	.418	.125	070	.685/625	.458/.438	275	260	.550	.853	.810	Blue
133		3/8 (.375)								.400	.395				
134		1/2 (.500)	2.525		.453					.525	.510		903	.860	
135	00	5/16 (312)	2 750	700	.473	.129	075	.755/685	520/509	.338	.323	610	956	913	Yellow
136		3/8 (375)								400	.385				
137		1/2 (500)								.525	.510				

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:37Z
Check the source to verify that this is the current version before use.

METRIC TABLE

INCH	mm	INCH	mm	INCH	mm	INCH	mm
022	0.56	.176	4.47	375	9.53	648	16.46
.027	0 69	178	4.52	380	9.65	668	16 97
.028	0 71	186	4 72	383	9 73	685	17 40
.029	0 74	190	4 83	385	9 78	690	17 53
.031	0.79	.193	4.90	386	9 80	700	17 78
.033	0 84	202	5.13	388	9.86	705	17 91
.035	0 89	.203	5 16	.398	10 11	711	18.06
.037	0 94	210	5.33	400	10.16	.720	18 29
038	0.97	.215	5.46	410	10 41	740	18.80
.043	1 09	222	5.64	418	10 62	755	19.18
.047	1.19	.227	5.77	425	10 80	774	19 66
.052	1 32	230	5 84	429	10 90	783	19.89
.054	1 37	.232	5.89	435	11 05	804	20.42
.062	1 57	234	5.94	437	11 10	810	20 57
.069	1.75	238	6 05	.438	11 13	853	21 67
070	1 78	.240	6.10	453	11 51	855	21 72
073	1.85	245	6 22	458	11 63	880	21 84
075	1 91	.250	6.35	460	11 68	865	21 97
.081	2 06	257	6.53	473	12 01	837	22 53
084	2 13	260	6.60	478	12 14	903	22 94
.086	2.18	265	6 73	480	12 19	910	23 11
090	2 29	.275	6.99	500	12.70	913	23 19
.094	2 39	276	7.01	503	12 78	915	23 24
.095	2 41	.280	7.11	.505	12.83	956	24 28
096	2 44	.290	7.37	.510	12 95	1 085	27.56
.098	2.49	.294	7 52	516	13.11	1.090	27 69
109	2 77	300	7.62	520	13 21	1 120	28 45
112	2 84	.302	7 67	525	13.34	1 225	31 12
114	2 90	.305	7 75	536	13 61	1 320	33 53
120	3 05	308	7 82	540	13 72	1 322	33 58
122	3 10	.312	7 92	547	13 89	1 402	35 61
125	3 18	315	8 00	550	13 97	1 414	35 92
126	3 20	317	8 05	560	14 22	1 466	37 24
129	3 28	.320	8 13	565	14 35	1 544	39 22
133	3 38	323	8 20	570	14 48	1 599	40 61
138	3 51	328	8 33	573	14 55	1 762	44 75
139	3 53	330	8.38	580	14 73	1 812	46 02
142	3 61	.338	8 59	590	14 99	1 879	47 73
152	3 86	343	8 71	598	15 19	2 069	52 55
153	3 89	.350	8.89	605	15 37	2 150	54 61
.156	3 96	355	9 02	.610	15 49	2 269	57 63
164	4 17	360	9 14	620	15 75	2 370	60 20
168	4 27	361	9.17	.623	15 82	2 401	60.99
.171	4.34	.365	9.27	.625	15 88	2.525	64 14
175	4 45	.370	9.40	.630	16 00	2 750	69 85

NOTES

1. DIMENSIONS ARE IN INCHES
2. METRIC EQUIVALENTS (TO THE NEAREST .01 mm) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 mm
3. "K" MAX AND MIN DIMENSIONS SHALL BE ONE HALF OF "W" MAX AND MIN DIMENSIONS, RESPECTIVELY
4. "C" MIN DIMENSIONS IS MIN WASHER CLEARANCE RADIUS.
5. DIMENSIONS "J" REPRESENTS THE MIN ID OPENING THAT WILL ACCEPT THE FINISHED WIRE
6. MAX AND MIN DIMENSIONS DUE TO OVALIZATION, MUST BE WITHIN 3% OF SPECIFICATION REQUIREMENTS
7. CONTOUR INDICATED BY PHANTOM LINES MAY VARY FROM THAT SHOWN TO SUIT INDIVIDUAL MANUFACTURER'S DESIGN
8. INSULATION SUPPORT AND TERMINAL BARREL MAY BE MULTIPLE PIECE CONSTRUCTION.
9. WIRE INSERTION SHALL BE FACILITATED BY BELL MOUTH
(A) 10. THE COLOR RING MUST COVER A MINIMUM OF 315° OF THE CIRCUMFERENCE. IN LIEU OF THE WIRE SIZE COLOR RING, 3 OR MORE LONGITUDINAL STRIPES EQUALLY SPACED ON THE INSULATION PORTION OF THE TERMINAL MAY BE USED THE STRIPES MUST EXTEND TO WITHIN 1/16" OF THE ENDS OF THE INSULATION AND MUST NOT OBLITERATE THE BASIC SLEEVE COLOR

(A) TERMINAL LUGS MANUFACTURED PRIOR TO 8 JUNE 1981, AND MARKED WITH 2 LONGITUDINAL STRIPES MAY BE USED UNTIL THE SUPPLY IS EXHAUSTED

CUSTODIANS:
ARMY - ER
NAVY - AS
AIR FORCE - 85

REVIEW ACTIVITIES
ARMY - AV, MI, MU, EC
NAVY - SH
AIR FORCE - 99
DSA - GS

USER ACTIVITIES
ARMY - AT
NAVY - OS
AIR FORCE - 17

PREPARING ACTIVITY
NAVY - AS

(PROJECT 5940-0890)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:37Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE MIL-T-7928/4A TERMINAL LUG, INSULATED, RING TONGUE, BELL-MOUTHED, TYPE II, CLASS 1 (FOR 150°C TOTAL CONDUCTOR TEMPERATURE)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 Replaces edition of 1 Jan 72 which may be used. S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:37Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Engineering Specifications and Standards Dept.
(Code 93)
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE 1981—703-023/3706 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:37Z
Check the source to verify that this is the current version before use.