
FED. SUP CLASS
5935



MS PART NO. MS 14010-1

DESIGN STANDARD FOR USE WITH MIL-C-28748/3.

(B) denotes changes

P.A Navy - EC Other Cust AF-85 Army - CR	International interest:	TITLE Insert (insulator), rectangular connector, electrical 7 (size 16 and 20 crimp removable) pin contacts.	MILITARY STANDARD MS14010
Procurement Specification MIL-C-28748		SUPERSEDES:	PAGE 1 OF 2

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

5935-3480-6

User activities: Army - ME, AM, AR
Navy - MC, OS
Air Force -

Review activities: Army - MI, AT
Navy - AS, SH
Air Force - 11
DLA-ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 20 May 1970 REVISED (A) 23 June 1972 (B) 18 March 1985

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:32Z
Check the source to verify that this is the current version before use.

User activities: Army - ME, AM, AR
Navy - MC, OS
Air Force -

Review activities: Army - MI, AT
Navy - AS, SH
Air Force - 11
DLA-ES

INCHES	MM	INCHES	MM	INCHES	MM
.002	0.05	.150	3.81	.375	9.53
.005	0.13	.172	4.37	.450	11.43
.010	0.25	.1875	4.76	.660	16.76
.016	0.41	.195	4.95	.856	21.74
.075	1.91	.228	5.79	.906	23.01
.086	2.18	.260	6.60	1.220	30.99
.09	2.29	.300	7.62		
.143	3.63	.370	9.40		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.02 (0.51 mm) for two place decimals and ±.015 (0.38 mm) for three place decimals.
4. Tolerance between any two adjacent contact centers shall be ±.004 (0.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ±.006 (0.15 mm).
5. Contact hole details shall be in accordance with MIL-C-28748.
6. Contact identification may be located on either side of the contact hole but shall appear on the front and rear face of each insert.
(B) 7. Designed for use with MIL-C-39029/34 contacts.
8. The maximum insertion and withdrawal force (connector assembly) shall be 8.75 pounds.
9. Insert material shall be in accordance with MIL-C-28748.
10. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
11. Referenced documents shall be of the issue in effect on date of invitation for bid.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 20 May 1970
REVISED (A) 23 June 1972
(B) for changes see page 2 of 2

P.A Navy - EC Other Cust AF-85 Army - CR	International interest:	TITLE Insert (insulator), rectangular connector, electrical 7 (size 16 and 20 crimp removable) pin contacts	MILITARY STANDARD MS14010
Procurement Specification MIL-C-28748		SUPERSEDES:	PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:32Z
Check the source to verify that this is the current version before use.