

TABLE I. DASH NUMBERS.

DASH NO	A	B	TEMPER
001	.097	12.000	1/2 H
003	.125	1.500	1/2 H
005	.125	1.750	1/2 H
007	.125	2.250	1/2 H
009	.125	2.500	1/2 H
011	.125	2.750	1/2 H
013	.125	3.000	1/2 H
015	.125	3.500	1/2 H
017	.125	4.000	1/2 H
019	.188	.375	1/2 H
021	.188	.625	1/2 H
023	.188	.875	1/2 H
025	.188	1.250	1/2 H
027	.188	1.750	1/2 H
029	.188	2.000	1/2 H
031	.188	2.250	1/2 H
033	.188	2.500	1/2 H
035	.188	3.000	1/2 H
037	.188	4.250	1/2 H
039	.250	.375	1/2 H
041	.250	.875	1/2 H
043	.250	1.750	1/2 H
045	.250	2.250	1/2 H
047	.250	2.500	1/2 H
049	.250	3.500	1/2 H
051	.250	4.313	1/2 H
053	.313	.500	1/2 H
055	.313	.750	1/2 H
057	.313	.875	1/2 H
059	.313	1.500	1/2 H
061	.313	2.000	1/2 H
063	.375	.625	1/2 H
065	.375	1.250	1/2 H
067	.375	1.500	1/2 H
069	.375	2.500	1/2 H
071	.500	3.500	1/2 H
073	.625	1.000	1/2 H
075	.625	1.500	1/2 H
077	.625	2.000	1/2 H
079	.625	2.500	1/2 H
081	.625	3.000	1/2 H
083	.750	1.000	1/2 H
085	.750	1.250	1/2 H
087	.750	1.500	1/2 H
089	.750	2.000	1/2 H
091	.750	2.500	1/2 H
093	.750	3.000	1/2 H
095	.875	1.500	1/2 H
097	.875	2.000	1/2 H
099	1.000	1.250	1/2 H
101	1.000	2.500	1/2 H
103	1.000	3.000	1/2 H
105	1.125	1.500	1/2 H
107	1.125	1.625	1/2 H

USER ACTIVITIES:
REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA-IS
The military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 25 OCT 84 REVISED

P.A. MR / Other Cust SH 99	INTERNATIONAL INTEREST	TITLE: BAR, METAL, FLAT, COPPER BASE ALLOY 342	MILITARY STANDARD MS52011
PROCUREMENT SPECIFICATION: QQ-B-613	SUPERSEDES:		PAGE 1 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:17Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL. COPPER BASE ALLOY 342 (UNS C34200), AS SPECIFIED IN PROCUREMENT DOCUMENT.

2. LENGTH. STANDARD LENGTH OF FLAT BAR IS 10 FEET MINIMUM, 12 FEET MAXIMUM.

3. FORMING PROCESS. ROLLED - CODE "R".

4. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS52011R001

- DASH NUMBER FROM TABLE I
- ROLLED (SEE REQUIREMENT 3)
- BASIC MS NUMBER

5. MARKING. COPPER AND COPPER BASE ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-185 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.

2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

USER ACTIVITIES:

REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 25 OCT 84 REVISED

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust MR SH 99		BAR, METAL, FLAT, COPPER BASE ALLOY 342	MS52011
PROCUREMENT SPECIFICATION: QQ-B-613	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:17Z
Check the source to verify that this is the current version before use.