
MS9811

FED. SUP CLASS 5306



PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9811-04	.875	.113- .133	11.14
MS9811-05	.938	.113- .133	11.51
MS9811-06	1.000	.113- .133	11.89
MS9811-07	1.062	.113- .133	12.27
MS9811-08	1.125	.113- .133	12.65
MS9811-09	1.188	.113- .133	13.03
MS9811-10	1.250	.113- .133	13.42
MS9811-11	1.312	.113- .133	13.79
MS9811-12	1.375	.113- .133	14.17
MS9811-13	1.438	.113- .133	14.56
MS9811-14	1.500	.113- .133	14.94
MS9811-15	1.562	.128- .188	15.32
MS9811-16	1.625	.190- .250	15.71
MS9811-17	1.688	.252- .312	16.09
MS9811-18	1.750	.315- .375	16.46
MS9811-19	1.812	.378- .438	16.84
MS9811-20	1.875	.440- .500	17.23
MS9811-21	1.938	.502- .562	17.61
MS9811-22	2.000	.565- .625	17.99
MS9811-23	2.125	.690- .750	18.75
MS9811-24	2.250	.815- .875	19.52
MS9811-25	2.375	.940-1.000	20.28
MS9811-26	2.500	1.065-1.125	21.05
MS9811-27	2.625	1.190-1.250	21.81
MS9811-28	2.750	1.315-1.375	22.57
MS9811-29	2.875	1.440-1.500	23.34
MS9811-30	3.000	1.565-1.625	24.09
MS9811-31	3.125	1.690-1.750	24.86
MS9811-32	3.250	1.815-1.875	25.63
MS9811-33	3.375	1.940-2.000	26.38
MS9811-34	3.500	2.065-2.125	27.15
MS9811-35	3.625	2.190-2.250	27.91
MS9811-36	3.750	2.315-2.375	28.67
MS9811-37	3.875	2.440-2.500	29.44
MS9811-38	4.000	2.565-2.625	30.20
MS9811-39	4.125	2.690-2.750	30.97
MS9811-40	4.250	2.815-2.875	31.73
MS9811-41	4.375	2.940-3.000	32.49
MS9811-42	4.500	3.065-3.125	33.26
MS9811-43	4.625	3.190-3.250	34.01
MS9811-44	4.750	3.315-3.375	34.78
MS9811-45	4.875	3.440-3.500	35.55
MS9811-46	5.000	3.565-3.625	36.30
MS9811-47	5.125	3.690-3.750	37.07
MS9811-48	5.250	3.815-3.875	37.84
MS9811-49	5.375	3.940-4.000	38.60
MS9811-50	5.500	4.065-4.125	39.36
MS9811-51	5.625	4.190-4.250	40.12
MS9811-52	5.750	4.315-4.375	40.89
MS9811-53	5.875	4.440-4.500	41.65
MS9811-54	6.000	4.565-4.625	42.41

1. SHANK SHALL BE STRAIGHT WITHIN .002 TOTAL PER INCH OF BOLT LENGTH.
2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .026 FIR.
4. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. MATERIAL: CORROSION RESISTANT STEEL AMS 5643.
6. HARDNESS: ROCKWELL C32-38.
7. MANUFACTURING SPECIFICATION: AMS 7474.
8. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
9. SURFACE TEXTURE: USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
10. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
11. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
12. DO NOT USE UNASSIGNED PART NUMBERS.

Ⓑ REINSTATED 15 AUG 84

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIV.

APPROVED 11 MAR 70 REVISED Ⓐ 21 DEC 83 Ⓑ 15 AUG 84

Review activities: Ⓑ AIR FORCE-82 DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. AS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust. Ⓑ AV 99	Ⓑ	BOLT, MACHINE - HEXAGON HEAD, PD SHANK, AMS 5643, .5625-18 UNJF-3A	MS9811
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:		PAGE 1 OF 1

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5306-0857

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:26Z
Check the source to verify that this is the current version before use.