MILITARY SPECIFICATION

CARTRIDGE, 20MM, HIGH EXPLOSIVE INCENDIARY WITH TRACER, M242

This amendment forms a part of Military Specification MIL-C-60836A(AR) dated 4 April 1975.

PAGE 9

Paragraph 4.4.4, Table I, 9/ Accuracy: Change "If the average mean radius of the sample cartridges exceeds the applicable requirement, a retest sample of 100 cartridges shall be tested. The lot shall be rejected if the average mean radius of the accuracy targets exceeds 15 inches at the same range." to "If the average mean radius of the sample cartridges exceeds the applicable requirement, a retest sample of 100 cartridges shall be tested for the accuracy parameter only. The lot shall be rejected if the average mean radius of the 10 accuracy targets exceeds the requirement."

Paragraph 4.4.4, Table I, 12/ Projectile function: Change "If more than 2 but less than 5 fail to comply, a second sample of 50 cartridges shall be tested." to "If more than 2 but less than 5 fail to comply, a second sample of 50 cartridges shall be tested for the projectile function parameter only."

PAGE 13

Add to paragraph 4.5.6 "The 200 yard range may be reduced by 11.5 yards to accommodate combining test phases. Any variation from 200 yard range requires direct proportional adjustment of the average mean radius."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number 1305-A87(

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

FSC: 1305