MILITARY SPECIFICATION

CARTRIDGE, DELAY, M128 ASSEMBLY

This amendment forms a part of Military Specification MIL-C-60861(MU), dated 6 December 1971, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete: "MIL-E-5272 . . ." in its entirety.
Delete: "MIL-P-46994 . . ." in its entirety.
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines".

PAGE 2

2.2 Delete "ASA B46.1 - Surface Texture" and substitute "ANSI B-46.1 Surface Texture (Surface Roughness, Waviness and Lay)"

3.3 Delete: ". . . MIL-E-5272, Procedure X11 . . ." and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5 . . .".

PAGE 5

4.3.2 Delete: ". . . ASA B46.1 . . ." and Substitute " . . . ANSI B46.1 . . ."

PAGE 10

4.4.4 Delete: ". . . MIL-E-5272, Procedure X11" and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5"

Preparing activity:
Navy - OS
Project No. 1377-N873

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.