MIL-C-55668A(EL)
AMENDMENT 1
4 April 1974

MILITARY SPECIFICATION

CORD, ELECTRICAL; AUDIO, SUBMINIATURE
(RETRACTILE AND STRAIGHT)

This amendment forms a part of Military Specification MIL-C-55668A(EL), dated 26 January 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 4

3.3 Insulation.- Delete second sentence in its entirety and substitute the following: "Insulation removed from insulated conductors of finished cords shall meet the requirements of REA Specification PE-23, with the following exceptions:

1. Cold bend shall be performed at -55°C.
2. For insulation removed from tinsel conductors, the ultimate elongation shall be 250% minimum, and the tensile strength shall be 2500 PSI minimum."

Page 6

Table I. Properties of jacket material.- For Aged - Air Oven, under:

1. Change in tensile strength, max percent,
   Delete: "10"
   Insert: "20"

2. Change in elongation, max percent,
   Delete: "50"
   Insert: "60"

Page 8

Table III. Cord requirements - Directly beneath -

"4.6.7.1---Breaking load, min pounds----70", insert the following in Value column: "60- for 2 conductor cords only".

Page 9

Table IV. Fillers, Center core, Requirement paragraph. Delete ",3.4.3".

Custodian:
Army - EL

Preparing Activity:
Army - EL

Project No. 6145-A095

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:52Z
Check the source to verify that this is the current version before use.