MIL-P-63293B (AR)
AMENDMENT 3
19 September 1984
SUPERSEDING
AMENDMENT 2
15 June 1984

MILITARY SPECIFICATION

PROJECTILE, 105MM, HEAT-T-MP, M456A2
METAL PARTS

This amendment forms a part of Military Specification MIL-P-63293B (AR), dated 18 October 1983, and is approved by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

4.3.1: Delete "Plug and disc assembly....8597489.....20".

PAGE 6

TABLE I: Category I, delete "9. 8597489-Plug and Disc Assy.....20.....3.1.....4.4.2.9"

PAGE 8

4.3.4.4: Add new paragraph "4.3.4.4 Deletion of the file test. The contractor, at his option, may select the wheel abrasive test (instead of the file test) to be used during regular production. In this case paragraphs 4.3.4.2 and 4.3.4.3 do not apply".

PAGE 12

4.4.2.1: Major Defect 124, in the Number of Samples Units column, delete "4.4.3.3.1" and substitute "4.4.3.3".

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.2.2: Major Defect 119, in the Number of Samples Units column, delete "4.4.3.3.1" and substitute "4.4.3.3".

PAGE 20

4.4.2.6: Major Defect 111, in the Number of Samples Units column, delete "4.4.3.3.1" and substitute "4.4.3.3".

PAGE 28

4.4.2.9: Delete this paragraph in its entirety.

PAGE 35

4.4.3.3 and 4.4.3.3.1: Delete these paragraphs in their entirety and substitute:

"4.4.3.3 Abrasion resistance test

4.4.3.3.1 Fin and boom assembly - file abrasive test. One fin and boom assembly (or set of components thereof) from each eight hours production or fraction thereof from the protective coating process shall be subjected to this test to determine compliance with paragraph 9.4.4 of MIL-C-60536, except that the information obtained during the file test in 4.3.4.2 shall be utilized as indicated in 4.3.4.3. Failure of the assembly or components to comply with the applicable requirements shall be cause for rejection of the product processed since the last acceptable test was performed.

4.4.3.3.2 Test panels - wheel abrasive test. If the contractor decides to use the wheel abrasive test during regular production (see 4.3.4.4), two test panels as specified in paragraph 9.4.3 of MIL-C-60536 shall be processed along with the product from each eight hours production. These test panels shall be subjected to a test in accordance with paragraph 9.4.3 of MIL-C-60536. Failure of any test to comply with the applicable requirement shall be cause for rejection of the product processed since the last acceptable test was performed."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 40

4.5.4.2: Delete this paragraph in its entirety and substitute:

"4.5.4.2 Abrasion resistance. The sample provided by 4.4.3.3.1 shall be tested using a filing machine of a type and model that was used in establishing correlation as indicated in 4.3.4.2. The samples shall be tested using the same type (roughness) file, the same length of stroke, the same number of strokes and the same file pressure as was used on the first article sample. If the contractor decides to do the wheel abrasive test (4.4.3.3.2), the test must be performed in accordance with paragraph 9.4.3 of MIL-C-60536."

4.5.5: Delete last sentence and substitute: "When ballistically testing the projectile metal parts, reference/calibration components shall be used as a minimum in the target-impact-dispersion phase."

PAGE 41

* 4.5.5.2.4: Delete this paragraph in its entirety and substitute:

"4.5.5.2.4 Weapon zeroing - boresight and superelevation. Actual superelevation of the weapon shall be measured and recorded for all target dispersion test phases. This requires that the weapon be zeroed at the beginning, end and during any extended breaks (30 minutes or longer) in target impact test phases using a conventional collimated M26 Pye Watson boresight (or equivalent). Record the weapon elevation and azimuth which aligns the boresight zero on the target center. Then record weapon elevation and azimuth data for all test and calibration phases. The gun superelevation is the weapon elevation during the test phases minus the weapon elevation which produced a muzzle boresight on target center. This data shall be obtained when using either a fixed mount or a service tank weapon system. This information shall be recorded for information only and included in the ballistic test report."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

* 4.5.5.2.4.1: Add new paragraph 4.5.5.2.4.1:

"4.5.5.2.4.1 Gun tube backlash removal. After loading and locking a round in the chamber, the gun tube shall be traversed off the target center, dropped down below the target center, traversed to the opposite side of the target center, elevated to the target center elevation, and traversed onto the target center. The distance traversed and dropped should be sufficient to remove the backlash from the system. If the sight is above or beyond the target center, do not reverse direction of gun tube movement, but repeat the sequence."

PAGE 45

5.1.1.2: Delete last sentence and substitute: "Pack sixteen (16) fin and boom assemblies arranged in a 4 x 4 pattern, using interlocking separators."

5.1.1.3: Delete this paragraph in its entirety.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1315-A648)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.