INCH-POUND

MIL-S-70538A (AR)
AMENDMENT 1
25 July 1996

MILITARY SPECIFICATION

SAW, M249 AMMUNITION MAGAZINE
ASSEMBLY AND FEEDSTRAP

This amendment forms a part of MIL-S-70538A (AR), dated 30 November 1994, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1 Under military specifications delete the following:

"MIL-L-3150	Lubricating Oil,Preservative,Medium
MIL-C-16173	Corrosion Preventive Compound, Solvent Cutback, Cold Application"

PAGE 7

TABLE I Add the following characteristic:

"Classification of Characteristics **50 0-1 3.1 4.4.2.2, 4.4.2.3**"

PAGE 11

4.4.2.1 Delete in its entirety and substitute the following new page 11 included as page 2.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-S-70538A (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Spring, Retention, Magazine	1 OF 1	12944208
			NEXT HIGHER ASSEMBLY: 9349672

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	32.51 dimension (Zone C-2)	Level I	3.2	SMTE
102	15.1 dimension (Zone B-2)	Level I	3.2	SMTE
103	4.86 dimension (Zone B-3)	Level I	3.2	SMTE
104	1.27 dimension (Zone c-3)	Level I	3.2	SMTE
105	Coating weight	5 0-1	3.2	4.7.10
106	Salt spray test	5 0-1	3.2	4.7.9
MINOR				
201	1.52 dimension (Zone B-2)	Level II	3.2	SMTE

NOTES:

2 (11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Magazine Assembly	1 OF 1	9349672

NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				4.7.5
101	Functioning 1/ 2/	10 0-1	3.4	4.7.3
102	Dovetail mount 1/ 3/	20 0-1	3.5	4.7.4
103	Drop test 1/ 3/	5 0-1	3.6	4.7.2
104	Spring, retention, magazine 1/ 3/	20 0-1	3.7	4.7.1
105	Magazine component interface 1/ 3/	20 0-1	3.8	4.5
106	Certification		3.2	
107	Magazine Assembly			
	Feedstrap	3 0-1	3.1	
		3 0-1	3.1	9349672
				9352578
Minor				
201	Workmanship	Level III	3.10	4.7.7

NOTES:
1/ Acceptance is based on meeting the requirement in 3.2.
2/ The magazines for the function test shall not be used for any other test.
3/ **The** same magazines shall be used for these tests. If applicable, the drop test shall be done last.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.2.2 Delete in its entirety and substitute the following new page 12 included as page 3.

PAGE 13

4.4.2.3 Delete characteristic 103 and 105 in there entirety. Renumber characteristic "104" to "103".

PAGE 14

4.5.2 Under characteristic a. hardness Delete "(see 4.7.12)" and substitute "(see 4.11)".

PAGE 20

4.7.9 Delete in its entirety and substitute the following:

"4.7.9 salt spray test For each item to be tested, five (5) parts shall be selected from each lot. The test for the clip shall be performed as specified in DOD-P-16232 and ASTM B 117 without the supplemental oil. The test for the spring, retention, magazine shall be as specified in ASTM B 117 for 24 hours after the application of the dry film lubricant (MIL-L-23398). Test procedures and equipment shall have the prior approval of the Government. If any part shows evidence of corrosion, it shall be classified as defective and the lot shall be rejected."

PAGE 21

4.7.12 Renumber paragraph to "4.7.11".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1005-A840)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.