INCH-POUND

MIL-S-70538A (AR)
AMENDMENT 2
24 April 2003
SUPERSEDING
AMENDMENT 1
25 July 1996

MILITARY SPECIFICATION

SAW, M249 AMMUNITION MAGAZINE ASSEMBLY AND FEEDSTRAP

MIL-S-70538A (AR) was inactivated after 14 December 1995 for new design.

This amendment forms a part of MIL-S-70538A (AR), dated 30 November 1994, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1:

Under Military Specifications delete "MIL-L-3150" and "MIL-C-16173" in their entirety.

* **Under Standards: Delete MIL-STD-109 in its entirety and substitute the following:**

"MIL-STD-1916 – DOD Preferred Methods for Acceptance of Product"

PAGE 7

Table I, Add the following characteristic:

"Classification of Characteristics 50 0-1 3.1 4.4.2.2, 4.4.2.3"

PAGE 8

* **Delete 4.4, 4.4.1, and 4.4.2 in their entirety and substitute the following:**

"4.4 Conformance verification.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

4.4.1 Inspection lot formation. Inspection lot formation shall be in accordance with the lot formation requirement of MIL-STD-1916, paragraph 4.2. The maximum lot size shall be 50,000 magazines or one month's production, whichever is smaller.

4.4.2 Classification of characteristics.

a. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. Conformance inspection shall include the characteristics of 4.4.2.1 through 4.4.2.3 and the tests of 4.7.

b. The definition of major and minor characteristics shall be in accordance with MIL-STD-1916, section 3.

c. The acceptance criteria shall be in accordance with MIL-STD-1916 for the verification levels listed in 4.4.2.1 through 4.4.2.3.

d. All inspections for Government acceptance shall be performed as least 48 hours after manufacture of the item.

e. Alternative conformance provisions. The contractor may use contractor proposed alternative Conformance acceptance provisions in accordance with MIL-STD-1916 in lieu of the verification provisions of this specification. Prior to applying the alternative conformance provisions, the contractor shall submit the proposed alternative conformance provisions for Government approval (see 6.4)."

PAGE 11

* **4.4.2.1: Delete included page 11 from amendment 1 and substitute new page 11 included as follows:**

PAGE 12

* **4.4.2.2: Delete included page 12 from amendment 1 and substitute new page 12 included as follows:**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Magazine Assembly	SHEET 1 OF 1	9349672

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	NEXT HIGHER ASSEMBLY: N/A / INSPECTION METHOD REFERENCE
CRITICAL	NONE			
MAJOR				
101	Functioning 1/ 2/	10 0-1	3.4	4.7.5
102	Dovetail mount 1/ 3/	20 0-1	3.5	4.7.3
103	Drop test 1/ 3/	5 0-1	3.6	4.7.4
104	Spring, retention, magazine 1/ 3/	20 0-1	3.7	4.7.2
105	Magazine component interface 1/ 3/	20 0-1	3.8	4.7.1
106	Certification		3.2	4.5
	Magazine and cover	4/	3.1	
	Feedstrap	4/	3.1	9352576, 9352577 9352578
MINOR				
201	Workmanship	Level II	3.10	4.7.7

NOTES:

1/ Acceptance is based on meeting the requirement in 3.2

2/ The magazine for the function test shall not be used for any other test.

3/ The same magazine shall be used for these tests. If applicable, the drop test shall be done last.

4/ A sample of three shall be selected from each mold cavity and inspected for the dimensions listed on the applicable drawing. One of the three selected shall be the last part produced for the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-S-70538A (AR)
AMENDMENT 2

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Spring, Retention, Magazine	1 OF 1	12944208

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	NEXT HIGHER ASSEMBLY 9349672 / INSPECTION METHOD REFERENCE
CRITICAL	**NONE**			
MAJOR				
101	**32.51 dimension (zone C-2)**	**Level III**	**3.2**	**SMTE**
102	**15.1 dimension (zone B-2)**	**Level III**	**3.2**	**SMTE**
103	**4.86 dimension (zone B-3)**	**Level III**	**3.2**	**SMTE**
104	**1.27 dimension (zone C-3)**	**Level III**	**3.2**	**SMTE**
105	**Coating weight**	**1/**	**3.2**	**4.7.10**
106	**Salt spray test**	**1/**	**3.2**	**4.7.9**
107	**Dry film lubricant salt spray**	**2/**	**3.2**	**2/**
MINOR				
201	**1.52 dimension (zone B-2)**	**Level II**	**3.2**	**SMTE**

NOTES:3.2

1/ Test and sample requirements before application of dry film lubricant shall be in accordance with TT-C-490.

2/ Test requirement, test method and sample requirements after application of dry film lubricant shall be in accordance with 4.7.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.3:

Delete majors 103 and 105 in their entirety. Renumber major 104 to 103.

* **Major 101 and 102, Delete "5 0-1" and substitute "1/"**

* **Major 104 and 105, Delete "Level I" and substitute "Level III"**

* **Add note 1/ as follows:**

"1/ A sample of five shall be selected from each lot. The lot size shall be as specified in 4.3.2 of MIL-DTL-16232. If any sample fails to meet the applicable requirement, the lot shall be rejected."

PAGE 14

4.5.2 Under characteristic a. hardness, delete "(see 4.7.12)" and substitute "(see 4.11)"

PAGE 20

4.7.9:

Delete in its entirety and substitute the following:

"4.7.9 Salt spray test. For each item to be tested, five (5) parts shall be selected from each lot. The test for the clip shall be performed as specified in DOD-P-16232 and ASTM B 117 without the supplemental oil. The test for the spring, retention, magazine shall be as specified in ASTM B 117 for 24 hours after the application of the dry film lubricant (MIL-L-23398). Test procedures and equipment shall have the prior approval of the Government. If any part shows evidence of corrosion, it shall be classified as defective and the lot shall be rejected."

* **Delete 4.7.9 in its entirety and substitute the following:**

"4.7.9 Salt spray test. For each item to be tested, five (5) sample parts shall be randomly selected from each lot. The test for the spring, retention, magazine and the clip shall be performed as specified in ASTM B 117 for 96 hours after the application of the final protective finishes. If any part shows evidence of corrosion, it shall be classified as defective and the lot shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

* **4.7.10, Delete in its entirety and substitute the following:**

"4.7.10 Coating weight. For each item tested, five (5) sample parts shall be randomly selected from each lot. Five (5) test panels of the same material and hardness of the representative parts may be used at the contractor's discretion. The test shall be performed as specified in MIL-DTL-16232 for the spring, retention, magazine and the clip. If any sample fails to meet the coating weight requirement of MIL-DTL-16232, it shall be classified as defective and the lot shall be rejected."

* **4.7.11, Delete in its entirety.**

PAGE 21

4.7.12, Renumber to 4.7.11

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army – AR

(Project 1005-0885)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.