INCH-POUND

A-A-55159

11 June 1992

COMMERCIAL ITEM DESCRIPTION

RESISTOR, WIREWOUND, INDUCTIVE, POWER TYPE

The General Services Administration
has authorized the use of
this commercial item description.

1. Abstract. This commercial item description (CID) covers the general requirements for wirewound, power type, resistors. These resistors are an all welded construction and rugged, flame resistant conformal vitreous enamel coating to ensure successful performance under high temperatures. Resistors supplied to this (CID) have hollow core construction which accommodates rigid mounting with brackets or through bolts.

1.1 Application. Resistors covered by this CID are intended for commercial/industrial applications and shall not be used in military systems needing stringent environmental and electrical requirements.

2. Part or identifying number (PIN). The PIN for the CID shall be as shown in the following example:

A-A-55159	-	XXX	K
CID number		Resistance value (see 3.1)	Resistance tolerance (See 3.2)


3. Salient characteristics.

3.1 Resistance. The nominal resistance expressed in ohms is identified by three characters, consisting of two digits and a letter. The letter is used simultaneously as a decimal point and a multiplier. For resistance values greater than or equal to 1 ohm but less than 1 kilohm, the letter "R" is used to represent a decimal point, greater than or equal to 1 kilohm but less than 1 megohm, the letter "K" is used to represent a decimal point. All digits preceding and following the letters "R" and "K" of the group represent significant figures. The following are examples of the resistance values:

1R0 = 1 ohm
10R = 10 ohms
101 = 100 ohms
1K0 = 1,000 ohms
12K = 12,000 ohms

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:43Z
Check the source to verify that this is the current version before use.



Length		Outside diameter		Inside diameter		Leads gauge
inch	mm	inch	mm	inch	mm	
2.000	50.80	0.438	11.11	0.250	6.35	18

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Configuration and dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:43Z
Check the source to verify that this is the current version before use.

3.2 Resistance value. The resistance values shall be 1 ohm to 100,000 ohms.

3.3 Resistance tolerance. Resistors are available in resistance tolerance (J) ±5 percent.

3.4 Temperature coefficient. The temperature coefficient shall be ±400 ppm < 5Ω, ±260 ppm ≥ 5Ω.

3.5 Maximum voltage. The maximum voltage rating shall be 750 volts.

3.6 Power rating. The power rating shall be 20.0 watts at 25°C derated to zero power at 350°C (see figure 2). When the resistance exceeds 10,000 ohms, derate power rating by 25 percent to improve reliability.




FIGURE 2. Derating curve.

3.7 Overload. Resistors shall be able to withstand 10 times rated wattage for 5 seconds.

3.8 Weight. The maximum weight shall be 16 grams.

3.9 Design and construction. Resistors supplied to this commercial item description shall have an all welded construction and rugged, flame resistant conformal vitreous enamel coating to ensure successful performance under high temperatures.

3.10 Marking. Resistors supplied to this commercial item description shall be marked with the manufacturers standard commercial PIN.

4. Quality assurance provisions.

4.1 Responsibility for inspection. The contractor is responsible for the performance of all inspections, examinations, and test requirements specified in the contract or purchase order. The contractor may use his own or any other facilities suitable for inspection requirements specified in the contract or purchase order, unless otherwise disapproved by the procuring activity. The acquiring activity reserves the right to perform any of the inspections set forth in the contract or purchase order where such inspections, examinations, and tests are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Contractor certification statement. The contractor shall certify and maintain objective quality evidence that the product offered meets this CID, and that the product conforms to the producers own drawings, specifications, standards, quality assurances practices, and is the same as the product provided as a bid sample. The acquiring activity reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.3 Certificate of compliance. A certificate of compliance shall accompany all resistors supplied to this CID.

5. Packaging.

5.1 Packaging. Preservation, packaging, labeling, and marking shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:43Z
Check the source to verify that this is the current version before use.

6. Notes. This section contains relevant information which is useful to buyers, users, and suppliers in the process of acquiring the item.

6.1 Ordering data. The contract or purchase order shall specify the following:

a. CID document number and revision and CID PIN.
b. Quality assurance provisions.
c. Packaging requirements.

6.2 Suggested sources of supply. Suggested source supply are listed herein. Additional sources will be added as they become available.

Suggested source of supply.

Vendor commercial PIN 1/	Vendor CAGE number
B20J***	44655

1/ Asterisks represent coded resistance values see 3.1 and 3.2.

Vendor CAGE number
44655

Vendor name and address
Ohmite Manufacturing
3601 Howard Street
Skokie, IL 60076

CONCLUDING MATERIAL

Civil Agency Coordinating Activity:
GSA - 7FXE

Preparing activity:
DLA-ES

(Project 5905-0325)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:43Z
Check the source to verify that this is the current version before use.