INCH-POUND

A-A-55197
08 April 1993

COMMERCIAL ITEM DESCRIPTION

BELT, MAN'S, WAIST, BLUE 334 (ARMY BAND UNIFORM)

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-B-43515.

Abstract. This description covers the requirements for belts that are intended for wear by enlisted men of the Department of the Army as a component of the army band uniform.

Classification. The belt shall be of one type in the following lengths:

Short - 42 ± 1/2 inches (1067 ± 13 mm)
Long - 51 ± 1/2 inches (1295 ± 13 mm)

Salient Characteristics. The belt shall be made from a strip of webbing ornamented with two stripes of braid; one stripe flush with the top edge of the belt and one stripe flush with the bottom edge of the belt. The braids shall be double stitched to each edge. Ends of all stitching, except when caught in other seams or stitching, shall be backstitched or overstitched 1/2 inch (13 mm) minimum. The finished belt shall be equipped with two belt keepers. One belt keeper shall be placed at each end of the belt to secure the belt buckle and buckle catch. Keepers shall be of the same braid as the ornamentation but shall be double thickness to fit snugly over the belt ends.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FSSD, 2800 South 20th Street, Philadelphia, PA 19101-8419, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8405

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Each keeper shall consist of a strip of braid cut 10 ± 1/8 inches (254 ± 3 mm) long. The strip shall be folded on itself and the side edges stitched not more than 1/16 inch (1.5 mm) from edge. Ends of strip shall be superimposed on each other and stitched 1/2 ± 1/16 inch (13 ± 1.5 mm) from end across the width of the braid. Fold ends back at the seam and stitch each end 1/8 ± 1/16 inch (3 ± 1.5 mm) each side of seam through the keeper. Turn keeper inside out, with ends to inside of the keeper, and thread one keeper over each end of belt. Do not stitch keepers to belt.

Materials.

Webbing, cotton. The basic material for the belt shall be multiple weave cotton webbing, 1-3/4 inches (45 mm) wide conforming to the following requirements; the weight (min., oz. per length) shall be 2.75; the yarns per inch (min.) shall be 333 warp and 100 filling; the thickness (inches) shall be 1/8 ± 1/64; the breaking strength (min., lbs.) full width shall be 1000; the yarn sizes (± 5%) 12/3 warp and 12/3 filling. The color shall be Blue 334 and shall show fastness to accelerated weathering equal to or better than a rating of "fair" when tested as specified in Table I. The dyed webbing shall show fastness to crocking equal to or better than a AATCC Chromatic Transference Scale rating not lower than 3.5 and shall show fastness to laundering (after 3 cycles) equal to or better than a rating of "good" when tested in accordance with Table I.

Braid. The braid for the belt ornamentation shall be a rayon or nylon braid containing a braided cotton stuffier for each vellum and one cotton stuffier end at each edge of the braid. The color shall be Goldenlite, Cable No. 17425. The width (inches) shall be 9/32; the weight (oz. per gross yd.) shall be 15 and picks per inch shall be 34 when tested in accordance with Table I. The dyed and finished braids shall show fastness to perspiration, wet dry-cleaning and light equal to or better than a rating of "good" and shall show fastness to crocking equal to or better than a AATCC Chromatic Transference Scale rating not lower than 2.5.

Thread. The cotton thread used for seaming and stitching shall be Type IC2, Ticket No. A, Goldenlite AJ, C.A. 66051, conforming to A-A-52094.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Table I. - Test methods

Characteristic	Test method
Weight	ASTM-D 3776 Option C
Yarns per inch	ASTM-D 3775
Thickness	ASTM-D 1777
Breaking strength	ASTM-D 1578
Colorfastness to:	
Accelerated weathering	FED-STD-5671 1/
Crocking	AATCC 8
Laundering	AATCC 61
Perspiration	AATCC 15
Wet dry-cleaning	AATCC 132
Light	AATCC 16
Picks per inch	FED-STD-5050

1/ Time of exposure shall be 40 hours.

Label/marking. The label/marking shall be direct printing, stamping, or stenciling. The contents shall consist of size, stock number (when applicable), contract number, and name of contractor and shall be applied to the inside of the belt, centered toward the end of the belt. The size of the characters shall be a minimum 18 point, approximately 1/4 inch (6 mm) and shall show fastness to laundering.

Workmanship. After completion, the finished belt shall be thoroughly cleaned, and all loose thread, lint, and foreign matter removed.

Product Demonstration Model. When required, offerers shall submit samples of their intended production. The Product Demonstration Model will consist of units independently developed. Product Demonstration Models will be analyzed and evaluated by the government. Evaluation criteria and basis for award are contained in the solicitation. Product Demonstration Models will be retained by the government. One (1) Product Demonstration Model approved by DPSC under the resultant contract will serve as a manufacturing standard for the corresponding production items delivered under this contract. Offerers are advised that the Product Demonstration Model does not relieve the successful offerer of his responsibility to perform in accordance with the Commercial Item Description specified above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Quality Assurance

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for, under the provisions of the contract. Reliance on contractor QA systems shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the government for acceptance comply with all requirements of the contract.

Examination. Belt lots shall be inspected in accordance with "Sampling Procedures and Tables for Inspection by Attributes", ANSI/ASQC Z1.4, published by the American Society for Quality Control.

Visual Examination. The belts shall be examined for the defects listed below. The lot size shall be expressed in units of belts. The sample unit is one belt. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5.

Defects. The belts shall be examined for the following defects: any hole, cut, tear, not firmly or tightly woven, abrasion mark affecting appearance or serviceability; color not as specified, appearance affected by shading or dye streaks; any spot or stain (outside); edges frayed or scalloped, thread ends not removed; marking missing, incorrect, or illegible; measurement of item not as specified; any component part omitted.

Dimensional Examination. The finished belt shall conform to the dimensions specified. Any dimension that is not within the established tolerance shall be classified as a defect. The sample unit shall be one belt; the inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Packaging Examination. The fully packaged shipping containers shall be examined in accordance with defects listed below. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and AQL, expressed in terms of defects per hundred units, shall be 2.5.

EXAMINE	DEFECT
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, or inadequate stapling
Content	Number of items in container is more or less than required
	NSN shown on one or more items not as specified on shipping container
Palletization	Length, width, or height exceeds specified maximum requirements
	Pallet type not as specified
	Load not bonded as specified

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, Packing, and Marking. The preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Source of Government Documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Sources of Nongovernment Documents.

ANSI/ASQC Z1.4 - Sampling Procedures and Tables For Inspection By Attributes

(Applications for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, NY 10018-3308.)

ASTM-D 3776 - Weight
ASTM-D 3775 - Yarns per inch
ASTM-D 1777 - Thickness
ASTM-D 1578 - Breaking strength

(Applications for copies should be addressed to American Society For Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AATCC 8 - Colorfastness to Crocking: AATCC Crockmeter Method
AATCC 15 - Colorfastness to Perspiration
AATCC 16 - Colorfastness to Light
AATCC 61 - Colorfastness to Laundering, Home, and Commercial: Accelerated
AATCC 132 - Colorfastness to Dry-cleaning

(Applications for copies should be addressed to American Association of Textile Chemists and Colorists (AATCC), P.O. Box 12215, Triangle Park, NC 27709-2215)

Custodian:
Army - GL

Civil Agency Coordinating Activity:
GSA - FSS

Preparing Activity:
DLA - CT

Project No. 8405-0217

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2. 3, and 8 In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	A-A-55197	930408

3. DOCUMENT TITLE
BELT, MAN'S, WAIST, BLUE 334 (ARMY BAND UNIFORM)

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible Attach extra sheets as needed)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Defense Personnel Support Center ATTN: DPSC-FSSD (12-3-D)	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code) 2800 South 20th Street P. O. Box 8419 Philadelphia, Pennsylvania 19101-8419	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.