NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-22885/108B
10 December 1991


SUPERSEDING
MIL-S-22885/108A
29 August 1988

PERFORMANCE SPECIFICATION SHEET

SWITCHES, PUSHBUTTON, ILLUMINATED, 4-LAMP, 0.750 SQUARE, SPDT, DPDT, 4PDT SILVER CONTACTS - 2 CIRCUIT (5 AMPERES) OR SPDT (7.5 AMPERES); GOLD CONTACTS - LOW LEVEL TO 1 AMPERE, SUNLIGHT READABLE DISPLAY (DRIPPROOF, WATERTIGHT, SPLASHPROOF, EMI/RFI SHIELDING, HIGH IMPACT SHOCK RESISTANT, COMMON TERMINATION SYSTEM, NIGHT VISION GOGGLE COMPATIBLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-S-22885.



Inches	mm
.010	0.25
.03	0.8
.032	0.81
.14	3.6
.185	4.7
.187	4.75
.23	5.8
.235	5.97
.55	14.0
.75	19.0
.760	19.30
1.125	28.58

FIGURE 1. Switch - type I, 2 pole (enclosure design 1, unsealed with solder terminals).


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 for three place decimals and ±.03 for two place decimals.
4. The mounting sleeve shall not exceed .760 square and shall be reversible so as to be usable with or without the mounting spacer. In either case, the switch shall accommodate mounting to panels from .032 to .187 thick.
5. A mounting spacer is supplied with each switch unit for MIL-P-7788 panel requirements and places the mounting flange flush with the top of a .235 thick edgelighted panel
6. Spacer is to be used only for edgelighted panels, discard otherwise
7. Pushbutton cap shall be designed to prevent incorrect insertion into switch housing
8. Pushbutton cap shall be held captive to switch body by retaining element to prevent accidental interchange, but shall allow replacement of the lamps.
9. Exact shape of switch is optional, provided dimensions specified are not exceeded
10. Terminals and basic switch identification shall be permanentlty marked as shown on figures 7 and 9.

FIGURE 1. Switch - type I, 2 pole (enclosure design 1, unsealed with solder terminals - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.





Inches	mm
010	0 25
.03	0.8
032	0 81
18	4.6
187	4.75
.235	5 97
.290	7 37
49	12 4
.760	19.30
.96	24.4
1.050	26.67

NOTES:

1. Dimensions are in inches
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± 010 for three place decimals and ± 03 for two place decimals.
4. The mounting sleeve shall not exceed 760 square and shall be reversible so as to be usable with or without the mounting spacer. In either case, the switch shall accommodate mounting to panels from .032 to .187 thick.
5. A mounting spacer is supplied with each switch unit for MIL-P-7788 panel requirements and places the mounting flange flush with the top of a .235 thick edgelighted panel
6. Spacer is to be used only for edgelighted panels, discard otherwise
7. Pushbutton cap shall be designed to prevent incorrect insertion into switch housing
8. Pushbutton cap shall be held captive to switch body by retaining element to prevent accidental interchange, but shall allow replacement of the lamps
9. Exact shape of switch is optional, provided dimensions specified are not exceeded
10. Terminals and basic switch identification shall be permanently marked as shown on figures 7 and 9.

FIGURE 2 Switch - type II, 2 pole (enclosure design 2, 3, and 4, dripproof, watertight, and splashproof with solder terminals)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.




FIGURE 3 Switch - type III (enclosure design 1; unsealed with 2 pole common terminal system)


Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 for three place decimals and ±.03 for two place decimals.
4. The mounting sleeve shall not exceed .760 square and shall be reversible so as to be usable with or without the mounting spacer. In either case, the switch shall accommodate mounting to panels from .032 to .187 thick.
5. A mounting spacer is supplied with each switch unit for MIL-P-7788 panel requirements and places the mounting flange flush with the top of a .235 thick edgelighted panel.
6. Spacer is to be used only for edgelighted panels, discard otherwise.
7. Pushbutton cap shall be designed to prevent incorrect insertion into switch housing.
8. Pushbutton cap shall be held captive to switch body by retaining element to prevent accidental interchange, but shall allow replacement of the lamps.
9. The Common Termination System (CTS) connector shall be designed and constructed in accordance with MIL-STD-1549. These items, M22885/10818200 for 2 pole switches and M22885/10BC8240 for 4 pole switches, shall be acquired from a source listed on QPL-22885.
10. The CTS connector shall be removable from the switch housing to allow the housing to be mounted separately. The connector may be wired during harnessing operations, allowing bench testing without the need of the switch housing.
11. The CTS connector shall be considered as a connector plug that may be separated from the switch housing for the convenience of installation.
12. The CTS connector shall be removable from the switch body by use of a M22885/10BT8234 CTS module extraction tool (see figure 10). This item shall be procured from a source listed on QPL-22885.
13. The CTS connector shall be capable of receiving MIL-C-39029/22-192 socket contacts crimped to a 20, 22, or 24 gauge wire.
14. The CTS connector shall be capable of having the socket contacts inserted or removed using an M81969/14-10 contact insertion/removal tool.
15. Exact shape of switch is optional provided dimensions specified are not exceeded.
16. Terminals and basic switch identification shall be permanently marked as shown on figures 7 and 9.

FIGURE 3. Switch - type III (enclosure design 1, unsealed with 2 pole common termination system) - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.



Inches	mm
.010	0.25
.03	0.8
.032	0.81
.18	4.6
.187	4.75
.235	5.97
.290	7.37
.49	12.4
.71	18.0
.760	19.30
.96	24.4
1.654	42.01

FIGURE 4. Switch - type IV (enclosure design 2, 3, and 4; dripproof, watertight, and splashproof with 2 pole common termination system).


Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 for three place decimals and ±.03 for two place decimals.
4. The mounting sleeve shall not exceed .760 square and shall be reversible so as to be usable with or without the mounting spacer. In either case, the switch shall accommodate mounting to panels from .032 to .187 thick.
5. A mounting spacer is supplied with each switch unit for MIL-P-7788 panel requirements and places the mounting flange flush with the top of a .235 thick edgelighted panel.
6. Spacer is to be used only for edgelighted panels, discard otherwise.
7. Pushbutton cap shall be designed to prevent incorrect insertion into switch housing.
8. Pushbutton cap shall be held captive to switch body by retaining element to prevent accidental interchange, but shall allow replacement of the lamps
9. The Common Termination System (CTS) connector shall be designed and constructed in accordance with MIL-STD-1549. These items, M22885/10818200 for 2 pole switches and M22885/10808240 for 4 pole switches, shall be acquired from a source listed on QPL-22885.
10. The CTS connector shall be removable from the switch housing to allow the housing to be mounted separately. The connector may be wired during harnessing operations, allowing bench testing without the need of the switch housing.
11. The CTS connector shall be considered as a connector plug that may be separated from the switch housing for the convenience of installation.
12. The CTS connector shall be removable from the switch body by use of a M22885/10818234 CTS module extraction tool (see figure 10). This item shall be procured from a source listed on QPL-22885.
13. The CTS connector shall be capable of receiving MIL-C-39029/22-192 socket contacts crimped to a 20, 22, or 24 gauge wire.
14. The CTS connector shall be capable of having the socket contacts inserted or removed using an M81969/14-10 contact insertion/removal tool
15. Exact shape of switch is optional provided dimensions specified are not exceeded.
16. Terminals and basic switch identification shall be permanently marked as shown on figures 7 and 9.

FIGURE 4 Switch - type IV (enclosure design 2, 3, and 4; dripproof, watertight, and splashproof with 2 pole common termination system) - Continued

Source: https://assist.dla.mil -- Downloaded: 202640-19T14:37Z
Check the source to verify that this is the currenversion before use.



Inches	mm
010	0.25
03	0 8
.032	0.81
14	3.6
185	4 70
187	4 75
23	5 8
235	5 97
.55	14 0
.60	15.24
.75	19 0
760	19 30
2.52	64 0

FIGURE 5 Switch - type V (enclosure design 1 unsealed with 4 pole common termination system)


Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 for three place decimals and ±.03 for two place decimals.
4. The mounting sleeve shall not exceed .760 square and shall be reversible so as to be usable with or without the mounting spacer. In either case, the switch shall accommodate mounting to panels from .032 to .187 thick.
5. A mounting spacer is supplied with each switch unit for MIL-P-7788 panel requirements and places the mounting flange flush with the top of a .235 thick edgelighted panel.
6. Spacer is to be used only for edgelighted panels, discard otherwise.
7. Pushbutton cap shall be designed to prevent incorrect insertion into switch housing.
8. Pushbutton cap shall be held captive to switch body by retaining element to prevent accidental interchange, but shall allow replacement of the lamps
9. The Common Termination System (CTS) connector shall be designed and constructed in accordance with MIL-STD-1549. These items, M22885/10818200 for 2 pole switches and M22885/10808240 for 4 pole switches, shall be acquired from a source listed on QPL-22885.
10. The CTS connector shall be removable from the switch housing to allow the housing to be mounted separately. The connector may be wired during harnessing operations, allowing bench testing without the need of the switch housing.
11. The CTS connector shall be considered as a connector plug that may be separated from the switch housing for the convenience of installation.
12. The CTS connector shall be removable from the switch body by use of a M22885/10818234 CTS module extraction tool (see figure 10). This item shall be procured from a source listed on QPL-22885.
13. The CTS connector shall be capable of receiving MIL-C-39029/22-192 socket contacts crimped to a 20, 22, or 24 gauge wire
14. The CTS connector shall be capable of having the socket contacts inserted or removed using an M81969/14-10 contact insertion/removal tool.
15. Exact shape of switch is optional provided dimensions specified are not exceeded.
16. Terminals and basic switch identification shall be permanently marked as shown on figures 7 and 9.

FIGURE 5. Switch - type V (enclosure design 1: unsealed with 4 pole common termination system) - Continued

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.



Inches	mm
.010	0.25
.03	0.8
.032	0.81
.18	4.6
.187	4.75
.235	5.97
.290	7.37
.49	12.4
.60	15.24
.760	19.30
.96	24.4
2.43	61.7

FIGURE 6. Switch - type VI (enclosure design 2, 3, and 4; dripproof, watertight, and splashproof with 4 pole common termination system).

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 for three place decimals and ±.03 for two place decimals.
4. The mounting sleeve shall not exceed .760 square and shall be reversible so as to be usable with or without the mounting spacer. In either case, the switch shall accommodate mounting to panels from .032 to .187 thick.
5. A mounting spacer is supplied with each switch unit for MIL-P-7788 panel requirements and places the mounting flange flush with the top of a .235 thick edgelighted panel.
6. Spacer is to be used only for edgelighted panels, discard otherwise.
7. Pushbutton cap shall be designed to prevent incorrect insertion into switch housing
8. Pushbutton cap shall be held captive to switch body by retaining element to prevent accidental interchange, but shall allow replacement of the lamps
9. The Common Termination System (CTS) connector shall be designed and constructed in accordance with MIL-STD-1549. These items, M22885/10818200 for 2 pole switches and M22885/108C8240 for 4 pole switches, shall be acquired from a source listed on QPL-22885.
10. The CTS connector shall be removable from the switch housing to allow the housing to be mounted separately. The connector may be wired during harnessing operations, allowing bench testing without the need of the switch housing
11. The CTS connector shall be considered as a connector plug that may be separated from the switch housing for the convenience of installation
12. The CTS connector shall be removable from the switch body by use of a M22885/108T8234 CTS module extraction tool (see figure 10) This item shall be procured from a source listed on QPL-22885.
13. The CTS connector shall be capable of receiving MIL-C-39029/22-192 socket contacts crimped to a 20, 22, or 24 gauge wire.
14. The CTS connector shall be capable of having the socket contacts inserted or removed using an M81969/14-10 contact insertion/removal tool
15. Exact shape of switch is optional provided dimensions specified are not exceeded.
16. Terminals and basic switch identification shall be permanently marked as shown on figures 7 and 9.

FIGURE 6 Switch - type V1 (enclosure design 2, 3, and 4; dripproof, watertight, and splashproof with 4 pole common termination system) - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.




FIGURE 7. Switch and lamp terminations - dimensions and center location.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

2 POLE

4 POLE

COMMON TERMINATION

SYSTEM




Inches	mm	Inches	mm
.020	0.51	.106	2.69
025	0 64	.125	3.18
.03	0 8	150	3.81
.053	0 71	.213	5.41
.06	1.5	.237	6.02
.069	1.75	.500	12.70
.075	1 90	.695	17.65

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for general information only.
3 Unless otherwise specified, tolerances are ±.010 (0.25 mm). For three place decimals and ± 03 for two place decimals.

FIGURE 7. Switch and lamp terminations - dimensions and center location - Continued

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

LAMP CIRCUIT SCHEMATIC



LAMP AND TERMINAL POSITIONS AS VIEWED FROM THE FRONT OF THE DISPLAY

SWITCH CIRCUIT SCHEMATIC






FIGURE 8 Lamp and switch circuit configurations, schematics, and recommended panel cutouts

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

RECOMMENDED PANEL CUTOUTS



TYPE I, III, AND V SWITCHES



TYPE II, IV, AND VI SWITCHES

Type I, III, and V switches

Type II, IV, and VI switches

Inches	mm
.010	0.25
031	0.79
.696	17.68
750	19 05
985	25.02


NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only

FIGURE 8. Loop and switch circuit configurations, schematics, and recommended panel cutouts - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

TYPE I AND II

COMMON GROUND, SOLDER TERMINATIONS TYPE I AND II



TYPE I AND II

SPLIT GROUND, SOLDER TERMINATIONS TYPE I AND II





FIGURE 9. Switch poles and lamp terminal arrangements and identification

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

COMMON GROUND, CTS TYPE III AND IV



SPLIT GROUND, CTS TYPE III AND IV






FIGURE 9 Switch poles and lead terminal arrangements and identification - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

COMMON GROUND, 4 POLE CTS
TYPE V AND VI



SPLIT GROUND, 4 POLE CTS
TYPE V AND VI



NOTES:
1. All 2 pole common termination system (CTS) switches have identical switch and lamp terminal arrangement identification. All 4 pole CTS switches have identical switch and lamp terminal arrangement identification.
2. To make the various CTS combinations, an MS27488-20 sealing plug is placed in the locations not to be used. In the above identifications, blackened circles indicate where the sealing plugs shall be located to form the described variation.
3. "SKT" identifies the socket side.
4. A and B or H, J, K and L identify each switch
5. C, B, G, F, D, and A identify the lamp circuit terminations
6. 1, 2, 3, and 4 identify the switch contact termination.

FIGURE 9. Switch poles and lamp terminal arrangements and identification - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.




FIGURE 10 CTS modules and extraction tools

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.




FIGURE 10 CTS modules and extraction tools - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.


Inches	mm	Inches	mm	Inches	mm	Inches	mm
.010	0.25	.080	2.03	.220	5.59	.608	15.4
.021	0.53	.090	2.29	.236	5.99	.634	16.1
.025	0.64	.093	2.36	.260	6.60	.640	16.2
.030	0 76	.094	2 39	.263	6.68	.652	16.54
.032	0.81	.100	2.54	.268	6.82	.656	16.60
.038	0.97	.106	2.69	.287	7.29	71	18 06
040	1.02	133	3.38	.290	7.37	.75	19.26
.050	1.27	135	3.43	.345	8.76	.81	20.66
.060	1.52	.138	3.51	.35	8.9	2.42	61.47
062	1.58	.150	3.81	.426	10.82	3 00	76.2
.065	1.65	.158	4.01	.46	11 7		
066	1 68	.160	4 06	.472	11.99		
.069	1.75	.164	4.17	.500	12.70		
070	1 78	170	4.32	.502	12 75		
078	1.98	.213	5 41	.60	15.2		

FIGURE 10. CTS modules and extraction tools - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

CTS MODULE EXTRACTION TOOL
(M22885/10818234)

PART NUMBER M22885/10818208 HAS BEEN CANCELED
AND REPLACED WITH M22885/10818234




DETAIL A - A

NOTES.
1 Dimensions are in inches
2 Metric equivalents are given for general information only
3 Above dimensions are shown for information only

FIGURE 10. CTS modules and extraction tools - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

RETAINING ELEMENT



NOTES
1. Retaining element shall be permanently attached to switch housing
2. Retaining element shall allow pushbutton cap to be pulled fully out of switch housing and dropped down 90 degrees to facilitate lamp replacement (Pushbutton cap must still be retained.)
3. Pushbutton cap shall be removable from the retaining element to allow caps to be changed if necessary

FIGURE 11. Pushbutton cap retaining element.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction: See figures 1 through 11

Complete switch shall consist of:

One switch body, including a reversible mounting sleeve, a panel mounting spacer, and an integral cap retaining element. Type II, IV and VI switch bodies also include a splashproof mounting flange. When specified, type III, IV, V, and VI switch bodies also include an environmentally sealed plug-on connector designed in accordance with common termination system (CTS) requirements of MIL-STD-1549.

One lens module pushbutton cap. Includes legend module configuration, lamp circuit type, night vision goggle compatibility when specified, EMI/RFI shielding efficiency when specified, and an integral dripproof, watertight, and splashproof seal when specified.

Four lamps: T-1 subminiature flange base not included, order separately.

Material:

Housing.

Type I and type II: Aluminum alloy, anodized black

Type III, type IV, type V and type VI: Corrosion-resistant steel

Mounting sleeve: Corrosion resistant steel or aluminum alloy. Aluminum alloy is surface treated in accordance with MIL-STD-171

Panel mounting spacer: Corrosion-resistant steel, black, for type I, type III, and type V. Thermoplastic, black, for type II, type IV, and type VI

Front lens material. High temperature heat-resistant thermoplastic

Enclosure design:

Symbol 1 (unsealed) for type I, type III, and type V.

Symbol 2 (dripproof) for type II, type IV, and type VI.

Symbol 3 (watertight) for type II, type IV, and type VI.

Symbol 4 (splashproof) for type II, type IV, and type VI

Temperature characteristic: 1 (-55°C to +85°C for type I, type III, and type V), (-48°C to +85°C for type II, type IV, and type VI)

Vibration grade: 3 (10 to 2,000 Hz)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

Operating characteristics

Actuation force: 2 to 5 pounds

Actuation travel: 0.150 ±0.030 inch, except 0.100 ±0.030 inch for high impact shock units.

Lens module extraction force. 2 to 5 pounds, except 2 to 8 pounds for high impact shock units.

Strength of actuator: 25 pounds.

Sand and dust: Applicable to type II, type IV, and type VI.

Shock. 75 g (MIL-STD-202, method 213, test condition B).

High impact shock: MIL-STD-202, method 207, when specified. Applicable to indicator and momentary action type II, type IV, and type VI only.

Weight:

Connector (CTS). 6 grams maximum

Type I (solder terminations): 18 grams maximum.

Type II (solder terminations): 20 grams maximum.

Type III (CTS) 26 grams maximum.

Type IV (CTS): 28 grams maximum.

Type V (4 pole CTS) 38 grams maximum

Type VI (4 pole CTS) 41 grams maximum

Seal:

Watertight test. When specified, test in accordance with MIL-S-22885 and MIL-STD-108 There shall be no leakage of water through the panel and pushbutton seals as determined by visual examination and the dielectric withstanding voltage test.

Splashproof test When specified, test in accordance with MIL-S-22885 and MIL-STD-108 There shall be no leakage of water through the panel and pushbutton seals as determined by visual examination and the dielectric withstanding voltage test.

Mechanical endurance: 100,000 cycles.

Unsealed switches: 10,000 cycles of operation at -55°C ±2°C, 20,000 cycles of operation at +85°C ±2°C, and 70,000 cycles of operation at room temperature.

Sealed switches: 10,000 cycles of operation at -46°C ±2°C, 20,000 cycles of operation at +85°C ±2°C, and 70,000 cycles of operation at room temperature. Cycling rate shall not exceed 18 cycles per minute during low temperature portion of the mechanical endurance test

Electrical endurance: 50,000 cycles.

Intermediate current: Applicable, 50,000 cycles.

Low level life: Applicable to gold-plated contacts, 50,000 cycles.

Source: https://assist.dla.mil -- Downloaded: 202640-19T14:37Z
Check the source to verify that this is the currenversion before use.

Electrical ratings See table I

Color and luminance. See table II and table III for display type S. See table IV and table V for display type N.

Sunlight readability (display type S):

Requirements: All legends shall be capable of being read in direct sunlight and at any glare-producing, specularly reflective angles up to 15 degrees ±2 degrees to the normal of the display viewing surface The average luminance contrast ratio of each lighted legend character to background shall be 0.6 minimum (0.4 minimum for blue). The average luminance contrast ratio of each unlighted legend character to background shall have an absolute value equal to or less than 0.1. The average luminance contrast ratio for each color shall not be less than the values listed in tables VI and VII for the respective glare-producing angle.

Test method The test procedure for measuring the average luminance contrast ratios for sunlight readability shall be the specular reflectance test in accordance with MIL-S-22885.

Color contrast In addition to luminance contrast, color contrast is an important factor in sunlight readability. The effects of both luminance contrast and color contrast can be combined into a single value called the index of discrimination (ID). The index of discrimination value for all legend characters shall be greater than 1.0 for those legends to be considered as sunlight readable The minimum value for the index of discrimination are also listed in table VI and table VII. The index of discrimination is determined by using the same specular reflectance test setup shown in MIL-S-22885, and using the following formulas for calculation

$$C_L = \frac{\log_{10}\left(\frac{L_1 + L_2}{L_b}\right)}{0\ 15} \qquad \textit{Formula I}$$

$$C_c = \frac{\sqrt{(u_1 - u_b)^2 + (v_1 - v_b)^2}}{0.027} \qquad \textit{Formula II}$$

$$ID = \sqrt{C_L^2 + C_c^2} \qquad \textit{Formula III}$$

Where

ID = Index of discrimination.
C_L = Luminance contrast.
C_c = Chrominance contrast
L_1 = Average character luminance of energized legend.
L_2 = Average reflected character luminance of nonenergized legend.
L_b = Average reflected background luminance.
u_1, v_1 = Average 1960 UCS color coordinates of the reflected and emitted light from the illuminated legend
u_b, v_b = Average 1960 UCS color coordinates of the reflected background light

The illuminated chromaticity limits and minimum average luminance for sunlight readable displays are listed in table II and table III

Source: https://assist.dla.mil -- Downloaded: 202640-19T14:37Z
Check the source to verify that this is the currenversion before use.

Display type N:

Requirements: All legends shall be visible white with an opaque black background. The legend characters shall always be visible in any light ambience except in darkened conditions. In darkened conditions, the legend characters shall illuminate in color with an average luminance of 0.5 to 3.0 foot-lamberts when energized at full rated voltage. See table IV and table V for specific colors and luminance.

Test method: The test procedure for measuring the average luminance and color of the illuminated visible white legend characters shall be in accordance with MIL-S-22885.

Night vision imaging system (NVIS) compatibility:

NVIS Green B: Shall meet all MIL-L-85762 requirements for illuminated controls for type I, class A and type II, class B equipment.

NVIS Yellow: Shall meet all MIL-L-85762 requirements for caution signals for type I, class A and type II, class B equipment.

Test methods: The test procedure for measuring luminance, chromaticity and spectral radiance shall be in accordance with MIL-L-85762 for illuminated controls (for NVIS green B) and caution signals (for NVIS yellow).

The night vision goggle compatible feature, when specified, is in addition to the sunlight readable feature and all minimum sunlight readable requirements shall be maintained on all type S displays along with the unique requirements for night vision goggle compatibility. When night vision goggle compatibility is specified for type N displays (visible legend), all the requirements for color and NVIS radiance in accordance with MIL-L-85762 shall be satisfied when display is operated at the specified luminance level (see table V).

EMI/RFI shielding:

Requirement: When specified, the EMI/RFI shielding attenuation shall be not less than 60 dB over the frequency range from 100 to 1,000 MHz.


Test method: Switches shall be tested to determine the shielding effectiveness in accordance with MIL-S-22885, for shielding efficiency.

Measurements are to be performed at the following frequencies:

Frequency	Minimum attenuation
100 MHz	60 dB
200 MHz	60 dB
400 MHz	60 dB
600 MHz	60 dB
800 MHz	60 dB
1,000 MHz	60 dB

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

Part or Identifying Numbers (PIN): PIN's are assigned as follows.



PIN's generated do not include display type (N or S), segment color (see table XIV), legends or lamp type. When lamps are to be included with the switch, equipment manufacturers may add an additional suffix number from table XIII to the military part number for reference only. Acquisition documents shall be prepared in accordance with ordering data in section 6 of MIL-S-22885 for category II switches.

Lamp types usable in the lens modules: Table XIII is shown for information only.

Lens module legend positions: Table XIV is shown for information only.

Qualification inspection: All applicants for qualification approval shall demonstrate that each of their items conform to all the requirements specified in the applicable documents singularly and in combination with all other previously qualified items, regardless of manufacturer. Table XV is based on the use of MIL-S-8805 category I or category II basic switches listed on QPL-8805.

Group submission: See table XV.

Group A inspection: See table XVI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Contact material	Load	Sea level			50,000 feet	
		28 V dc		115 V ac, 60 Hz	28 V dc	
		NO or NC (amperes max)	2 circuit (amperes max)	NO or NC (amperes max)	NO or NC (amperes max)	2 circuit (amperes max)
Silver (gold flash)	Resistive	7.5	5.0	7.5	4.0	3.0
	Inductive	4.0	2.0	4.0	2.5	1.0
	Motor	4.0	---	---	---	---
	Lamp	1.0	---	---	---	---
Gold plated	Resistive	1.0	---	---	1.0	---
	Inductive	0.5	---	---	0.5	---
	Low level life applicable: 30 millivolts maximum or peak ac at 10 milliamperes maximum.					

TABLE II. Illuminated chromaticity limits and luminance for sunlight readable displays (type S).

Color	Color code	x 1/	y 1/	Minimum average character luminance with or without EMI/RFI shielding
Red	R	.695 .710 .655 .660	.285 SL 2/ .325 SL 2/	150 foot-lamberts
Green	G	.300 .300 .380 .380	SL 2/ .600 .600 SL 2/	200 foot-lamberts
Yellow	Y	.562 .570 .596 .605	.415 SL 2/ .382 SL 2/	300 foot-lamberts
Blue	B	.230 .230 .320 .320	.420 .350 .350 .420	150 foot-lamberts
White	W	.400 .460 .400 .460	.420 .420 .380 .380	250 foot-lamberts

1/ Chromaticity is expressed as x and y on the CIE chromaticity diagram. Values shown are corners of the limiting envelope.
2/ SL - spectrum locus (where intersected by other coordinate pair).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE III. Illuminated chromaticity limits and luminance for NVIS night vision goggle compatible, sunlight readable displays (type S).

Color	Color code	u' 1/	v' 1/	r 1/	Minimum average character luminance with or without EMI/RFI shielding
NVIS Green B	J	131	.623	057	200 foot-lamberts
NVIS Yellow	K	.274	.622	.083	200 foot-lamberts

1/ Chromaticity is expressed as u' and v' coordinates of the 1976 UCS diagram. The values shown describe a circle whose center is at u', v', and of radius r. The area enclosed by this circle intersecting the spectral locus is the envelope limiting the acceptable color space.

TABLE IV. Illuminated chromaticity limits and luminance for visible legend displays (type N).

Color	Color code	x 1/	y 1/	Character luminance with or without EMI/RFI shielding
Blue/ white	V	400 460 400 460	420 420 .380 .380	0.5 to 3.0 foot-lamberts
Red	N	.695 .710 655 660	.285 SL 2/ 325 SL 2/	0.5 to 3.0 foot-lamberts

1/ Chromaticity is expressed as x and y on the CIE chromaticity diagram. Values shown are corners of the limiting envelope.

2/ SL - spectrum locus (where intersected by other coordinate pair).

TABLE V. Illuminated chromaticity limits and luminance for NVIS night vision goggle compatible, visible legend displays (type N).

Color	Color code	u' 1/	v' 1/	r 1/	Character luminance with or without EMI/RFI shielding
NVIS Green B	L	131	623	057	0 5 to 3 0 foot-lamberts

1/ Chromaticity is expressed as u' and v' coordinates of the 1976 UCS diagram. The values shown describe a circle whose center is at u', v', and of radius r. The area enclosed by this circle intersecting the spectral locus is the envelope limiting the acceptable color space

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T14:37Z
Check the source to verify that this is the currentversion before use.

TABLE VI Minimum contrast ratios 1/ and minimum indexes of discrimination 2/ for sunlight readable displays (type S) with or without EMI/RFI shielding.

Color 3/	Color code	Condition 1 ($\phi1 = \phi2 = 15°$)		Condition 2 ($\phi1 = \phi2 = 30°$)	
		Contrast ratio	Index of discrimination	Contrast ratio	Index of discrimination
Red	R	0.6	2.0	0.3	1.4
Green	G	0.6	1.6	0 3	1.2
Yellow	Y	0 6	1.6	0.4	1.2
Blue	B	0.4	1.2	0.2	1 1
White	W	0.6	1 2	0 2	1 1

1/ Minimum average contrast of each legend character

2/ The index of discrimination takes into account both the luminance contrast and the chrominance contrast.

3/ Application note: In addition to luminance contrast, color contrast is an important factor in readability. Colors in table are listed in order of general preference Red has the best color contrast during sunlight conditions, blue and white have the poorest color contrast

TABLE VII Minimum contrast ratios 1/ and minimum indexes of discrimination 2/ for NVIS night vision goggle compatible sunlight readable displays (type S) with or without EMI/RFI shielding.

Color 3/	Color code	Condition 1 ($\phi1 = \phi2 = 15°$) 4/	
		Contrast ratio	Index of discrimination
NVIS green B	J	0 6	1.6
NVIS yellow	K	0 6	1 4

1/ Minimum average contrast of each legend character

2/ The index of discrimination takes into account both the luminance contrast and the chrominance contrast.

3/ Application note In addition to luminance contrast, color contrast is an important factor in sunlight readability Colors in table are listed in order of general preference for sunlight readability

4/ Condition 2 is not applicable to NVIS compatible colors

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE VIII. Lens module configurations.





	Configurations							
								
Standard lighting designations	B	C	D	E	F	G	J	H
MVIS compatible designations	K	L	M	N	P	Q	R	S

TABLE IX. Switch housing termination configuration.

Termination type	Designation
Turret terminals	1
Wire wrap/PCB terminals	3
CTS (SPDT, DPDT and indicator light)	
Without connector module 1/	4
With connector module 2/	5
CTS (4PDT only)	
Without connector module 1/	A
With connector module 2/	B

1/ The common termination system designation 4 or A is for the CTS switch housing excluding the connector module. The connector module is provided separately so wiring and harnessing can be accomplished independent of the switch housing.

2/ The common termination system designation 5 or B is for the CTS switch housing including the connector module. The connector module is provided plugged into the switch housing (sealing plugs are in their appropriate positions).

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE X Switch circuit configuration, poles and contact material.

Switch poles and circuit configuration 1/	Contact material	
	Silver with gold flash	Gold plated
SPDT-SB	1	5
DPDT-SB	2	6
SPDT-DB	3	7
DPDT-DB	4	8
4PDT-SB	A	F
4PDT-DB	C	H
Indicator light	Q	Q

1/ SPDT - Single pole, double throw.
SB - Single break
DPDT - Double pole, double throw.
DB - Double break.
4PDT - Four pole, double throw.

TABLE XI Enclosure design and EMI/RFI shielding efficiency.

Enclosure design	Without EMI/RFI shielding	With EMI/RFI shielding
1-Unsealed	1	4
2-Dripproof 3-Watertight 4-Splashproof	2	5
High impact shock resistant 1/ 2-Dripproof 3-Watertight 4-Splashproof	3	6

1/ Not available in alternate action

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE XII. Lamp circuit configuration and actuation


Lamp circuit configuration	Actuation		
	Momentary	Alternate	Indicator
Common ground	1	4	7
Horizontal split ground	2	5	8
Vertical split ground	3	6	9

TABLE XIII. Lamp types usable in the lens modules. 1/

Lamp type	MS number	Voltage	Current	MSCP	Life hours
1	---	5	.060	.15	6500
2	MS-24515	5	115	15	40000
6	MS-3338	28	.024	.15	16000

1/ Lamps with a mean spherical candle power of 15 minimum must be used to obtain the sunlight readability specified. Replacement lamps must be aged and selected to meet this requirement.

TABLE XIV Lens module legend positions. 1/



1/ Segment numbers are to be used to identify color and legend positions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE XV. Qualification inspection, group submission

Test sample	Inspection table X of MIL-S-22885		Additional testing	Extent of approval 1/
	Group	Number of samples		
M22885/108144482 2/	I II III VI VII VIII	14 4 (from group I) 3/ 4/ 2 (from group I) 2 (from group I) 5/ 4 (from group I) 4/ 6/ 7/ 20 8/	Sunlight readable testing shall include determining the index of discrimination. NVIS color and NVIS radiance measurements shall be taken where applicable after sunlight readable testing.	All
M22885/108184482 2/	I VII	2 9/ 2 (from group I) 4/ 10/		
M22885/108BC61B2 2/	I II III V VI VII	12 4 (from group I) 4/11/12/ 2 (from group I) 2 (from group I) 4/ 12/ 2 (from group I) 13/ 2 (from group I) 4/ 14/		
M22885/108123282 2/	I II	4 4 (from group I) 4/11/12/		
2 samples - any wirewrap/pc terminal switch			Solderability Terminal strength	

1/ Includes single break, silver contacts, gold contacts, and wire wrap termination when the basic switches are qualified to MIL-S-8805/101 category I or category II.
2/ Lens module configuration shall be "B" in accordance with table VIII.

Test legend:

REMOTE
ALT LOW

3/ Shock method I.
4/ During tests requiring switch to be mounted, one-half of the sample units shall be mounted utilizing the mounting spacer. The remaining half shall be mounted with the mounting spacer removed.
5/ Inductive dc NO-NC only, sea level.
6/ Two units shall be subjected to the mechanical endurance test.
7/ Two units shall be tested for intermediate current.
8/ Twenty lens modules only, two for each of 10 colors shall be tested for color, luminance, and sunlight readability where applicable. A single separate switch body shall be provided so lens modules can be individually energized.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

TABLE XV. Qualification inspection, group submission - Continued.

9/ Contact resistance measurement for gold contact switches which are to be subjected to low level life testing shall be made in accordance with MIL-S-22885, switch contact resistance paragraph, except the test current shall not exceed 10 milliamperes and the open-circuit test voltage shall not exceed 30 millivolts dc. Maximum contact resistance is 3 ohms
10/ Two units shall be tested for low level life only.
11/ Shock method II
12/ Sealing shall be verified by performing the watertight test and the splashproof test only.
13/ Resistive dc two circuit only, see level.
14/ Intermediate current test not required.

TABLE XVI. Group A inspection.

Inspection
Seal (when applicable)(external inspection only)
Visual and mechanical examination
Operating characteristics
Dielectric withstanding voltage
Contact resistance 1/
Sunlight readability 2/
NVIS compatibility 3/

1/ Contact resistance measurements for gold contact switches shall be measured in accordance with switch contact resistance paragraph of MIL-S-22885, except the test current shall not exceed 10 milliamperes and the open-circuit test voltage shall not exceed 30 millivolts dc Maximum contact resistance is 3 ohms

2/ Test one switch per color and use these as visual standards. Visually inspect all switches in each lot against the appropriately colored standard switch. The switches used as visual standards shall be certified annually by performing the sunlight readability test

3/ Test one switch each for NVIS green B and NVIS yellow in accordance with the requirements of MIL-L-85762. These units will serve as standards when viewed with an image intensifier. Visually inspect all NVIS compatible switches in each lot with an image intensifier against the appropriate standard switch. The switches used as visual standards shall be certified annually by performing the NVIS compatibility test.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.

Revision letters are not used to denote changes due to the extensiveness of the changes

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 99

User activity:
Army - AT

Preparing activity
Navy - EC

Agent:
DLA - ES

(Project 5930-1474)

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:37Z
Check the source to verify that this is the current version before use.