NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND
MIL-PRF-22885/108B
AMENDMENT 2
21 July 1997
SUPERSEDING
AMENDMENT 1
1 July 1997

PERFORMANCE SPECIFICATION SHEET

SWITCHES, PUSHBUTTON, ILLUMINATED,
4-LAMP, 0.750 SQUARE, SPDT, DPDT, 4PDT
SILVER CONTACTS - 2 CIRCUIT (5 AMPERES) OR SPDT (7.5 AMPERES);
GOLD CONTACTS - LOW LEVEL TO 1 AMPERE, SUNLIGHT READABLE DISPLAY
(DRIPPROOF, WATERTIGHT, SPLASHPROOF, EMI/RFI SHIELDING, HIGH IMPACT
SHOCK RESISTANT, COMMON TERMINATION SYSTEM, NIGHT VISION GOGGLE COMPATIBLE)

This amendment forms a part of MIL-S-22885/108B, dated 10 December 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 24

Material, panel mounting spacer: Delete and substitute:

"Panel mounting spacer: Corrosion resistant steel, black, or thermoplastic, black for type I, type III and type V. Thermoplastic, black for type II, type IV and type VI."

PAGE 25

* Weight: Delete and substitute:

"Weight:

Connector (CTS): 6 grams maximum.

4 pole connector (CTS): 6 grams maximum.

Type I (solder terminations): 19 grams maximum.

Type II (solder terminations): 21 grams maximum.

Type III (CTS): 26 grams maximum.

Type IV (CTS): 28 grams maximum.

Type V (4 pole CTS): 38 grams maximum.

Type VI (4 pole CTS): 41 grams maximum."

PAGE 26

* Sunlight readability (display type S), requirements, second sentence, delete: "(0.4 minimum for blue)" and substitute: "(0.4 minimum for blue and NVIS red)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

PAGE 27

Night vision imaging system (NVIS) compatibility: Add:

"NVIS Green A: Shall meet all MIL-L-85762 requirements for illuminated controls for type I, class A and type II, class B equipment."

After NVIS Yellow: Add:

"NVIS Red: Shall meet all MIL-L-85762 requirements for warning signals for type II, class B equipment."

After night vision paragraph: Add:

"Lens module pushbutton caps containing NVIS compatible displays are marked with NVIS Type ( ), Class ( ), in accordance with MIL-L-86762."

PAGE 28

After Group A inspection: Add:

"Group B inspection: See table XVII."

PAGE 30

TABLE III: Delete and substitute:

"TABLE III. Illuminated chromaticity limits and luminance for NVIS night vision goggle compatible, sunlight readable displays (type S).

Color	Color code	u' 1/	v' 1/	r 1/	Minimum average character luminance with or without EMI/RFI shielding
NVIS Green A	P	.088	.543	.037	200 foot Lamberts
NVIS Green B 2/	J	.131	.623	.057	200 foot Lamberts
NVIS Yellow 2/	K	.274	.622	.083	200 foot Lamberts
NVIS Red 2/	S	.450	.550	.060	200 foot Lamberts

1/ Chromaticity is expressed as u' and v' coordinates of the 1976 UCS diagram. The values shown describe a circle with center at u', v', and of radius r.
2/ The area enclosed by the described circle intersecting the spectral locus is the envelope limiting the acceptable color space."

* TABLE V: Delete and substitute:

"TABLE V. Illuminated chromaticity limits and luminance for NVIS night vision goggle compatible, visible legend displays (type N).

Color	Color code	u' 1/	v' 1/	r 1/	Character luminance with or without EMI/RFI shielding
NVIS Green A	M	.088	.543	.037	0.5 to 3.0 foot-Lamberts
NVIS Green B 2/	L	.131	.623	.057	0.5 to 3.0 foot-Lamberts

1/ Chromaticity is expressed as u' and v' coordinates of the 1976 UCS diagram. The values shown describe a circle with center at u', v', and of radius r.
2/ The area enclosed by the described circle intersecting the spectral locus is the envelope limiting the acceptable color space."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.

* Add:

"TABLE XVII. Group B inspection.

Inspection 1/	Test sample PIN's and sample numbers																
	M22885/1085445E2								M22885/1085861E2				M22885/ 1083444E2		M22885/ 108BC41E2		
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	2/
Visual and mechanical	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Solderability													X	X			
Shock I	X	X															
Shock II									X	X							
Moisture resistance	X	X							X	X							
Salt spray			X	X													
Overload cycling					X	X									X	X	
Electrical endurance - inductive dc															X	X	
Electrical endurance - resistive dc					X	X											
Mechanical endurance							X	X									
Low level life											X	X					
Color																	X
Luminance																	X
Sunlight readability																	X
NVIS compatibility																	X
Dielectric withstanding voltage					X	X									X	X	
Operating characteristics	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Seal									X	X							
Marking visibility	X	X	X	X					X	X							

1/ All tests shall be performed as required by table XV.
2/ Two samples of each color."

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, AV, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5930-1642)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:37Z
Check the source to verify that this is the current version before use.