NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND
MIL-PRF-22885/109A(USAF)
AMENDMENT 1
9 June 1993

PERFORMANCE SPECIFICATION SHEET

SWITCHES, PUSH BUTTON, ILLUMINATED,
4-LAMP, .75 SQUARE, 4PDT AND DTDP, 7 AMPERES,
SUNLIGHT READABLE DISPLAY OPTION, NVIS CAPABLE OPTION,
MOMENTARY AND ALTERNATE HOLDDOWN, LOW TOUCH TEMPERATURE,
CONNECTOR MODULE TERMINATION OPTION

This amendment forms a part of MIL-S-22885/109A, dated 16 February 1990, and is approved by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 15

Requirements, after shock, add the following:

"Dielectric withstanding voltage at reduced barometric pressure:

Altitude: 50,000 feet (MIL-STD-202, method 105, test condition B)."

CONCLUDING MATERIAL

Custodian:
Air Force - 85

Review activities :
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5930-F733-04)

DISTRIBUTION STATEMENT A. Approved for public release; Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:38Z
Check the source to verify that this is the current version before use.