MILITARY SPECIFICATION SHEET

SWITCH, PUSHBUTTON, ILLUMINATED 4-LAMP, SPDT AND DPDT, 7.5 AMPERES, SILVER CONTACTS, 1 AMPERE, GOLD CONTACTS (DRIPPROOF, SUNLIGHT READABLE, RFI SHIELDED.

This amendment forms a part of Military Specification MIL-S-22885/100(USAF), dated 27 August 1982, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

TABLE III, delete in its entirety, and substitute:

"

TABLE III. Luminance

Display Type	Color	Brightness (foot-lamberts) 1/		
		Color Code	Without EMI/RFI Screen 2/	With EMI/RFI Screen 2/
N	Yellow	Y	200	100
	Red	R	50	25
	Green	G	40	20
	White	W	300	150
	Blue	B	25	12
W	Yellow	Y	350	175
	Red	R	70	35
	Green	G	50	25
	White	W	350	175
	Blue	B	30	15
S 3/	Yellow	Y	275	225
	Red	R	185	150
	Green	G	185	150
	White	W	275	225
	Blue	B	185	--- 4/
C	Yellow	Y	350	175
	Red	R	80	40
	Green	G	60	30
	White	W	350	175
	Blue	B	40	20

1/ When illuminated by 4 (T-1 midget-flange base) subminiature lamps of .15 * .01 mean spherical candlepower (MSCP) at 5 V dc, 2400°K.
2/ Minimum average.
3/ Luminance shall be measured at three points on each legend character and averaged provided that the ratio of high-to-low readings shall not exceed 2:1. The average contrast of each character shall be reported.
4/ Not available in blue."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:33Z
Check the source to verify that this is the current version before use.

FSC 5930

TABLE IV, delete in its entirety, and substitute:

TABLE IV. Illuminated color limits 3/

Color	X 1/	Y 1/
Red (R)	.665 .663 .711 .713	SL 2/ .335 .257 SL 2/
Green (G)	.300 .300 .365 .365	.560 SL 2/ .560 .635
Yellow (Y)	.568 .575 .630 .623	.425 SL 2/ SL 2/ .370
Blue (B)	.260 .250 .330 .330	.330 .420 .330 .420
White (W)	.480 .480 .540 .540	.395 .435 .431 .391

1/ The chromaticities of the colors are expressed as "X" and Y" coordinates on the CIE chromaticity diagram and are within the limits bound by the coordinates listed for each color.
2/ Where intersection occurs with the spectrum locus on the CIE chromaticity diagram.
3/ Chromaticity values are obtained when switch is illuminated by 4 (T-1 midget-flange base) subminiature lamps of .15 * .01 mean spherical candlepower (MSCP) at 5 V dc, 2400°K."

Custodians:
Air Force - 85

Review activities:
Air Force - 11, 99
DLA - ES

User activities:
Air Force - 19

Agent
DLA - ES

Preparing activity:
Air Force - 85

(Project 5930-F587)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:33Z
Check the source to verify that this is the current version before use.