MILITARY SPECIFICATION SHEET

SWITCHES, PUSH BUTTON, ILLUMINATED, 4-LAMP, LOW LEVEL TO 7.5 AMPERES, SPLASHPROOF, SUNLIGHT READABLE, HIGH IMPACT SHOCK RESISTANT, EMI SHIELDED

This specification is approved for use by Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switches described herein shall consist of this specification and the latest issue of MIL-S-22885.





FIGURE 1. Dimensions and configurations.


FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:32Z
Check the source to verify that this is the current version before use.

SQUARE BUTTON



RECTANGULAR BUTTON




Inches	MM
.030	.76
.031	.79
.19	4.83
.27	6.86
.64	16.3
.69	17.5
.74	18.8
.75	19.1
.89	22.6
1.00	25.4
1.25	31.7
2.354	59.79
2.850	72.39


NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerances are ±.005 for three place decimals and ±.03 for two place decimals.
3. Basic switches shall be MIL-S-8805/4 or /109.
4. Pushbutton shall be design to prevent incorrect insertion into switch housing.
5. Pushbuttons shall be held captive to switch body by retaining element to prevent accidental interchange.
6. Exact shape of switch optional provided dimensions specified are not exceeded.
7. Legend area for sunlight readable display is .480 square.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:32Z
Check the source to verify that this is the currentversion before use.




COMMON GROUND
LAMP CIRCUIT



SPLIT GROUND
LAMP CIRCUIT

1/ SWITCH BODY IS ROTATED FOR SOME LEGEND PLATE STYLES (SEE TABLE VI)



SWITCH POSITIONS 3PDT
(SHOWN FOR REFERENCE)

FIGURE 2. Schematic diagram.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:32Z
Check the source to verify that this is the current version before use.




FIGURE 3. Recommended panel cutouts.

REQUIREMENTS:

Design and construction: See figure 1 thru 3.

Enclosure design: Splashproof.

Splashproof test: Test in accordance with MIL-STD-108. There shall be no leakage of water through the panel and push button seals as determined by visual examination and the dielectric withstanding voltage test.

Temperature characteristic: 1 (-55° to +85°C).

Vibration grade: 3 (10-2000 Hz).

Lens transmittance: T (translucent) lens shall appear translucent white in the unlit condition. In the lit condition, it shall appear in a color determined by the color filters. Sunlight readable lens appear black in unlit condition. When lit, the legend appears in a color determined by the color filters.

Operating characteristics:

Actuation force: 3.5 ±1.5 pounds.

Actuation travel: .160 ±.031 total travel. Actuation occurs when the face of the push button is below the mounting flange.

Push button extraction force: 1.5 to 4 pounds.

Shock:

Method I: 75 G (MIL-STD-202, method 213, test condition H).

Method II: Applicable.

Thermal shock: During high temperature portion of thermal shock test all four lamps shall be energized with full rated voltage.

EMI shielding requirement: When specified, switches shall be equipped with an EMI screen. When switches are tested in accordance with the following test method, the attenuation shall not be less than specified in figure 4.

Test method: Switches shall be tested to determine shielding effectiveness in accordance with the general procedures specified in MIL-STD-285. The test shall consist of electric field and plane wave measurements performed at the following frequencies:

Source: https://assist.dla.mil -- Downloaded: 20261O-19T14:32Z
Check the source to verify that this is the current version before use.

Electric field	Minimum attenuation	Plane wave	Minimum attenuation
15 kHz	60 dB	100 MHz	47 dB
150 kHz	60 dB	400 MHz	39 dB
500 kHz	60 dB	1 GHz	33 dB
1 MHz	60 dB	2.5 GHz	28 dB
10 MHz	60 dB	10 GHz	20 dB




FIGURE 4. Minimum attenuation.

Weight: 2.5 ounces, maximum.

Electrical ratings: See table I.

Color: In accordance with MIL-S-22885/70. See table III for sunlight readable displays.

Luminance:

Other than sunlight readable: See table II.

Sunlight readable: 300 ±150 foot lamberts minimum average with or without EMI screen when illuminated by 2 T-1 lamps of .15 ±.05 MSCP per half for divided legends, or 4 T-1 lamps of .15 ±.05 MSCP for full face legends. Same conditions apply for T-1 3/4 lamps of .30 MSCP minimum.

TABLE I. Electrical ratings. 1/

Contact finish	Load	Sea level		50,000 ft.
		28 V dc	115 V ac, 60 Hz	28 V dc
		(amps, max)	(amps, max)	(amps, max)
Silver	Res.	7	7	4
	Ind.	4	7	2.5
	Lamp 2/	2.5	2	2.5
Gold	Res.	1.0	---	1.0
	Ind.	0.5	---	0.5

1/ Minimum conditions are dependent on use and atmospheric conditions.
2/ Inrush, 10:1 for 20 milliseconds maximum.

Source: https://assist.dla.mil -- Downloaded: 20260-19T14:32Z
Check the source to verify that this is the current version before use.

TABLE II. Luminance (other than sunlight readable).

Color	Color symbol	Minimum average luminance (foot-lamberts) 1/	
		Without EMI screen	With EMI screen 2/
Blue	B	8.0	4.0
Green	G	50.0	25.0
Red	R	30.0	15.0
White	W	180.0	90.0
Yellow	Y	300.0	150.0

1/ When illuminated by two MS25237 lamps of .30 ±.05 mean spherical candlepower at 28 volts dc. Readings are for full display (see table VI).
2/ For information only.

TABLE III. Illuminated color limits - sunlight readable displays. 1/

Color	Chromaticity limits	
	X	Y
Red	.695 .710 .655 .660	.285 SL 2/ .325 SL 2/
Green	.300 .300 .380 .380	SL 2/ .600 .600 SL 2/
Yellow	.562 .570 .596 .605	.415 SL 2/ .382 SL 2/
Blue	.230 .230 .320 .320	.420 .350 .350 .420
White	.400 .460 .400 .460	.420 .420 .380 .380

1/ The chromaticities of the colors are expressed as "X" and "Y" coordinates on the CIE chromaticity diagram and are within the limits bound by the coordinates listed for each color.
2/ SL-spectrum locus (where intersected by other coordinate pair).

Source: https://assist.dla.mil -- Downloaded: 20261O-19T14:32Z
Check the source to verify that this is the current version before use.

Sunlight readability: Applicable (with or without EMI shielding): This switch assembly may be obtained with legends that are visible when illuminated in direct sunlight. The legends are hidden when not illuminated. Illumination is by 4, 5 volts T-1, .15 MSCP lamps. Other T-1 lamps are available and interchangeable with different illumination results. Available area for legend illumination in all push button styles is .48 x .48 inches. The illuminated chromaticity limits are as specified in table III.

Complete switch shall consist of:

1. Switch body - includes seal adapter, clamp, gasket and mounting sleeve.
2. Push button with integral seal.
3. Push button accepts 4 T-1 3/4 midget flange base lamps (not included, order separately). Push button with full lens style (see table VI) will accomodate lamps in the upper left and lower right positions only. Sunlight readable push button accepts 4, T-1 midget flange base lamps or, when specified, 4 T-1 3/4 midget flange base lamps.

Part numbers: Part numbers are assigned as follows:




TABLE IV. Configuration code.

Configuration code	Button style (see figure 1)	EMI shielding
A	Square	Yes
B	Rectangular	Yes
C	Square	No
D	Rectangular	No

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:32Z
Check the source to verify that this is the current version before use.



TABLE V. Function code.

Function code	Circuit	Action	Contact material
A	2PDT	Momentary	Silver
B	3PDT		
C	4PDT		
D	2PDT	Alternate	
E	3PDT		
F	4PDT		
K	2PDT	Momentary	Gold
L	3PDT		
M	4PDT		
N	2PDT	Alternate	
P	3PDT		
Q	4PDT		
V	None 1/	-	-

1/ Use code V to specify push button portion of unit only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:32Z
Check the source to verify that this is the current version before use.

TABLE VI. Lens style, lamp circuit and color.

Code 1/	Lens style 2/	Lamp circuit and application
A		
C		
D		
E		
F		
H		
J	NONE - SWITCH BODY ONLY	
K		
L		
M		
N	NONE - SWITCH BODY ONLY	

1/ Codes are shown for units without color filters. When color filters are to be included, add the color symbols of table II in the sequence shown (code letters J and N do not require additional color filter symbols).
2/ Numbers indicate color symbol sequence.
3/ Switch body is rotated for lens styles not shown.

Qualification inspection:

Group submission: When similar switches have been qualified to MIL-S-22885/67 and the basic sensitive switches are listed on QPL-8805, table VII applies. When similar switches have been qualified to MIL-S-22885/97, qualification will be extended to MIL-S-22885/98.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:32Z
Check the source to verify that this is the current version before use.

TABLE VII. Qualification inspection (group submission).

Part number	Inspection table X of MIL-S-22885		Additional testing	Extent of approval
	Group	Number of samples		
M22885/98-DFAW	I II 1/ 2/ 3/ VII 3/ VIII	All 4 (from group I) 2 (from group I) 10 4/	-2- samples-EMI shielding (after group VII operating characteristics test).	All
Sunlight readable version of M22885/98-BFA 5/	VIII	10 4/		
M22885/97-AFAW	- - -	2	Visual and mechanical examination operating characteristics.	

1/ Insulation resistance: Following step 6 of the final cycle of the moisture resistance test, the insulation resistance measurement shall be not less than 5 megohms.
2/ Method II high impact shock only.
3/ Splashproof seal test to be performed. Twenty-five cycles of removal and reinstallation of the sealed push button shall be made as part of the intermediate current test.
4/ Two push buttons for each color.
5/ Test legend shall fully utilize legend area. Test legend:

REMOTE
ALT LOW

Custodian:
Navy - EC

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5930-N528)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-S- 22885/98

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:32Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20360
ATTN: ELEX 8111

FOLD

Source: https://assist.dla.mil -- Downloaded: 20261O-19T14:32Z
Check the source to verify that this is the current version before use.