INCH-POUND
MIL-DTL-0016377/88(SH)
30 June 2014

DETAIL SPECIFICATION SHEET

FIXTURES, LIGHTING; SOLID STATE LIGHTING (SSL), FOR NON-VITAL SPACES

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy. Other activities in the Department of Defense may use this interim document.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-16377.

REQUIREMENTS:

CLASSIFICATION:

Type: III
Class: 1 or 2

DESIGN:

General:	New luminaires will be designed to be direct replacements of existing Type I, Class 1 and 2 MIL-DTL-16377 fixtures. Design requirements are contained completely within this document. Additional design considerations contained in MIL-DTL-16377 do not apply.
Safety:	Shall meet requirements of UL 1598A.
Electrical:	115 Volts Alternating Current (VAC), 60 Hertz. Shall draw less power than legacy fluorescent fixture.
Weight:	Shall weigh less than legacy fluorescent fixture.
Dimensions and configuration:	External dimensions cannot exceed that of legacy fluorescent fixture.
Mounting:	Shall maintain same mounting dimensions as legacy fluorescent fixture.
Cabling:	Shall use same cable as existing legacy fluorescent fixture.
Color rendering index (CRI):	≥75.
Correlated color temperature (CCT):	4000 K in accordance with ANSI ANSLG C78.377 for white light.
Rated life:	L70 ≥ 36,000 hours in accordance with IES TM-21.
Field replaceable parts:	The light emitting diode (LED) driver, LED array, and any window assemblies shall be field replaceable with simple hand tools (e.g., screwdriver and wrench). LED drivers and arrays shall be pre-wired to allow for ease of installation.
Designation and marking:	The following labels shall be furnished in accordance with MIL-DTL-16377

a. Two Type I.
b. One Type IV label shall be “USE THE FOLLOWING REPAIR PARTS ONLY”.

EXAMINATION AND TESTS:

First article inspection: Examination and test shall be as specified in UL 1598A and table I.
Conformance:
Conformance inspection: See UL 1598A
Comparison inspection: Same as the first article inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article and comparison inspection for complete fixtures. [1/]

Test	Requirement	Test Method	Remarks
Shock	3.5.12	4.8.7	Grade B
Photometrics	3.7.1	4.8.6	Candlepower
Chromaticity	3.7.4	4.8.6.5	
Correlated color temperature (CCT)	3.7.4.1.1	4.8.6.6	4000 K
Enclosure effectiveness	3.5.11	4.8.14.4	

NOTE:
[1/] Requirement and test method paragraph numbers refer to MIL-DTL-16377.

Preparing activity:
Navy – SH
(Project 6210-2014-015)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:57Z
Check the source to verify that this is the current version before use.