NOT MEASUREMENT SENSITIVE


MIL-B-3628/78
28 May 1991

MILITARY SPECIFICATION SHEET

Badge, Qualification, Excellence in Competition,
Pistol Shot, Coast Guard

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.




MATERIAL:
PENDANT: Guilding metal
SUSPENSION BAR:
-1: Guilding metal
-2: Guilding metal or red brass

DASH NO:
-1: Bronze, 1st Award
-2: Silver, 2nd Award

DIMENSIONS:
PENDANT:
HEIGHT (Overall): 1-7/16 inch (3.65 cm) (REF)
WIDTH (Overall): 1-23/64 inch (3.43 cm (REF)
THICKNESS (Edge): .085 inch ± .010 inch (0.190 cm ± 0.025 cm)
SUSPENSION BAR:
HEIGHT (Overall): 11/32 inch (0.87 cm) (REF)
WIDTH (Overall): 1-7/8 inch (4.76 cm) (REF)
THICKNESS (Edge) .075 inch ± .010 inch (0.215 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:23Z
Check the source to verify that this is the current version before use.

FINISH:
PENDANT:
-1: Hard enamelled, oxidized, relieved, highlights and rim highly polished. reverse highly polished. Lacquered front, back and edges.
-2: Hard enamelled, nickel plated, silver plated, matte finish, highlights and rim highly polished. Reverse mirror-like polished. Lacquered front, back and edges.
SUSPENSION BAR:
-1: Oxidized, relieved, highlights and rim highly polished. Reverse mirror-like polished. Lacquered front, back and edges.
-2: Nickel plated, silver plated, matte finish, highlights and rim highly polished. Reverse mirror-like polished. Lacquered front, back and edges.

NOTES:
1. Enamelled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

| COLOR | CHIP NUMBER |
|---|---|
| Black | 26 |
| White | 28 |

2. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal centerline of the suspension bar, equidistant from each end and 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08 cm) apart.

3. All lugs are integral. The links shall be fabricated from copper wire for Dash No. 1 and silver plated wire for Dash No 2 with a nominal diameter of .050 inch (0.127 cm). The overall dimension of the links shall be 1/4 inch (0.64 cm) in length and 7/32 inch (0.56 cm) in width.

4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. The epoxy resin shall be a stoning epoxy, have a shore D hardness of 85 and incorporate an ultraviolet inhibitor.

Custodian:
Army - IH
Navy - NU

Preparing Activity:
Army - IH

Review Activity:
Navy - CG
DLA - CT

(Projected No. 8455-0591)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:23Z
Check the source to verify that this is the current version before use.