NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/78B
15 November 1996
SUPERSEDING
MIL-B-3628/78A
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, EXCELLENCE IN COMPETITION, PISTOL SHOT, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL:
PENDANT: Gilding Metal
SUSPENSION BAR:
-1: Gilding Metal
-2: Gilding Metal or Red Brass

DASH NO.
-1: Bronze, 1st Award
-2: Silver, 2nd Award

FINISH:
PENDANT:
-1: Hard Enameled, Oxidized, Relieved, Highlights and Rim Highly Polished. REVERSE: Highly Polished. Lacquered Front, Back and Edges.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:23Z
Check the source to verify that this is the current version before use.

-2: Hard Enameled, Nickel Plated, Silver Plated, Matte Finish, Highlights and Rim Highly Polished. REVERSE: Nickel Plated, Silver Plated, Mirror-like Polished. Lacquered Front, Back and Edges.

SUSPENSION BAR:
-1: Oxidized, Relieved, Highlights and Rim Highly Polished. REVERSE: Mirror-like Polished. Lacquered Front, Back and Edges.

-2: Nickel Plated, Silver Plated, Matte Finish, Highlights and Rim Highly Polished. REVERSE: Nickel Plated, Silver Plated, Mirror-like Polished. Lacquered Front, Back and Edges.

DIMENSIONS:

PENDANT:

HEIGHT (Overall):	1-7/16 inch (3.65 cm) (REF)
WIDTH (Overall):	1-23/64 inch (3.43 cm (REF)
THICKNESS (Edge):	0.085 inch ± 0.010 inch (0.190 cm ± 0.025 cm)

SUSPENSION BAR:

HEIGHT (Overall):	11/32 inch (0.87 cm) (REF)
WIDTH (Overall):	1-7/8 inch (4.76 cm) (REF)
THICKNESS (Edge):	0.075 inch ± 0.010 inch (0.215 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08 cm) apart.

5. All lugs are integral. The links shall be fabricated from copper wire for Dash No. -1 and silver plated wire for Dash No. -2 with a nominal diameter of 0.050 inch (0.127 cm). The overall dimension of the links shall be 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and 7/32 inch ± 1/64 inch (0.56 cm ± 0.04 cm) in width.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Coast Guard - CG

Preparing activity:
Army - IH

Review activities:

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:23Z
Check the source to verify that this is the current version before use.

DLA - CT

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:23Z
Check the source to verify that this is the current version before use.