NOT MEASUREMENT SENSITIVE


MIL-B-3628/82
28 May 1991

MILITARY SPECIFICATION SHEET

Badge, Qualification, Pistol Shot, Coast Guard

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL:
PENDANT: Guilding metal
SUSPENSION BAR: Guilding metal or red brass

DIMENSIONS:
PENDANT:
HEIGHT (Overall): 1-1/2 inch (3.81 cm) (REF)
WIDTH (Overall): 1-5/16 inch (3.33 cm (REF)
THICKNESS (Edge): .100 inch ± .005 inch (0.254 cm ± 0.012 cm)
SUSPENSION BAR:
HEIGHT (Overall): 11/32 inch (0.87 cm) (REF)
WIDTH (Overall): 1-7/8 inch (4.76 cm) (REF)
THICKNESS (Edge) .075 inch ± .010 inch (0.190 cm ± 0.025 cm)

AMSC N/A
FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:24Z
Check the source to verify that this is the current version before use.

FINISH:
PENDANT: Hard enamelled, gold plated, matte finish, highlights and rim highly polished. Reverse mirror-like polished.
SUSPENSION BAR: Gold plated, matte finish, highlights and rim highly polished. Reverse mirror-like polished.

NOTES:
1. Enamelled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Black	26
White	28

2. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal centerline of the suspense bar, equidistant from each end and 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08 cm) apart.

3. All lugs are integral. The links shall be fabricated from gold plated wire with a nominal diameter of .050 inch (0.127 cm). The overall dimension of the links shall be 1/4 inch (0.64 cm) in length and 7/32 inch (0.56 cm) in width.

4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. The epoxy resin shall be a stoning epoxy, have a shore D hardness of 85 and incorporate an ultraviolet inhibitor.

Custodian:
Army - IH
Navy - NU

Preparing Activity:
Army - IH

Review Activity:
Navy - CG
DLA - CT

(Projected No. 8455-0591)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:24Z
Check the source to verify that this is the current version before use.