MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, COAXIAL, 0.141 INCH (3.58 mm) DIAMETER, SEMIRIGID, 50 OHMS

This amendment forms a part of Military Specification Sheet MIL-C-17/130E, dated 17 January 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, add the following new part numbers:

"

Part number	Inner conductor	Dielectric core	Outer conductor 1/ 7/
M17/130-00008	Solid, silver-coated copper-clad steel diameter, .0362 ±.0007 inch.	Type F-1 diameter, .1175 ±.0010 inch.	Seamless aluminum tubing 8/ diameter, .141 ±.001 inch.
M17/130-00009	Same as above	Same as above	Seamless aluminum tubing 8/ diameter, .141 ±.001 inch tin plated in accordance with MIL-T-10707, type I, .0003 minimum inch thick.
M17/130-00010	.0362 ±.0007 inch diameter. 4/	Same as above	Seamless aluminum tubing 8/ diameter, .141 ±.001 inch.
M17/130-00011	Same as above	Same as above	Seamless aluminum tubing 8/ diameter, .141 ±.001 inch tin plated in accordance with MIL-T-10707, type I, .0003 minimum inch thick.

"

TABLE I, at the end of footnote 2/, add the following sentence:

"33,000 psi, minimum, 30 percent elongation, maximum."

TABLE I, following footnote 6/, add:

"7/ Cable outer conductor tin plating shall not be equal to or greater than 97 percent in purity. Change effectivity, tin plating change (if required) shall become effective 12 months from the date of this specification. Disposition of stock, qualified manufacturers and their selling agents or distributors may ship from stock tin plated cables which were manufactured in accordance with the previous issue of MIL-C-17/130 for a period of 30 months from the date of this specification."

8/ The tensile strength (outer conductor) shall be 15,500 psi, maximum, 40 percent elongation minimum measured over 2 inches."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:14Z
Check the source to verify that this is the current version before use.

Bendability, add the following: "Mandrel diameter .250 inch maximum for -00008 through -00011."

Weight, add the following: "18.8 pounds per 1,000 feet for -00008 and -00010.
20.5 pounds per 1,000 feet for -00009 and -00011."

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 17, 99
DLA - ES, IS

User activities:
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 6145-2037)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:14Z
Check the source to verify that this is the current version before use.