MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, COAXIAL, 0.141 INCH (3.58 mm)
DIAMETER, SEMIRIGID, 50 OHMS

This amendment forms a part of Military Specification Sheet MIL-C-17/130E, dated 17 January 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, add the following new part numbers:

Part number	Inner conductor	Dielectric core	Outer conductor 1/
M17/130-00008	Solid, silver-coated copper-clad steel diameter, .0362 ±.0007 inch.	Type F-1 diameter, .1175 ±.0010 inch.	Seamless aluminum tubing 7/ diameter, .141 ±.001 inch.
M17/130-00009	Same as above	Same as above	Seamless aluminum tubing 7/ diameter, .141 ±.001 inch tin plated in accordance with MIL-T-10727, type I, .0003 minimum inch thick.
M17/130-00010	.0362 ±.0007 inch diameter. 4/	Same as above	Seamless aluminum tubing 7/ diameter, .141 ±.001 inch.
M17/130-00011	Same as above	Same as above	Seamless aluminum tubing 7/ diameter, .141 ±.001 inch tin plated in accordance with MIL-T-10727, type I, .0003 minimum inch thick.
M17/130-00012 5/ 6/	Solid, silver-coaated copper-clad steel diameter, .0362 ±.0007 inch.	Same as above	Copper tubing, diameter 3/ .141 +.002 inch, -.001 inch, silver plated in accordance with QQ-S-365, Type II, Grade A, 300µ inches, minimum.
M17/130-00013 5/ 6/	.0362 ±.0007 inch diameter. 4/	Same as above	Copper tubing, diameter 3/ .141 +.002 inch, -.001 inch, silver plated in accordance with QQ-S-365, Type II, Grade A, 300µ inches, minimum.

Table I, at the end of footnote 2/, add the following sentence:

"33,000 psi, minimum, 30 percent elongation, maximum."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:14Z
Check the source to verify that this is the current version before use.

PAGE 2

Table I, following footnote 6/, add:

"7/ The tensile strength (outer conductor) shall be 15,500 psi, maximum, 40 percent elongation minimum measured over 2 inches."

PAGE 3

Eccentricity, delete "7.5 percent, maximum." and substitute "6 percent, maximum."

PAGE 4

Figure 2, Power rating and attenuation, delete and substitute the following:

"1. M17/130-RG402, 00001, 00004, 00005, 00008, 00009, and 00012.
2. M17/130-00003, 00006, 00007, 00010, 00011, and 00013."

PAGE 6

Bendability, add the following: "Mandrel diameter .250 inch maximum for -00008 through -00011."

Weight, add the following: "18.8 pounds per 1,000 feet for -00008 and -00010.
20.5 pounds per 1,000 feet for -00009 and -00011.
35.1 pounds per 1,000 feet for -00012 and -00013."

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, ME, MI
Navy - AS, MC, OS, SH
Air Force - 17, 19, 99
DLA - ES, IS

Preparing activity:
DLA - ES

(Project 6145-2075)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:14Z
Check the source to verify that this is the current version before use.