MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, TRIAXIAL,
50 OHMS, M17/131-RG403

This amendment forms a part of MIL-C-17/131A, dated 9 October 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I: Delete and substitute:

"TABLE I. Description.

Components	Construction details
Inner conductor	Seven strands of AWG size 38 silver-coated, copper-covered steel. Overall diameter: .012 inch nominal.
Dielectric	Type F-1. Overall diameter: .033 ±.002 inch.
Inner shield	Silver-coated, AWG size 38 copper wire. Overall diameter: .048 - .054 inch. Coverage: 95.9% nominal Carriers: 16 Ends: 3 Picks/inch: 25.0 ±10%
Outer dielectric	Type M-1. Overall diameter: .068 - .080 inch.
Outer shield	Silver-coated, AWG size 38 copper wire. Overall diameter: .084 - .098. Coverage: 95.9% nominal Carrier: 16 Ends: 6 Picks/inch: 13.4 ±10%
Outer jacket	Type IX. Overall diameter: .104 - .128 inch. Wall thickness: .010 inch minimum.

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:15Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 6145-1113)

Source: https://assist.dla.mil - Downloaded: 2026-10-15T16:15Z
Check the source to verify that this is the current version before use.