
MILITARY SPECIFICATION SHEET

COUPLERS, FIBER OPTIC CABLE, CABLE SPLITTER, PASSIVE,
GLASS-PIGTAILED OUTPUT; TYPE II,
820 TO 910 NANOMETERS WAVELENGTH RANGE,
5 X 5 PORT TRANSMISSION STAR, 50/125 AND 100/140 MICROMETER FIBER.

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the fiber optic couplers described herein shall consist of this specification and the latest issue of DOD-C-24621.




cm	Inches	cm	Inches
0.30	.118	1.30	.512
0.41	.161	2.00	.788
0.50	.197	4.00	1.576
.64	.252	18.00	7.092
.65	.256	95.00	37.430

NOTES:
1. Dimensions are in centimeters.
2. Unless otherwise specified, tolerance is ±0.03 centimeter.
3. Pigtails shall be 95 $^{+5}_{-0}$ centimeters long, external to the star coupler package.

FIGURE 1. Fiber optic coupler scale chart.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:23Z
Check the source to verify that this is the current version before use.




18.75% output


$10 \log_{10}(.1875) = -7.3dB$

P_{16}	P_{17}	P_{18}	P_{19}	P_{110}
P_{26}	P_{27}	P_{28}	P_{29}	P_{210}
P_{36}	P_{37}	P_{38}	P_{39}	P_{310}
P_{46}	P_{47}	P_{48}	P_{49}	P_{410}
P_{56}	P_{57}	P_{58}	P_{59}	P_{510}
P_{61}	P_{62}	P_{63}	P_{64}	P_{65}
P_{71}	P_{72}	P_{73}	P_{74}	P_{75}
P_{81}	P_{82}	P_{83}	P_{84}	P_{85}
P_{91}	P_{92}	P_{93}	P_{94}	P_{95}
P_{101}	P_{102}	P_{103}	P_{104}	P_{105}
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3
-7.3	-7.3	-7.3	-7.3	-7.3

NOTES:
1. Ports 1-5 are not useable as outputs when ports 1-5 are being used as inputs (mode 1) and reflected power back to the input ports shall be -40 dB or less.
2. $P_{IJ} = 10 \log_{10} (P_I/P_J)$ where P_J is the input power at port J, and P_I is the output power at port I.



MODE 1



MODE 2

NOTES:
1. J and I are illustrated as the dominant posts of the couples.
2. Each matrix element specified herein has a maximum allowed tolerance of ±0.5 dB (=10%).
3. Matrix elements above include the connector losses of the mating connector.

FIGURE 2. Transmission matrix derivation configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:23Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction: See figure 1.

Mass: 1 kilogram maximum.

Pigtail optical fiber cable: All pigtail fibers must be covered and protected by sheath buffer, and coating as for standard cable (see DOD-C-85045). Buffered fiber, kevlar strength member, and outer jacket shall be 2.5 to 3.0 mm diameter per fiber.

Pigtail minimum bend radius: 70 mm maximum.

Splice compatability: In accordance with DOD-C-24623.

Mating cable type: In accordance with DOD-C-85045.

Operating temperature: -40°C to +85°C minimum temperature range.

Dominant input/output port path: (1, 6) 1/.

Designated input port: (J = 1).

Designated output port: (I = 6).

Part number: D24621/4-01 for 100/140 µm fiber; D24621/4-02 for 50/125 µm fiber.

1/ These dominant ports are the ports used to monitor insertion loss for testing purposes (see transmission matrix) (see figure 2).

Custodians:
Army - CR
Navy - SH
Air Force - 85

Review activities:
Navy - AS, EC
Air Force - 11, 17, 19, 80, 99
DLA - ES

User activities:
Navy - CG, MC

Preparing activity:
Navy - SH

Agent:
DLA - ES

(Project 6060-0036-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:23Z
Check the source to verify that this is the current version before use.