
MILITARY SPECIFICATION SHEET

COUPLER, FIBER OPTIC CABLE, CABLE SPLITTER, PASSIVE GLASS-CONNECTORIZED OUTPUT; TYPE I 820 to 910 NANOMETERS WAVELENGTH RANGE, 2 X 2 SYMMETRICAL TRANSMISSION STAR, 50/125 MICROMETER FIBER, GRADED INDEX MULTI-MODE BIDIRECTIONAL (METRIC)

This specification sheet is approved for use by Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the fiber optic couplers described herein shall consist of this specification and the latest issue of DOD-C-24621.




NOTES:
1. All dimensions are in cm.
2. Unless otherwise specified, tolerance is ±.025 cm.

FIGURE 1. Fiber optic coupler scale chart.

FSC 6060

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:22Z
Check the source to verify that this is the current version before use.




$$P_{IJ} = \begin{matrix} P_{11} & P_{12} & P_{13} & P_{14} \\ P_{21} & P_{22} & P_{23} & P_{24} \\ P_{31} & P_{32} & P_{33} & P_{34} \\ P_{41} & P_{42} & P_{43} & P_{44} \end{matrix}$$

$$P_{IJ} = -10 \log_{10}\left(\frac{P_J}{P_I}\right)$$

Where P_J is the input power at port J, and P_I is the output power at port I.

$$P_{IJ} = \begin{matrix} \leq -17 & \leq -35 & -3.5 & -3.5 \\ \leq -35 & \leq -17 & -3.5 & -3.5 \\ -3.5 & -3.5 & \leq -17 & \leq -35 \\ -3.5 & -3.5 & \leq -35 & \leq -17 \end{matrix}$$



NOTES:
1. J_1 and I_1 are illustrated as the dominant ports of the coupler.
2. Each matrix element specified here has a maximum allowed tolerance of ±0.5 dB (= ≈10%).
3. Matrix elements above do not include the connector losses of the mating connector plug.

FIGURE 2. Transmission matrix derivation configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction: See figure 1.

Mass: Not applicable.

Mating connector type: Not applicable.

Mating cable type: See DOD-C-85045.

Dominant input/output port path: (1/3) 1/

Designated input port: (J = 1)

Designated output port: (I = 3)

Dominant port-to-port insertion loss: P_{31} = 3.5 ±0.5 dB.

Part number: The part number shall be D24621/1-01.

1/ These dominant ports are the ports used to monitor insertion loss for testing purposes (see transmission matrix) (see figure 2).

Custodian:
Navy - SH

Review activities:
Navy - AS, EC
DLA - ES

User activities:
Navy - CG, MC

Agent:
DLA - ES

Preparing activity:
Navy - SH

(Project 6060-N010-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:22Z
Check the source to verify that this is the current version before use.