MIL-A-11600C (PA)
15 March 1975
SUPERSEDING
MIL-A-11600B (MU)
15 April 1966

MILITARY SPECIFICATION

ADAPTER, GRENADE-PROJECTION, M1A2, METAL PARTS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal parts assembly for one type of adapter designated as Adapter, Grenade-Projection, M1A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

*MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

FSC: 1330

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

PRODUCT AND PACKING DRAWINGS

9216131 - Adapter, Grenade-Projection, M1A2 Metal Parts Assembly
9216175 - Carton, Packing and Marking for Adapters, Grenade, Projection, M1A2
9216176 - Box, Packing, Ammo, For Adapter, Grenade Projection, M1A2
*2816283 - Package Shipping & Storage (for 12 Adapter Grenade, Projection, M1A2 or M1A1)
*2128133 - Pack, Shipping and Storage (for 24 Adapter Grenade, Projection, M1A2 or M1A1)

INSPECTION EQUIPMENT DRAWINGS

*7286203 - Gage, Plug, Special

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Metal parts assembly. - The metal parts assembly shall comply with all requirements specified on drawing (dwg. 9216131) and with all requirements specified in applicable specifications.

3.3 Brazed joint of stabilizer tube assembly

3.3.1 The brazed joint of the stabilizer tube assembly shall withstand an applied load of 1,000 pounds, minimum (min.)

3.3.2 The brazed joint of the stabilizer tube assembly shall be stronger than the stablizer tube and withstand an applied load of 7,500 pounds min., unless the stablizer tube breaks first.

3.4 Stabilizer tube and fin assembly. - The stabilizer tube and fin assembly shall withstand a load of 200 pounds min., with no evidence of weld failures and with no change greater than 0.02 inch in the outside diameter of the outer ring of the fin assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

When tested to destruction, the spot welds shall leave a button of fin material on the stabilizer tube, which is the thickness of the fin material and has an area at the base of at least one half the area of the specified weld diameter.

3.5 Adapter assembly

3.5.1 Pull test. - The adapter shall withstand a pull of 18 pounds, min. simulating attempted axial withdrawal of the M62 Grenade without the claws releasing and separating.

3.5.2 Functioning

3.5.2.1 The arming clip retainer shall permit release of the arming clip.

3.5.2.2 Action in flight. - When fired with an M62 practice hand grenade the adapter shall not become detached from the grenade prior to impact.

*3.6 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be free of burrs, chips, sharp edges, cracks, chipped edges, blisters, excess flash, dirt, grease, rust, salt deposits, visible raised cement seams, solder splash, corrosion products, and other defects and foreign matter which would affect their serviceability. The cleaning method used shall not be injurious to any part or assembly nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

*3.7 First article inspection. - The specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. - The following types of inspection shall be conducted on this item.

a. First article inspection
b. Quality conformance inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

4.3 First article inspection

*4.3.1 Submission . - The contractor shall submit a first article sample (see 6.2b) as designated by the Contracting Officer. The first article sample shall consist of twenty-five (25) complete sets of parts and sub-assemblies (i.e., twenty-five (25) each of every component and sub-assembly, including at least five (5) items from each cavity used to produce molded parts, five (5) items from each cavity used to produce die cast parts and be so identified as to permit tracing each item to the cavity in which it was molded). The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

*4.3.2 Inspections to be performed. - See MIL-A-48078 and paras 4.4.2.1 thru 4.4.2.17, testing per para. 4.4.3, and Table I specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-11600C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2 Cont.	Adapter, Grenade - Projection, M1A2				9216131
					NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Examination for Defects	25		3.2	4.4.2.1 thru 4.4.2.17
	Tests				
	Pull test	25		3.5.1	4.5.3.1
	Functioning	25			
	Arming clip release			3.5.2.1	4.5.3.2
	Action in flight			3.5.2.2	4.5.3.2
	Stabilizer tube assembly (Dwg. 9216132)				
	Pull test brazed joint	25		3.3.1	4.5.1.1
	Pull to destruction brazed joint			3.3.2	4.5.1.2
	Load test stabilizer tube and fin assembly	25		3.4	4.5.2
	Load to destruction tube and fin assembly			3.4	4.5.2

NOTES:

5

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

*4.3.3 Rejection. - (See MIL-A-48078).

4.4 Quality conformance inspection.

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-A-11600C (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Tube Stabilizer		9216144
			NEXT HIGHER ASSEMBLY 9216132

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Wall thickness, minimum (min)		0.40%	3.2	Gage
Minor:					
201.	Diameter of flared flange, min.		0.65%	3.2	Gage
202.	Length of tube, min.		0.65%	3.2	Gage
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

7

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Fin				9216137
					NEXT HIGHER ASSEMBLY 9216132
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A&B:	None defined				
Minor:					
201.	Inside diameter, min.		0.65%	3.2	Gage
202.	Length, min.		0.65%	3.2	Gage
203.	Outside diameter, min		0.65%	3.2	Gage
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

MIL-A-11600C (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9216132
*4.4.2.3	Stabilizer Assembly				NEXT HIGHER ASSEMBLY 9216131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Straightness full length		0.40%	3.2	Gage
Minor:					
201.	Concentricity of fin at tube		0.65%	3.2	Gage
*202.	Total length, max.		0.65%	3.2	Gage
203.	Spot weld missing		0.65%	3.2	Visual
204.	Fin insecure		0.65%	3.2	Manual
205.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

9

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Cup, Retainer		9216133
			NEXT HIGHER ASSEMBLY 9216131

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Width of flat		0.40%	3.2	Gage
132.	Depth of cup		0.40%	3.2	Gage
Minor:					
201.	Width of claw holes		0.65%	3.2	Gage
202.	Flange open end, missing		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

10

Source: https://assist.dla.mil - Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Claw, long				9216134
					NEXT HIGHER ASSEMBLY 9216131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Length, center of screw hole to small radius		0.40%	3.2	Gage
Minor:					
201.	Location of screw hole		0.65%	3.2	Gage
202.	Location of rivet hole		0.65%	3.2	Gage
203.	Total length after forming		0.65%	3.2	Gage
204.	Width of claw		0.65%	3.2	Gage
205.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Claw, Short				9216135
					NEXT HIGHER ASSEMBLY 9216131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Length, center of screw hole to small radius		0.40%	3.2	Gage
Minor:					
201.	Location of screw hole		0.65%	3.2	Gage
202.	Total length after forming		0.65%	3.2	Gage
203.	Width of claw		0.65%	3.2	Gage
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-A-11600C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9216136
4.4.2.7	Clip, Arming				NEXT HIGHER ASSEMBLY 9216131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A&B:	None defined				
Minor:					
201.	Total length, min.		0.65%	3.2	Gage
202.	Length of opening, either end, min.		0.65%	3.2	Gage
203.	Width of opening, formed end, min.		0.65%	3.2	Gage
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-A-11600C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9216140
4.4.2.8	Retainer, Arming Clip				NEXT HIGHER ASSEMBLY 9216131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Hardness		0.40%	3.2	Test
132.	Angle of prong		0.40%	3.2	Gage
133.	Width of prong		0.40%	3.2	Gage
Minor:					
201.	Width of slot		0.65%	3.2	Gage
202.	Length from rivet to prong		0.65%	3.2	Gage
203.	Total length after forming		0.65%	3.2	Gage
204.	Width of clip		0 .65%	3.2	Gage
205.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

14

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

MIL-A-11600C (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Clip, Launcher Positioning				9216145
					NEXT HIGHER ASSEMBLY 9216131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Clip failure, functional		0.40%	3.2	Gage/7286203
Minor:					
201.	Length after forming, max.		0.65%	3.2	Gage
202.	Width		0.65%	3.2	Gage
203.	Evidence of poor workmanship		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-A-11600C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Adapter, Grenade Projection, M1A2				9216131
					NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Rivet, arming clip retainer, not peened		100%	3.2	Visual
2.	Prong cracked or missing		100%	3.2	Visual
Major A:					
101.	Claw screws not fully seated		0.40%	3.2	Visual
102.	Arming clip retainer, slot end, improperly seated to claw		0.40%	3.2	Visual
103.	Arming clip, improperly assembled		0.40%	3.2	Visual
Minor:					
201.	Total length		0.65%	3.2	Gage
202.	Marking incomplete, misleading or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

16

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-A-11600C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Carton, Prior to Sealing				9216175
					NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A&B:	None defined				
Minor:					
201.	Incorrect number of adapters		0.65%	3.2	Visual
202.	Dowel missing from arming clip		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-11600C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Carton, Sealed				9216175
					NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Sealing strip incomplete or badly wrinkled		0.40%	3.2	Visual
132.	Carton damaged		0.40%	3.2	Visual
Minor:					
201.	Label missing		0.65%	3.2	Visual
202.	Marking incorrect, misleading or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-A-11600C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Packing Box		9216176
			NEXT HIGHER ASSEMBLY N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Contents of box incomplete		0.40%	3.2	Visual
132.	Box damaged		0.40%	3.2	Visual
133.	Hardware missing, broken or loose		0.40%	3.2	Visual/Manual
134.	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
Minor:					
201.	Hardware improperly engaged		0.65%	3.2	Visual
202.	Strapping improperly assembled		0.65%	3.2	Visual
203.	Seal missing, unsealed or improperly positioned		0.65%	3.2	Visual
204.	Marking incorrect incomplete or unidentifiable		0.65%	3.2	Visual
205.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.14	Package Shipping and Storage (for 12 Adapter, Grenade, Projection, M1A2 or M1A1) (Prior to Closing)				2816283
					NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Any packing component missing or improperly assembled		0.40%	3.2	Visual
Minor:					
201.	No. inner packages incorrect		0.65%	3.2	Visual
202.	Clip and bag missing		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

20

Source: https://assist.dla.mil - Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-11600C (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.15	Package Shipping and Storage (for 12 Adapter, Grenade Projection, M1A2 or M1A1) (Sealed)	1 OF 1	2816283
			NEXT HIGHER ASSEMBLY: N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Filler interferes with seal of box lid		0.40%	3.2	Visual
132.	C.F.R. markings missing or unidentifiable		0.40%	3.2	Visual
Minor:					
201	Description marking missing, misleading, or unidentifiable		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.16	Pack Shipping and Storage (For 24 Adapter, Grenade, Projection, M1A2 or M1A1) (Prior to Closing)	1 OF 1	2128133
			NEXT HIGHER ASSEMBLY: N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Package missing or positioned improperly		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

22

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-11600C (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.17	Pack, Shipping and Storage (For 24 Adapter, Grenade, Projection, M1A2 or M1A1) (Sealed)	1 OF 1	2128133
			NEXT HIGHER ASSEMBLY: N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Wire binding not properly secured		0.40%	3.2	Visual
132.	Car seal missing		0.40%	3.2	Visual
133.	C.F.R. marking missing or not legible		0.40%	3.2	Visual
Minor:					
201.	Description marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Stabilizer tube, brazed joint

4.4.3.1.1 Load test (See 3.3.1). - Major A defect. This test shall be performed one hundred percent. Any brazed joint which shows evidence of failure shall cause the assembly to be classed defective. The test shall be performed as specified in 4.5.1.1 using equipment in accordance with 4.4.4.

4.4.3.1.2 Test to destruction (see 3.3.2). - Major A defect. The sampling plan for this test shall be in accordance with Standard MIL-STD-105 using code letter H and the AQL of 1.50 percent. Any stabilizer tube assembly which fails to comply with the applicable requirement shall be classed defective. The test shall be performed as specified in 4.5.1.2 using equipment in accordance with 4.4.4.

4.4.3.2 Stabilizer tube and fin assembly

4.4.3.2.1 Load test (see 3.4). - Major A defect. The sampling plan for this test shall be in accordance with Standard MIL-STD-105 using code letter H and an AQL of 1.50 percent. If a weld failure occurs or if the diameter of the outer ring of the fin assembly fails to comply with the applicable requirement, the assembly shall be classed defective. The test shall be performed as specified in 4.5.2.1 using equipment in accordance with 4.4.4.

4.4.3.2.2 Test to destruction (see 3.4) Major A defect. The sampling plan for this test shall be in accordance with Standard MIL-STD-105 using code letter H and an AQL of 1.50 percent. If one or more welds of any assembly fail to comply with the applicable requirement the assembly shall be classed defective. The test shall be performed as specified in 4.5.2.2 using equipment in accordance with 4.4.4.

4.4.3.3 Adapter assembly

4.4.3.3.1 Pull test (see 3.5.1) - Major A defect. - This test shall be performed one hundred percent. Any adapter which fails to comply with the applicable requirement shall be classed defective and removed from the lot. The test shall be performed as specified in 4.5.3.1 using equipment in accordance with 4.4.4.

4.4.3.3.2 Functioning (see 3.5.2) - Major A defect. - A sample of 35 assemblies shall be selected at random from each

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

lot. If more than one failure of the arming clip retainer occurs or more than three adapters become detached from the grenade in flight, the lot shall be rejected. The test shall be performed as specified in 4.5.3.2 using equipment in accordance with 4.4.4.

*4.4.4 Inspection equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.3 herein.

4.5 Test methods and procedures

4.5.1 Stabilizer tube brazed joint

4.5.1.1 Load test. - The brazed joint of the stabilizer tube assembly shall be tested by applying a load of 1,000 pounds, min., to the inside of the brazed joint. The load shall be applied in a direction parallel to the axis of the tube at the rate of 0.100 to 0.125 inch per minute, inclusive. Observation shall be made for any evidence of joint failure. Test equipment shall be in accordance with 4.4.4.

4.5.1.2 Test to destruction . - The stabilizer tube assembly shall be tested by applying a load in a direction parallel to the axis of the tube sufficient to cause failure in tension of the tube, or a load of 7,500 pounds (whichever is reached first). The load shall be applied at a rate of 0.100 to 0.125 inch per minute, inclusive. The sides of the tube may be flattened, if necessary, for attachment to the testing machine. Observation shall be made to determine compliance with the applicable requirement. Test equipment shall be as specified in 4.4.4.

4.5.2 Stabilizer tube and fin assembly

4.5.2.1 Load test. - The stabilizer tube and fin assembly shall be tested by applying the specified load along the axis of the tube assembly. The load shall be applied at a rate of 0.100 to 0.125 inch per minute, inclusive. The diameter of the outer ring assembly shall be measured both before and after application of the load. Test equipment shall be in accordance with 4.4.4.

4.5.2.2 Test to destruction. - The welded material shall be pulled apart utilizing equipment in accordance with 4.4.4. Observation shall be made to determine compliance with the applicable requirement.

Source: https://assist.dla.mil -- Downloaded: 202610-17T21:46Z
Check the source to verify that this is the current version before use.

4.5.3 Adapter assembly

4.5.3.1 Pull test. - The adapter shall be subjected to a pull test by applying a steady and gradual pull using the applicable test equipment specified in 4.4.4. Observation shall be made to determine compliance with the applicable requirement. Any adapters which fails to meet the requirement shall be classed defective.

4.5.3.2 Functioning test. - Sample adapters shall be assembled to M62 practice grenades and launched by means of a rifle and M7A3 launcher using the M3 Grenade Cartridge. The assemblies shall be fired with the butt of the rifle against a sandbag, or other appropriate fixture, using each of the following conditions:

Extremity of Stabilizer Tube at Launcher Position	Approximate Elevation of Rifle Barrel, Degrees	Sample Size
5	65	7
4	45	7
3	45	7
2	45	7
All	30	7

Observation shall be made to determine compliance with the applicable requirement.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

*5.1.1 Level A

5.1.1.1 Packaging. - Packaging shall be in accordance with dwg. 9216175.

*5.1.1.2 Level A. - For Marine Corps use preservation and packaging shall be in accordance with dwg. 2816283 and 2128133.

5.2 Packing

*5.2.1 Level A. - Packing shall be packed in accordance with dwg. 9216176.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

*5.2.2 Level A. - For Marine Corps use, packing shall be in accordance with dwg. 2128133 and 2816283.

5.3 Marking

*5.3.1 The carton and exterior containers shall be marked in accordance with dwgs. 9216175 and 9216176 or dwgs. 2816283 and 2128133.

6. NOTES

*6.1 Intended Use. - To adapt hand grenades for launching from a rifle.

*6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

*6.3 Submission of inspection equipment designs for approval. - (see MIL-A-48078). Submit equipment designs as required to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

*6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1330-A-039

Source: https://assist.dla.mil -- Downloaded: 202610-17T21:46Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.

1216

2/2

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

١٤ ١٥

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-10-17T21:46Z
Check the source to verify that this is the current version before use.