MIL-A-11610B
22 DECEMBER 1959
SUPERSEDING
MIL-A-11610A
17 MARCH 1952

MILITARY SPECIFICATION

ADAPTER, LINE, FILLING, 1-TON CONTAINER, M1

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers a filling line adapter for use on three types of 1-ton containers.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids form a part of this specification:

SPECIFICATIONS

FEDERAL

PPP-B-585 — Boxes; Wood, Wirebound.

PPP-B-591 — Boxes, Fiberboard, Wood-Cleated.

PPP-B-601 — Boxes, Wood, Cleated-Plywood.

PPP-B-621 — Boxes, Wood, Nailed and Lock-Corner.

PPP-B-636 — Boxes, Fiber.

PPP-C-843 — Cushioning Material, Cellulosic.

PPP-P-150 — Paper, Shredded, Waxed.

PPP-T-60 — Tape, Pressure-Sensitive Adhesive, Waterproof — for Packaging and Sealing.

PPP-T-76 — Tape, Pressure-Sensitive Adhesive, Paper, Water Resistant.

MILITARY

MIL-P-116 — Preservation, Methods of.

MIL-B-121 — Barrier Material, Greaseproofed, Flexible (Waterproofed).

MIL-B-10377 — Box, Wood, Cleated, Veneer, Paper Overlaid.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:47Z
Check the source to verify that this is the current version before use.

MIL-STD-129 — Marking for Shipment and Storage.

MIL-STD-130 — Identification Marking of U. S. Military Property.

DRAWINGS

CHEMICAL CORPS

C28-10-21 — Adapter, Line, Filling, 1-Ton Container, M1 — Assembly and Bill of Material.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CONSOLIDATED CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules.

(Application for copies of these freight classification rules should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Ill.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 *Materials.* All materials cited on Drawing C28-10-21 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 *Components.* All components of the item shall conform to the specifications and drawings listed on Drawing C28-10-21 and subsidiary drawings.

3.2 Manufacturing and assembly. The filling line adapter shall be manufactured and assembled as specified on Drawing C28-10-21 and the subsidiaries listed thereon.

3.3 Leakage. The filling line adapter, composed of the filling assembly and the venting assembly, shall not leak when tested as specified in 4.5.

3.4 Identification. The adapter shall be marked in accordance with Standard MIL-STD-130.

3.5 Workmanship. The adapter shall be free from contamination (foreign matter) and damage, such as dents, cracks, bends, or deformations which would impair its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier's responsibility. Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Objective evidence. The supplier shall present objective evidence as required by the Government representative that all materials and components are in accordance with 3.1 and section 5 (see 6.4).

4.3 Alternate inspection (including testing) procedures. The supplier may utilize any alternate inspection procedure which will assure equal or better quality by submitting proposal with justification and obtaining written approval from the Government prior to its institution. In case of dispute, the procedures of this specification will govern.

4.4 Inspection provisions.

4.4.1 *Regular production lot.* A regular

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:47Z
Check the source to verify that this is the current version before use.

production lot shall consist of the filling line adapters produced by one manufacturer from the same materials and under essentially the same manufacturing conditions and offered for shipment at one time.

4.4.2 *Sampling.*

4.4.2.1 *Nondestructive examination and test.* Sampling shall be conducted in accordance with Standard MIL-STD-105.

4.4.3 *Examination.* Sample adapters shall be examined in accordance with the classification of defects and Standard MIL-STD-105.

4.4.4 *Classification of defects.*

4.4.4.1 *Adapter, line, filling, 1-ton container, M1 — Assembly (Dwg. C28-10-21).*

Categories and defects	*Acceptance standards*
Major A—AQL 0.65 percent defective	
1a. Leakage	4.5
Major—AQL 1.0 percent defective	
1. Component missing, incorrect or incorrectly assembled.	
2. Thread (1.035-14NGO-RH-INT) incorrect.	
3. Thread (1½-12UNF-2B) incorrect.	
4. Valve inoperable.	
5. Piping bent or mashed; valve stem bent or handle broken.	
6. Damage (see 3.5).	
Incidental—AQL 10.0 percent defective	
101. Contamination (see 3.5).	

4.4.4.2 *Preparation for delivery (sec. 5).*

Categories and defects
Major—AQL 4.0 percent defective
1. Adapter improperly cleaned.
2. Preservative missing.
3. Adapter wrap missing.
4. Containers incorrect.
5. Cushioning missing or insufficient to make a tight pack.
6. Closure of containers incorrect.
7. Number of adapters per container incorrect.
8. Strapping loose or missing.
9. Containers broken or wracked.
10. Marking missing, illegible or incorrect.

4.5 Leakage test. The filling and venting assemblies (Dwg. C28-10-21) shall be sealed by inserting a luted plug into the open end of the tee of the filling assembly, and into the open end of the valve in the venting assembly. The valve adapters in each assembly shall then be sealed with fittings equipped with air valves to permit air under pressure to be pumped into the assembly. Dry air at a controlled pressure of 100 pounds per square inch (psi) shall be introduced into the assembly and the assembly submerged for a period of 1 minute under 4 to 6 inches of water containing a wetting agent in sufficient concentration to prevent air bubbles from clinging to the surfaces. Each filling and venting assembly shall be tested with valves closed tightly and with valves fully open. Leaking assemblies (joints, valve stems, etc.) shall be identified for return to the supplier either for rework or for salvage of the filling line adapter.

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. The adapter shall be cleaned in accordance with method C-3 of Specification MIL-P-116. Drying shall be accomplished by utilizing the most applicable drying method specified in the same specification.

5.2 Preservation and packaging.

5.2.1 *Level A.* The adapter, including threaded surfaces, shall be coated with type P-7 preservative oil, conforming to Specification MIL-P-116. The excess preservative oil shall be drained off; the adapter wrapped in grease-proof barrier-material, conforming to type II, grade A, of Specification MIL-B-

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:47Z
Check the source to verify that this is the current version before use.

121; and the wrap secured in place with pressure-sensitive tape, conforming to Specification PPP–T–76. The wrapped adapters shall then be individually packaged in a W5c, style RSC, fiber box, conforming to Specification PPP–B–636. Cushioning material, conforming to either Specification PPP–P–150 or to PPP–C–843, shall be employed as required to prevent movement within the container. The box shall be closed in accordance with the appendix to Specification PPP–B–636, except that the closure shall be the same as that specified for exterior boxes. In addition, all box seams, including manufacturer's joint, shall be sealed, using 3-inch-wide pressure-sensitive tape conforming to type III, class 1, color optional, of Specification PPP–T–60, extending the tape over all corners and edges a minimum of 3 inches. Strapping shall not be accomplished.

5.2.2 *Level B.* Not applicable.

5.2.3 *Level C.* Preservation, as applicable, and packaging shall be in accordance with the manufacturer's commercial practice when adequate to provide protection for the items packed as specified in 5.3.3.

5.3 Packing.

5.3.1 *Level A.* Adapters, preserved and packaged as specified in 5.2.1, shall be packed in overseas class or type shipping containers conforming to Specification PPP–B–585, PPP–B–591, PPP–B–601, PPP–B–621 or MIL–B–10377. As far as practical containers shall be of uniform shape or size, be of minimum cube and tare consistent with the protection required and contain identical quantities. The gross weight of each pack shall be limited to approximately 200 pounds. Containers shall be closed and strapped in accordance with applicable container specification or appendix thereto using galvanized strapping.

5.3.2 *Level B.* Adapters shall be packed as specified in 5.3.1 except that domestic class or type shipping containers and coated-finish strapping shall be used.

5.3.3 *Level C.* The adapters, preserved and packaged as specified in 5.2.3, shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Containers used shall comply with the Uniform Freight Classification Rules or other carrier regulations applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order, unit packages and exterior shipping containers shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 Intended use. This specification covers a filling line adapter capable of being attached to the valve of a type A, type D, or type E, 1-ton container. The container valves may be Chlorine Institute or angle valve type, each type requiring a special valve adapter consisting of a standard ¾-inch union elbow, a special nipple, and a special nut for attaching to the container valve. The special valve adapters are listed on Drawing C28–10–21.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Level of packaging and packing required.

6.3 Stock number. The Federal stock number for this item is 4730–368–6188.

6.4 Objective evidence. Provisions for objective evidence and inspection records and maintenance of inspection records will be specified by the procuring activity.

6.5 Pilot lot. A pilot lot may be required to

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:47Z
Check the source to verify that this is the current version before use.

evaluate the supplier's production and quality control systems. The contracting officer will specify whether a pilot lot is required and the applicable pilot lot acceptance criteria.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Chemical Corps
Air Force

Preparing activity:
Army—Chemical Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:47Z
Check the source to verify that this is the current version before use.