FREQUENCY METER FR-40( )/GSM-1

1. Delete Section 2. "APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS AND DRAWINGS", in its entirety and add the following:

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| PPP-B-585 | Boxes; Wood, Wirebound |
| PPP-B-591 | Boxes, Fiberboard, Wood-Cleated |
| PPP-B-601 | Boxes, Wood, Cleated Plywood |
| PPP-B-621 | Boxes, Wood, Nailed and Lock-Corner |
| PPP-B-636 | Boxes, Fiber |

MILITARY

| | |
|---|---|
| MIL-P-116 | Preservation, Methods Of |
| MIL-T-945 | Test-Equipment, For Use With Electronic Equipment: General Specification |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection By Attributes |
| MIL-STD-129 | Marking for Shipments and Storage |

DRAWINGS

SIGNAL CORPS

| | |
|---|---|
| SC-DL-38391 | Frequency Meter FR-40/GSM/1 |

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. Both the title and number or symbol should be stipulated when requesting copies.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.

2.2 Other publications.- The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

AMERICAN TRUCKING ASSOCATION, INC.

National Motor Freight Classification No. A-3 and No. 14

(Application for copies should be addressed to The National Classification Board, 1424 Sixteenth Street, NW, Washington 6, D. C.)

CONSOLIDATED CLASSIFICATION COMMITTEE

Uniform Freight Classification No. 4

Consolidated Freight Classification Rule 21

(Application for copies should be addressed to The Consolidated Classification Committee, 202 Union Station, Chicago 6, Ill.)

2. Paragraph 3.3.3.1 Input power.- Replace with the following:

3.3.3.1 Input power.- Volt-amperes consumed at center scale shall not exceed 3.0, and at the ends of scale, shall not exceed 6.0.

3. Delete Section 5 in its entirety and replace with the following:

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 Level A.- Frequency Meter FR-40( )/GSM-1 shall be preserved, packaged and tested in accordance with the procedures specified for the designated methods as prescribed in Specification MIL-P-116 and as described herein.

5.1.1.1 Spare parts.- Running spare parts, determined in quantity and number from the bid request or contract shall be packaged in accordance with the applicable provisions of Specification MIL-P-116.

5.1.1.2 Frequency Meter FR-40( )/GSM-1.- Each frequency meter shall be packaged Method IC-5 as follows: Place the meter within its case, close the case and secure all fastenings. Cushion the case with contents on all surfaces with cells or pads or both, fabricated of double faced corrugated fiberboard and designed to absorb the shock of impact encountered in handling and transit. Fiberboard shall have water resistant qualities and dry bursting strength equal to the box in which they will be used. Place the packaged running spare parts (see 5.1.1.1) within the cushioning cells. Place the cushioned case with contents within a close-fitting regular slotted sytle corrugated fiber box W5c class 2, conforming to Specification PPP-B-636. Box closure shall be in accordance with the referenced box specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.

5.1.2 Level C.- Frequency Meter FR-40( )/GSM-1 shall be preserved and packaged in accordance with commercial practice and in a manner that will afford protection against corrosion, deterioration and physical damage during direct shipment to the first receiving activity.

5.2 Packing.-

5.2.1 Level A.- Frequency Meter FR-40( )/GSM-1 shall be packed for shipment within class 2 fiber boxes, or class 2, nailed and lock-corner wood boxes, or class 3 wirebound wood boxes or overseas class wood cleated fiberboard boxes, or overseas class wood, cleated-plywood wood boxes conforming to Specification PPP-B-636, PPP-B-621, PPP-B-585, PPP-B-591, or PPP-B-601, as applicable. Boxes shall be fabricated to fit the contents snugly. The weight of box with contents, other than fiber, shall not exceed 200 pounds. The weight of fiber box with contents shall shall not exceed the weight limitation specified in Specification PPP-B-636. Box closure shall be in conformance with the applicable box specification or appendix thereto.

5.2.1.1 Metal strapping.- Shipping containers shall be strapped in conformance with the requirements of the appendix of the applicable container specification only for direct shipment to ports.

5.2.2 Level B.- Frequency Meter FR-40( )/GSM-1 shall be packed for shipment as specified in 5.2.1 except shipping containers shall be domestic class. No strapping required.

5.2.3 Level C.- Frequency Meter FR-40( )/GSM-1 shall be packed for shipment in a manner conforming to the requirements of Uniform Freight Classification No. 4 and Consolidated Freight Classification, Rule 21 for rail shipment, National Motor Freight Classification No. A-3 and No. 14 for truck shipment, Parcel Post Regulations, and the regulations of other carriers as applicable to the mode of transportetion employed at lowest transportation rate.

5.3 Marking.- Interior packages and exterior shipping containers shall be marked in accordance with the applicable provisions of Standard MIL-STD-129.

4. Delete 4.1 through 4.1.3 inclusive and replace with the following:

4.1 Contractor Responsibility and Acceptable Inspection.

4.1.1 Contractor responsibility.- Unless otherwise specified herein the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.

4.1.2 Acceptance inspection.- Unless otherwise specified, acceptance inspection shall be conducted by the Government inspector when the equipment is submitted for acceptance on contract. Acceptance inspection shall consist of Production Inspection (4.1.5)

4.1.3 Scope of acceptance inspection.- Acceptance inspection shall include Visual and Mechanical inspection as described in 4.2, Performance Tests (4.3), and such other inspection and non-destructive testing of material, parts and components, or complete equipments as are considered necessary by the Government inspector to determine compliance with this specification or its subsidiaries.

4.1.4 Inspection lots.- When so required by the Government inspector, the equipment shall be submitted for acceptance in discrete lots. The size of the lots and the manner in which they are formed (output of one assembly line, machine, operator, etc., for a period of time such as a shift, day or week or a definite number of units) shall be as determined by the Government inspector.

4.1.5 Production inspection.- At the discretion of the contracting officer, production inspection may be conducted by either or both of the following methods:

(a) One hundred per cent inspection and non-destructive testing.

(b) Statistical Sampling.- MIL-STD-105 shall be used for statistical sampling, when applicable."

5. Paragraph 3.1 Construction.- In line number 2, delete "The model" and add "Drawing SC-DL-38391".

In the line before the last line, delete "The model" and add "Drawing SC-DL-38391".

6. Delete paragraphs 3.1.1 Availability of model and 3.1.2 Performance in their entirety.

7. Paragraph 3.2.3 Test data. In line number 5, delete "model".

8. Add paragraphs 4.7 through 4.7.2.2 as follows:

4.7 Procurement inspection of preparation for delivery.- The contractor shall perform the inspection specified by 4.7.1 and 4.7.2, to demonstrate compliance with specified requirements. However, this does not relieve the contractor of responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. The Government will review and evaluate the contractor's inspection procedures and examine the contractor's inspection records. In addition the Government--at its discretion--may perform all or any part of the inspection specified in 4.7.1 and 4.7.2, to verify the contractor's compliance with specified requirements. (The amount of such verification inspection will depend on the extent to which the contractor's inspection procedures and records insure that the equipment on contract meets the specified procurement inspection.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.

When Standard MIL-STD-105 specifies action by the Government, the Government may authorize the contractor to perform any of such actions except that responsibility for acceptance rests with the Government.

4.7.1 Preservation and packaging.- Inspection of preservation and packaging shall be as specified in Specification MIL-P-116. Classification of defects shall be as shown on table I.

4.7.2 Packing and marking of exterior containers.- Packing and marking of exterior containers shall be given visual inspection for the defects listed and to determine conformance with the approved process sheet furnished by the contractor as required by the contract. This inspection shall conform to the Appendix to Standard MIL-STD-105. Inspection level L-8 shall be used for normal inspection and L-6 for reduced inspection. Unless otherwise specified herein, normal inspection shall be used at the start of the contract. The reduced inspection procedure shall be R-1. The AQL for major defects shall be four percent and the AQL for minor defects shall be ten percent. Classification of defects shall be as shown on table II.

4.7.2.1 Inspection lot.- A lot for visual inspection of the pack shall be all completed packs which are identical and will be submitted for acceptance at one time.

4.7.2.2 Disposition of nonconforming product.- Disposition of nonconforming product (sample units and inspection lots) shall be in accordance with the requirements of Standard MIL-STD-105 for disposition of rejected product. When submitted for acceptance, such product shall be suitably tagged or identified by equivalent means to indicate the cause of failure and means employed to correct the fault. The required information shall be presented to the Government when the product is submitted and shall become the property of the Government.

CLASSIFICATION OF DEFECTS FOR PRESERVATION, PACKAGING AND MARKING

TABLE I

| MAJOR | MINOR |
|---|---|
| 1. Use of improper or defective material. | 1. Item not properly blocked or braced within the unit package to prevent movement. |
| 2. Quantity in unit package not as specified. | 2. Packaging material damaged. |
| 3. Incorrect packaging method applied. | 3. Air not expelled from barrier. |
| 4. Grease proof wrap omitted if required. | 4. Conforming wraps are not snug-fitting and contain voids. |
| 5. Cushioning or padding omitted. | 5. Any item of marking information other than 9 thru 11 omitted, incorrect, or illegible. |
| 6. Cushioning or padding inadequate for the protection of the barrier material from projections, sharp edges, or other similar features of the item. | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS FOR PRESERVATION, PACKAGING AND MARKING

MAJOR — TABLE I (cont'd) — MINOR

7. Cushioning inadequate for the physical and mechanical protection of the item.

8. Unsealed, punctured, or improperly sealed barrier bag, wrap, or envelope.

9. Stock number omitted, incorrect, or illegible.

10. Nomenclature omitted, incorrect, or illegible.

11. Marking of quantity of items in package omitted, incorrect or illegible.

12. Different stock numbered items in the same unit package.

## CLASSIFICATION OF DEFECTS FOR PACKING AND MARKING
TABLE II

| MAJOR | MINOR |
|---|---|
| 1. Use of improper or defective material. | 1. Unsealed carton. |
| 2. Quantity in pack not as specified. | 2. Defective taping or sealing of carton. |
| 3. Gross weight in excess of specified | 3. Any other box defect which may be considered minor by definition of Standard MIL-STD-105. |
| 4. Box closure not as specified. | 4. Any item of required marking information other than 10 thru 16 listed under major defects omitted, incorrect, or illegible. |
| 5. Type, grade, class, and style of the shipping container not as specified. | |
| 6. Strapping omitted. | |
| 7. Strapping inadequate or incorrectly applied. | |
| 8. Items not adequately blocked, braced, or cushioned within the shipping container to prevent movement or damage. | |
| 9. Shipping documents or packing list omitted. | |
| 10. Stock number omitted, incorrect, or illegible. | |
| 11. Nomenclature omitted, incorrect, or illegible. | |
| 12. Marking of quantity of items in pack, omitted, incorrect, or illegible. | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS FOR PACKING AND MARKING
TABLE II

| | MAJOR | MINOR |
|---|---|---|
| 13. | Destination marking omitted, incorrect, or illegible. | |
| 14. | Service designation (color marking) omitted. | |
| 15. | Special marking or labeling (when required) omitted. | |
| 16. | Overseas code marking omitted, incorrect, or illegible. | |

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:48Z
Check the source to verify that this is the current version before use.