MIL-T-11674F
2 December 1982
SUPERSEDING
MIL-T-11674E
10 May 1977

MILITARY SPECIFICATION

TRIPOD, SURVEYING, FOR RANGE POLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a lightweight metal folding tripod.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-E-529	- Enamel, Alkyd, Semigloss.
PPP-B-636	- Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6675

Source: https://assist.dla.mil -- Downloaded: 202610-17T21:49Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-704	- Treatment and Painting of Materiel.
MIL-S-3534	- Surveying Instruments and Accessories, Packaging of.
MIL-L-11566	- Level, Level Rod.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13207E1370	- Tripod, Surveying, for Range Pole Assembly.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The tripod shall be in accordance with Top Assembly TA13207E1370, and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances

Source: https://assist.dla.mil -- Downloaded: 202640-17T21:49Z
Check the source to verify that this is the currentversion before use.

within those prescribed on the drawings to insure correct fit, assembly, and operation of the tripod. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, materials and material finishes, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Materials. Materials shall be as specified herein (and on the drawings). Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

3.3 Level. A level conforming to MIL-L-11566 shall be furnished with each tripod.

3.4 Identification marking. Each tripod shall be identified in accordance with MIL-STD-130.

3.5 Treatment and painting. The tripod, except for the threaded parts, shall be cleaned, treated, and painted in accordance with MIL-T-704, type A, semigloss, color as specified (see 6.2). Buckles and end clips shall be finished with an enamel conforming to TT-E-529, type as applicable, color black.

3.6 Workmanship. All parts, components, and assemblies of the tripod including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. External surfaces shall be free from burrs, sharp edges, and corners, except when sharp edges and corners are required.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Quality conformance inspection (see 4.3).

b. Inspection of packaging (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:49Z
Check the source to verify that this is the current version before use.

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified herein for the following defects. AQL shall be 1.5 percent defective for major defects and 6.5 percent defective for minor defects.

Major

101. Dimensions not as specified.
102. Material not as specified.
103. Insert not properly positioned or cut.
104. Mounting bracket casting shows cracks, blowholes, or rough upper surface.
105. Leg not firmly welded to socket.
106. Bar in locking screw does not swing freely.
107. Swivel shaft shows cracks or fracture.
108. Leg shows split or fracture.
109. Swivel shaft not attached firmly to leg.
110. Steel point not attached firmly to socket.
111. Locking screw does not turn readily into both sides of the mounting bracket.
112. Straps not mounted firmly to the leg.
113. Workmanship not as specified.

Minor

201. Extension bracket bowed.
202. Extension bracket lug not fitted firmly to leg.
203. Level retainer not fitted firmly to leg.
204. Marking missing, incorrect, incomplete or illegible.

4.4 Inspection of packaging. Preservation, packing and marking for level A or B shall be examined and tested in accordance with the Quality Assurance Provisions of MIL-S-3534. Commercial preservation, packing and marking shall be examined to determine compliance with MIL-STD-1188.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, level B, or commercial, as specified (see 6.2).

5.1.1 Level A. Each tripod shall be preserved in accordance with the level A preservation and packaging requirements of MIL-S-3534.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:49Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Each tripod shall be preserved in accordance with the level B preservation and packaging requirements of MIL-S-3534.

5.1.3 Commercial. Each tripod shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, level B, or commercial, as specified (see 6.2).

5.2.1 Level A. The tripods, preserved as specified in 5.1, shall be packed in accordance with the level A packing requirements of MIL-S-3534.

5.2.2 Level B. The tripods, preserved as specified in 5.1, shall be packed in accordance with the level B packing requirements of MIL-S-3534 except boxes conforming to PPP-B-636, V3c, style optional, may also be used, providing the gross weight or size limitations of the box are not exceeded. Box closure and sealing shall be in accordance with the appendix to the box specification.

5.2.3 Commercial. The tripods, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The tripod is used in general surveying operations to support a range pole. It may also be used to support a signal light or other surveying equipment.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Color required (see 3.5).

c. Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:49Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ME
Navy - YD

Review activity:
DLA - GS

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 6675-0728

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-T-11674F Tripod, Surveying, for Range Pole

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:49Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R & D Command
Attn: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:49Z
Check the source to verify that this is the current version before use.