NOT MEASUREMENT SENSITIVE

MIL-L-11484/58C
14 January 1994
SUPERSEDING
MIL-L-11484/58B
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, HONORABLE DISCHARGE, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.



MATERIAL: Gilding Medal

DIMENSIONS:
DIAMETER: 19/32 inch (1.51 cm) (REF)
THICKNESS (At Edge): 0.045 inch ± 0.005 inch (0.114 cm ± 0.012 cm)

FINISH:
RIM, LETTERS AND SHIELD: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

RECESSED AREA BETWEEN RIM AND SHIELD: Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:23Z
Check the source to verify that this is the current version before use.

2. Enameled areas shall be blue as indicated. The color shall conform to the TIOH color chip number 20 or the standard sample.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH
Coast Guard - CG

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0743)

Source: https://assist.dla.mil -- Downloaded: 202610-17T16:23Z
Check the source to verify that this is the current version before use.