NOT MEASUREMENT SENSITIVE

MIL-L-11484/62C
14 January 1994
SUPERSEDING
MIL-L-11484/62B
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, HONORABLE DISCHARGE, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

WHITE ENAMEL

DULL BLACK LACQUER



MATERIAL: Gilding Medal

DIMENSIONS:
- **DIAMETER:** 19/32 inch (1.51 cm) (REF)
- **THICKNESS (At Edge):** 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

FINISH: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights with Dull Black Lacquer and shall match TIOH Metal Finish Chip Number 8.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T16:25Z
Check the source to verify that this is the current version before use.

2. Enameled area shall be white as indicated. The color shall conform to the TIOH color chip number 28 or the standard sample.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The dull, flat black lacquer shall match FED-STD-595, Chip Number 37038 or the standard sample.

5. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0743)

Source: https://assist.dla.mil - Downloaded: 2026-10-17T16:25Z
Check the source to verify that this is the current version before use.