GG-C-00590B(GSA-FSS)
May 18, 1970
SUPERSEDING
Int. Fed. Spec. GG-C-00590a(GSA-FSS)
October 22, 1963

# INTERIM FEDERAL SPECIFICATION

## COPYHOLDER, TYPIST'S

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers requirements for forward and side reading typist's copyholders.

1.2 Classification.

1.2.1 Types and classes. The copyholders covered by this specification shall be of the following types and classes, as specified:

Type I - Forward reading; mechanical spacing adjustment.
  Class 1 - Collapsible; platen roller.
  Class 2 - Noncollapsible; moving reading plate.

Type II - Deleted (see 6.3).

Type III - Side reading; mechanical spacing adjustment.
  Class 1 - Noncollapsible; feed roller, cylindrical body.
  Class 2 - Noncollapsible; movable line guide, flat reading plate.

Type IV - Side reading; manual spacing adjustement, movable line guide, flat reading plate.

1.2.2 Sizes. See 3.3 and 6.2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.
PPP-C-795 - Cushioning Material, Cellular, Plastic Film (For Packaging Applications).
PPP-C-843 - Cushioning, Material, Cellulosic.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 141 - Paint, Varnish, Lacquer, and Related Material; Method of Inspection, Sampling and Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:51Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Office in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Classification Board:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. Except for changes necessary to comply with this specification requirements, all copyholders furnished under this specification shall be the manufacturer's standard commercial product which has been produced and sold commercially.

3.2 Material. The copyholders shall be made from material suitable for the intended purpose, and shall meet the performance requirements of this specification. When steel strip is used it shall have a minimum thickness of 0.024 inch. All metal surfaces, except corrosion resistant steel and nickel-silver shall be treated to resist corrosion and present a good appearance.

3.3 Design and construction. The copyholders shall consist of a base, reading plate or paper support, spacing mechanism or device, line spacer, and line guide. Type I copyholders shall be provided with a holding device, or means to allow the typewriter to be used as a holding device. Types III and IV copyholders shall be table models that rest firmly on any flat surface.

3.3.1 Base. The base of the copyholder shall be provided with securely attached rubber, cork, or felt feet, or part or the entire bottom shall be covered with suitable material to prevent marring the surface on which copyholder may be placed.

3.3.2 Line spacer. Types I and III copyholders shall be provided with means to adjust and control the variable spacing movements from 3/32-inch to at least 1/2-inch by a single operation. Standard spacing is six lines to the inch.

3.3.3 Line guide. The line guide shall be fixed or movable, depending upon the type of copyholder specified (see 6.2). The line guide, except type III, class 1, shall be as wide as the maximum width for which the copyholder is designed. Type III, class 1, shall have a permanent line guide that is an integral part of the copyholder and shall be not less than 6-3/4 inches wide. When specified, an adjustable line guide and paper support shall be provided which shall be capable of being attached to the permanent line guide. When contracted the width of the adjustable line guide shall be not more than 11 inches, and when extended not less than 20 inches (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

3.3.4 Line magnifier (type III, class 1 only). When specified, a line magnifier shall be supplied. The line magnifier shall be made of appropriate material, and shall magnify the word or characters of three single spaced typed lines approximately 2-1/2 times. Both ends of the magnifier shall have a slot that will fit the frame of the completely contracted line guide and paper support and securely hold the magnifier in place.

3.3.5 Type I, class 1. The copyholder shall comply with the applicable paragraphs of section 3. The copyholder shall be designed to permit adjustment to obtain the correct light reflection, and shall be collapsible to facilitate storing it in desk typewriter compartment together with the typewriter. A variable adjustment shall be provided permitting single, double, triple, quadruple, or intermediate line spacing. In operation, the reading material shall be inserted between suitable rollers and held in a vertical position behind and above the typewriter. The movement of the sheet between rollers shall be controlled by either platen knobs or pressure on a lever. The lever shall extend forward in a convenient position to the right of the typewriter keyboard.

3.3.5.1 Size. Copyholders shall be furnished in sizes to accommodate a sheet ranging in width from less than 1 inch up to 11, 14, 18, 24, 28, and 32 inches (see 6.2).

3.3.6 Type I, class 2. The copyholder shall comply with the applicable paragraphs of section 3. The copyholder shall hold reading material in a vertical position behind and above the typewriter. The design of the copyholder shall permit adjustment to obtain the correct light reflection. The copyholder shall have a moving reading plate with a stationary line guide. The length of the reading plate shall be not less than 15 inches, and the spacing mechanism shall raise the reading plate not less than 10-1/2 inches. A variable adjustment shall be provided permitting at least a single and double line spacing. In operation, the reading material shall be attached to the reading plate by moving the line guide forward and passing the sheet(s) under the line guide and inserting it under the clamp located at the top of the reading plate; the line guide is then pushed back into position against the reading plate. The up and down movement of the reading plate shall be controlled by pressure on a lever. The lever shall extend forward in a convenient position to the right of the typewriter keyboard.

3.3.6.1 Size and capacity. Copyholders shall be furnished in sizes to accommodate sheets ranging width from 1 inch up to 12, 16, 20, 24, 30 and 36 inches, and shall hold from 1 to 25 sheets (see

3.3.7 Type III, class 1. The copyholder shall comply with the applicable paragraphs of section 3. The copyholder shall have a slotted cylindrical body with a fixed line guide, and hold reading material in a vertical position for side reading. The fixed line guide shall be not less than 6-3/4 inches wide. A variable adjustment shall be provided permitting single, double, and triple line spacing. In operation, the sheet shall be inserted within the cylinder and then carried through a slot over suitable feed rollers. The feed rollers shall project sufficiently to facilitiate holding and moving of reading material. Movement of sheet by feed rollers shall be controlled by pressure on a space bar located at the base of the copyholder.

3.3.7.1 Size. Copyholder shall be furnished in a size to hold a single sheet with a minimum width of 2-1/2 inches (see 6.2).

3.3.8 Type III, class 2. The copyholder shall comply with the applicable paragraphs of section 3. The copyholder shall have a movable line guide with a stationary reading plate. The copyholder shall hold sheet(s) for side reading in a vertical position. A variable adjustment shall be provided permitting single and double line spacing. In operation, the sheet(s) shall be attached to the reading plate by moving the line guide forward and passing reading material under the line guide and inserting the sheet(s) under the clamp located at the top of the reading plate; the line guide is then pushed back into position against reading material. Movement of the line guide shall be controlled by pressure on the space bar located at the base of the reading plate.

3.3.8.1 Size and capacity. Copyholder shall hold sheet(s) not less than 11 inches in width, horizontally, and not less than 14 inches in length, vertically, and shall hold from 1 to 25 copies.

3.3.9 Type IV. The copyholder shall comply with the applicable paragraphs of section 3. The copyholder shall be capable of being erected (set up) and folded flat. The copyholder shall have a movable line guide with a stationary reading plate. It shall hold reading material for side reading in a vertical position. No variable spacing mechanism is to be provided. In operation, the sheet(s) shall be attached to the reading plate by moving line guide forward and passing reading material under the line guide and inserting sheet(s) under the clamp located at the top of the reading plate; the line guide is then pushed back into position against reading material. Movement of the line guide across the reading plate shall be controlled by manual adjustment.



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:51Z
Check the source to verify that this is the current version before use.

3.3.9.1 Size and capacity. Copyholders shall hold sheet(s) in the following sizes: (1) not less than 9 inches in width, horizontally, and not less than 12 inches in length, vertically; (2) not less than 9 inches in width, horizontally, and not less than 16 inches in length, vertically; (3) not less than 16 inches in width, horizontally and not less than 12 inches in length, vertically (see 6.2). The copyholder shall hold from 1 to 25 sheets.

3.4 Performance. The copyholders shall be designed and constructed for heavy duty usage, operate without requiring lubrication and tools, and not vibrate when in use. The spacing mechanism shall perform easily, smoothly, and quietly in presenting a new reading line (one at a time). The copyholder shall permit easy insertion and removal of reading material and securely hold sheet(s) at the desired and easy reading position.

3.5 Finish. All metal exterior surfaces, except plated hardware, corrosion resistant steel and nickel-silver shall be cleaned and pretreated for final finishing in accordance with TT-C-490, and coated with pigmented enamel or lacquer, or a combination thereof. The minimum total dry coating shall be not less than 1.0 mil, when tested in accordance with 4.4.2.4. The finish shall be uniform without runs, wrinkles, blisters, lumpy areas, areas of thin or no film, or separation of color.

3.5.1 Plated hardware. Plated hardware shall be finished with nickel, cadmium, zinc, or chromium (see 3.2 and 4.4.2).

3.6 Identification marking. Each copyholder shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.7 Workmanship. The copyholders shall be free from defects or imperfections which may affect appearance, or impair serviceability. The copyholder shall be devoid of sharp corners, edges, burrs, or other imperfections that may be hazardous to the user.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. All copyholders of the same type, class and size presented for inspection at one time shall be considered a lot for the purpose of examinations and tests.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random sample of copyholders shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one copyholder. The copyholder shall be examined for defects listed in table I. The Inspection Level shall be S-4, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery requirements. Sampling shall be in accordance with MIL-STD-105. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery and selected at random just prior to closing operations. Shipping containers fully prepared shall be examined for closure defects. The Inspection Level shall be S-4, and the AQL shall be 4.0 defects per hundred units.

4.2.5 Sampling for performance tests. A random sample of copyholders shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one copyholder. The copyholder shall be tested as specified in 4.4. The Inspection Level shall be S-2, and the AQL shall be 4.0 percent defective.

4.2.6 Sampling for coating or plating test. Two sample units shall be taken from each lot and tested as specified in 4.4.2.

4.3 Examination.

4.3.1 Visual and dimensional examination. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.



Source: https://assist.dla.mil -- Downloaded: 202610-26T11:51Z
Check the source to verify that this is the currentversion before use.

TABLE I. Classification for defects

| Examine | Defects |
|---|---|
| Type and class | Type or class not as specified (see 1.2). |
| Size | Not as specified. |
| Standard product | Not standard commercial product (see 3.1). |
| Material | Not suitable, or as specified (see 3.2). |
| Design and construction | Copyholder not designed and constructed as specified (see section 3).<br>Copyholder not equipped with required components (see section 3).<br>Base not provided with feet or covered as specified (see 3.3.1).<br>Line guide not as specified (see section 3).<br>Magnifier not as specified (see 3.3.3). |
| Finish | Not as specified (see 3.2, 3.5 and 3.5.1). |
| Identification marking | Not as specified (see 3.6). |
| Workmanship | Not in accordance with 3.7. |

4.3.2 Examination of preparation for delivery requirements. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II, to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with.

TABLE II. Classification of preparation for delivery defects

| Examine | Defects |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect, illegible; or improper size, location, sequence, or method of application. |
| Material | Any component missing, or damaged. |
| Content | Number of units per package or shipping container not as specified. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling.<br>Distortion of container. |

4.4 Tests.

4.4.1 End item tests. Samples taken in accordance with 4.2.5 shall be tested to insure compliance with the requirements stated in section 3. Any copyholder having one or more defects shall be rejected. If the number of defective copyholder exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.1.1 Performance tests. All copyholders shall be tested for the following: (1) Adjustments can be made without the use of tools; (2) Easy insertion of reading material; (3) Securely holds sheet(s); (4) Copyholder will not vibrate when typewriter is used. When applicable, copyholder shall be tested for the following: (1) Collapses to enable storage in desk typewriter compartment; (2) Permits adjustment to obtain correct light reflection; (3) Does not under-space or over-space when set for desired line spacing.

4.4.2 Test for coating or plating. Samples selected in accordance with 4.2.6 shall be subjected to one of the following tests applicable to the finish of the end product. Failure to identify an authorized plating or coating, or not meeting the thickness requirement of the enamel or lacquer shall be cause for rejection of the entire lot (see 3.5 and 3.5.1).

4.4.2.1 Identification for presence of nickel. Using a medicine dropper, apply several drops of nitric acid ($HNO_3$), Sp. gr. 1.42 to the metal surface. At the end of one minute observe acid drop; a clear pale green color indicates presence of nickel.

4.4.2.2 Identification for presence of zinc and cadmium. Place part to be tested in a beaker of nitric acid ($HNO_3$), Sp. gr. 1.42. At the end of 1 minute observe the reaction. A vigorous reaction and no precipitate identifies zinc. A slight reaction and a yellow-colored solution identifies cadmium.



Source: https://assist.dla.mil -- Downloaded: 202610-26T11:51Z
Check the source to verify that this is the current version before use.

4.4.2.3 Identification for presence of chromium. Using a medicine dropper, apply several drops of concentrated hydrochloric acid (HCl), Sp. gr. 1.18. A green solution identifies presence of chromium.

4.4.2.4 Thickness of enamel or lacquer coating test. The thickness of the final coating of the copyholder shall be determined to the nearest 0.0001 inch by Test Method 6183 of Fed. Test Method Std. No. 141, for compliance with 3.5.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each copyholder and its components shall be cushioned and packaged in a snug-fitting fiberboard box conforming to PPP-B-636, class weather-resistant, grade W5c. Cushioning used shall be die-cut or built up forms and pads of corrugated fiberboard or material conforming to PPP-C-843 or PPP-C-795. The packages shall be waterproof sealed with tape in accordance with the appendix to PPP-B-636.

5.1.2 Level B.

5.1.2.1 Collapsible copyholders. Each collapsible copyholder shall be packaged in a snug-fitting fiberboard box or paperboard box conforming to PPP-B-636, PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be secured to prevent accidental opening.

5.1.2.2 Noncollapsible copyholders. Each noncollapsible copyholder shall be packaged in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic. Closure shall be made to prevent accidental opening.

5.1.2.3 Line guides. Each line guide when furnished separately shall be packaged in a kraft or plastic envelope. The envelope shall be closed to prevent loss of contents.

5.1.2.4 Line Magnifiers. Each magnifier when furnished separately shall be packaged in a snug-fitting paperboard box conforming to PPP-B-566, PPP-B-665, or PPP-B-676.

5.1.3 Level C. Each copyholder with components shall be packaged to assure adequate protection against damage during shipment from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Copyholders, of one type, class, and size only, in quantities as specified (see 6.2), shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class weather-resistant, grade V3c. The gross weight of the shipping container shall not exceed the weight limitations of PPP-B-636. The fiberboard boxes shall be waterproof sealed with tape and reinforced with strapping strapping in accordance with the appendix to PPP-B-636.

5.2.2.1 Collapsible copyholders. Four (4) unit packages of collapsible copyholders, of one stock number, shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.2.2 Noncollapsible copyholders. Four (4) unit packages of copyholders, of one stock number, shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.2.3 Line guides. Twenty-four (24) unit packages of line guides shall be intermediately packaged in a snug-fitting paperboard box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Six intermediate packages (144 line guides) shall be packed in a fiberboard box conforming to PPP-B-636, class domestic. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.2.4 Magnifiers. One hundred forty-four (144) magnifiers shall be packed in a fiberboard box conforming to PPP-B-636, class domestic. Closure shall be in accordance with PPP-B-636.

5.2.3 Level C. The copyholders and components in quantities as specified (see 6.2) packaged as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special markings required by the procurement documents the interior packages and the shipping container shall be marked in accordance with Fed. Std. No. 123 for civil agencies and MIL-STD-129 for Military agencies, as applicable.



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:51Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use. The copyholders are intended to hold reading material to be transcribed for the convenience of the typist.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in the procurement document:

(a) Title, number, and date of this specification.
(b) Type, class, and size (see 1.2.1 and 1.2.2).
(c) Levels of packaging, packing and any special marking required.
(d) Quantities to be supplied for level A or C shipments.

6.3 Change in classification. This specification includes a change in the classification of copyholders designated in previous documents. Type II copyholder cited in previous documents is no longer commercially available, and has been deleted from this document.



GSA DC 70-14863

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

# SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail: General Services Administration, FSS (FMSO) Washington, D. C. 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

Interim Federal Specification GG-C-00590B(GSA-FSS) Copyholder, Typist's

| 2. CONTRACT NO. *(If any)* | 3. QUANTITY ON CONTRACT *(Optional)* | 4. DOLLAR VALUE *(Optional)* |
|---|---|---|
| | | |

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time, temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

| 9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC. | 10. ADDRESS *(Number, Street, City, State and Zip Code)* |
|---|---|
| | |

| 11. NAME AND TITLE OF SUBMITTER | 12. DATE |
|---|---|
| | |

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:51Z
Check the source to verify that this is the current version before use.