GG-D-458b
APRIL 2, 1962

SUPERSEDING
Int. Fed. Spec. GG-D-00458a (NAVY-S&A)
March 30, 1960 and
Fed. Spec. GG-D-458
October 2, 1958

FEDERAL SPECIFICATION

DISPENSER, PRESSURE-SENSITIVE ADHESIVE TAPE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers non-electrically operated pressure-sensitive adhesive-tape dispensers for dispensing tapes with pressure-sensitive adhesive on one side only.

1.1.1 Federal specification coverage. Federal specifications do not cover all types, classes, and sizes of commodities as indicated by the specification title or that are commercially available, but are intended to cover types, classes, and sizes that are generally used by the Federal Government.

1.2 Classification.

1.2.1 *Types and classes.* Pressure-sensitive adhesive-tape dispensers shall be of the following types and classes as specified (see 6.2):

Type I.—Heavy-duty dispenser, measured lengths.
- Class 1.—For tapes up to 4 inches wide.
- Class 2.—For tapes up to 2 inches wide.

Type II.—Medium-duty dispenser, measured lengths.

Type III.—Light-duty dispenser, measured lengths.
- Class 1.—For tapes up to 1 inch wide, special.
- Class 2.—For tapes up to 1 inch wide, regular.

Type IV.—Bag sealer.

Type V.—Desk dispenser.
- Class 1.—For tapes up to 1 inch wide, measured lengths.
- Class 2.—For tapes up to 3 inches wide.
- Class 3.—For tapes up to 2 inches wide.
- Class 4.—For tapes up to 1 inch wide.
- Class 5.—For tapes up to ¾ inch wide.

Type VI.—Hand dispenser.
- Class 1.—For tapes up to ¾ inch wide.
- Class 2.—For tapes up to ½ inch wide.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

Federal Specifications:

L-T-90 —Tape, Pressure-Sensitive, Adhesive (Cellophane and Cellulose Acetate).
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-585—Boxes, Wood, Wirebound.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner.
~~PPP-B-636—Box, Fiberboard.~~
PPP-B-665—Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676—Boxes, Set-Up, Paperboard.
PPP-T-60 —Tape; Pressure-Sensitive Adhesive, Waterproof—For Packaging and Sealing.
PPP-T-76 —Tape; Pressure-Sensitive Adhesive, Paper, Water Resistant.
PPP-T-97 —Tape; Pressure-Sensitive Adhesive, Filament Reinforced.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specifications

MIL-P-116 —Preservation, Methods of.
MIL-B-121 —Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-B-10377—Boxes; Wood-Cleated, Veneer, Paper Overlaid.
MIL-L-10547—Liners, Case, Waterproof.

Military Standards

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Material.** The material of the body for types I, II, III, and IV, where it supports the operating mechanism, shall be cast iron, cast aluminum, zinc die castings or sheet steel not less than 1/16 inch thick. Type V dispensers shall be made of metal not less than 1/32 inch thick. Type VI dispensers shall be lightweight durable plastic.

3.2 **Construction.**

3.2.1 *Type I.* Type I dispenser shall be of sturdy construction suitable for heavy-duty use in dispensing pressure-sensitive tape which has adhesive on one side (see 6.1.1). The tape shall be fed with a manually operated lever. The tape cutoff shall be manual, using a replaceable cutoff blade. Razor-type knife blades shall be fully guarded. Means shall be provided for anti-curl attachment for use with paper-backed pressure-sensitive tapes and an adjustable tape-slitter attachment. The dispenser shall enclose the roll of tape to protect the tape from dirt and damage. A front overhang design shall be employed to prevent the tacky surface of the tape from contacting the work area.

3.2.1.1 *Type I, class 1.* The feeding power of the lever and the single stroke length of type I, class 1 dispenser shall be inversely variable to three different settings by means of interchangeable gears. The feed-gear train shall be made of steel or cast iron of at least 20 pitch and minimum ¼-inch face.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

3.2.1.2 *Type I, class 2.* The feeding power of the lever and the single stroke length of type I, class 2 dispenser shall be inversely variable to not less than two different settings by means of interchangeable gears.

3.2.2 *Type II.* Type II dispenser shall be of sturdy construction suitable for dispensing pressure-sensitive carton-sealing kraft tape. The tape shall be fed with a manually operated lever. The tape cutoff shall be manual, using a serrated-edge, stainless-steel or surgical steel knife. The dispenser shall enclose the rolls of tape to protect the tape from dirt and damage. A front overhang design shall be employed to prevent the tacky surface of the tape from contacting the work area when long strips are dispensed. The feed-gear train shall be made of steel or cast iron of at least 20 pitch and ⅜-inch face.

3.2.3 *Type III.*

3.2.3.1 *Class 1.* Type III, class 1 dispenser shall be of sturdy construction suitable for use with cellophane-backed, paper-backed, or polyester-backed pressure-sensitive adhesive tape. The tape feed shall be lever operated and tape cutoff manual. The tape cutoff shall be by means of a serrated-edge, stainless-steel blade. When specified, the dispenser shall be equipped with a slitter attachment, attachment for dispensing polyester-backed tapes, or an anti-curl attachment for use with paper-backed tapes (see 6.2).

3.2.3.2 *Class 2.* Type III, class 2 dispenser shall fully enclose the roll of tape for protection against dirt and damage. The feed shall be by means of a manually operated lever which cuts the tape in the same stroke. The dispenser shall be capable of dispensing tape in pre-set lengths.

3.2.4 *Type IV.* Type IV dispensers shall be suitable for dispensing paper-backed pressure-sensitive tapes for bag closing. The dispensers shall be available with various size slots for inserting the neck of the bag (see 3.3.5). The dispensers with throat sizes less than ½ inch shall be so designed that the bag is closed and the tape cut off in one operation. The dispensers with a throat size of ½ inch or larger shall be designed to close the bag and cut off the tape in one or more operations. When specified, the dispensers shall be equipped with an attachment that will trim the bag in the same operation as that which cuts off the tape (see 6.2).

3.2.5 *Type V.*

3.2.5.1 *Class 1.* Type V, class 1 dispenser shall be suitable for dispensing any type of pressure-sensitive tape in predetermined lengths. Tape shall be dispensed by setting indicator to the length desired and manually pulling and cutting the tape on a knife edge.

3.2.5.2 *Classes 2, 3, 4, and 5.* Type V, classes 2, 3, 4, and 5 dispensers shall be suitable for dispensing cellophane-backed tape and acetate-fiber pressure-sensitive tape. The dispenser body shall be open and the tape feed manual. The tape cutoff shall be manual, using a serrated-edge, rust-proof steel knife. When specified, classes 2 and 3 dispensers shall have two ½-inch-wide drums (see 6.2).

3.2.6 *Type VI.* Type VI dispensers shall be suitable for dispensing cellophane-backed pressure-sensitive tape. The dispenser body shall be closed and the tape feed manual. The tape cutoff shall be manual, using a serrated-edge blade.

3.3 Capacity and performance.

3.3.1 *Core accommodations.* Types I, II, IV, and V, classes 1, 2, 3, and 4 dispensers shall accommodate rolls of tape having 3-inch-diameter cores. Type V, class 5 and type VI dispensers shall accommodate rolls of tape having 1-inch-diameter cores. Type III dispensers shall accommodate rolls of tape having 3-inch cores and, when specified type III, class 1 dispensers shall be furnished with adapters for using 1-inch-core rolls (see 6.2).

3.3.2 *Type I.*

3.3.2.1 *Class 1.* Type I, class 1 dispenser shall accommodate rolls of tape up to 4 inches wide with a roll diameter up to 8½ inches.

3.3.2.2 *Class 2.* Type I, class 2 dispenser shall accommodate rolls of tape from ½ inch up to 2 inches wide with a roll diameter up to 7½ inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

3.3.3 *Type II.* Type II dispenser shall accommodate rolls of tape from ¼ inch up to 8 inches wide with a roll diameter up to 8 inches.

3.3.4 *Type III.*

3.3.4.1 *Class 1.* Type III, class 1 dispenser shall accommodate rolls of tape from ¼ inch up to 1 inch wide with a roll diameter up to 5½ inches.

3.3.4.2 *Class 2.* Type III, class 2 dispenser shall accommodate rolls of tape from ¼ inch up to 1 inch wide with a roll diameter up to 6½ inches.

3.3.5 *Type IV.* Type IV dispensers shall have the following throat sizes, as specified: ¼, ⅜, ½, ¾, 1, or 1-¼ inches, plus or minus 1/16 inch (see 6.2).

3.3.5.1 *One-quarter and ⅜-inch sizes.* The ¼- and ⅜-inch size dispensers shall accommodate rolls of tape from ⅜ to ½ inch wide with a roll diameter up to 8½ inches.

3.3.5.2 *One-half inch size and over.* Dispensers with ½-inch and over throat sizes shall accommodate rolls of tape from ⅜ to ½ inch wide with a roll diameter up to 6 inches.

3.3.6 *Type V.*

3.3.6.1 *Classes 1, 2, 3, and 4.* Type V, classes 1, 2, 3, and 4 dispensers shall accommodate rolls of tape up to the widths indicated for each class in 1.2 with a roll diameter up to 5 inches.

3.3.6.2 *Class 5.* Type V, class 5 dispensers shall accommodate rolls of tape up to ¾ inch wide with a roll diameter up to 2-½ inches.

3.3.7 *Type VI.* Type VI, classes 1 and 2 dispensers shall accommodate rolls of tape ¾ inch wide and ½ inch wide, respectively. Dispensers shall accommodate rolls containing up to 36 yards of cellulose tape.

3.4 **Single-stroke length.** Types I, II, and III dispensers shall on a single full stroke of the operating lever dispense a length of tape not less than the length indicated in table I for the applicable type, class and change gear and shall dispense longer lengths by repeat strokes. The single-stroke length shall be determined in accordance with 4.5.2.

TABLE I. *Dispensing lengths*

Type	Class	Full stroke dispensing length, min.—inches		
		Low gear	Medium gear	High gear
I	1	8	13	20
	2	6	..	10
II	..	..	..	30
III	1	..	..	4
	2	..	..	3

3.4.1 *Variation.* The variation in measured length permissible shall be plus or minus 1 inch when tested in accordance with 4.5.3.

3.5 **Identification marking.** Each dispenser shall be marked in a legible and permanent manner with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

3.6 **Workmanship.** Tape dispensers shall be free from any defects that may affect serviceability or appearance such as dents, nicks, burrs, rust, and sharp edges other than knife edges.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the government. Inspection records of the examination and tests shall be kept complete and available to the government as specified in the contract or order. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

4.1.1 *Inspection of preparation for delivery requirements.* The packaging, packing and marking of tape dispensers shall be subject to inspection by the inspector to determine compliance with the requirements of Section 5 of this specification.

4.2 **Lot.** A lot shall consist of all dispensers of the same type, class and size offered for delivery at one time. The unit of product shall be dispenser.

4.3 **Sampling.**

4.3.1 *For examination.* The samples shall be selected in accordance with MIL–STD–105.

4.3.2 *For tests.* The samples selected in accordance with 4.3.1 shall be used for testing purposes.

4.4 **Examination.** Dispenser samples selected in accordance with 4.3.1 shall be inspected for the following defects, Acceptable Quality Level (AQL) 4.0 percent defective:

Defect	Applicable Paragraph
Material not as specified	3.1
Cutoff blade not as specified	3.2.1, 3.2.2, 3.2.3.1, 3.2.5.2, 3.2.6
Construction not as specified	3.2
Capacity not as specified	3.3
Identification marking missing	3.5
Workmanship	3.6

4.5 **Tests.**

4.5.1 *Capacity and performance.* A roll of tape of a width equal to the maximum width indicated in 3.3 for the respective type and class shall be inserted in the applicable dispenser. Various lengths of tape shall be dispensed to determine ease of operation. Tape for the various dispensers shall be in accordance with the specifications listed in table II.

4.5.2 *Single-stroke length.* Immediately following the capacity test, the single-stroke length shall be determined by setting the dispenser for the maximum length obtainable and dispensing 12 lengths of tape at a moderate uniform dispensing speed. The single stroke shall be the average length of the 12 lengths dispensed (see 3.4).

TABLE II. *Tapes used for testing dispensers*

Dispenser		Tape
Type	Class	Federal Specification
I	1 and 2	PPP–T–97
II	.....	PPP–T–76
III	1 and 2	L–T–90, type I
IV	.....	PPP–T–76
V	1, 2, 3, 4, 5	L–T–90, type I
VI	1 and 2	L–T–90, type I

4.5.3 *Measured lengths.* Immediately following the single-stroke length test, the tape dispenser shall be set for a measured length and two lengths of tape dispensed at a moderate uniform speed; the second length shall be accurately measured and the length noted. The same procedure shall be followed at four different settings (see 3.4.1).

5. PREPARATION FOR DELIVERY

(Civil agencies. Fed. Std. No. 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.)

5.1 **Preservation and packaging.** Dispensers shall be preserved and packaged level A or C, as specified in the contract or order (see 6.2).

5.1.1 *Level A.* All uncoated and unpainted ferrous-metal surfaces shall be cleaned method C-1, thoroughly dried, and coated with P-7 type preservative in accordance with MIL–P–116. Preserved surfaces, subject to contact with packaging or packing materials, shall be covered or wrapped with greaseproof barrier material conforming to MIL–B–121, type II or III, grade A. The barrier material shall be secured in place with pressure-sensitive tape, minimum 2 inches in width, conforming to PPP–T–76. Dispensers,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

except type V, class 5 and type VI shall then be individually packaged in a fiberboard box conforming to type I or II, class 1 of PPP-B-636. When specified, the fiberboard boxes shall be constructed and sealed with tape in accordance with class 2, V3c or V3s of PPP-B-636. The contents of each fiberboard box shall be adequately cushioned with fiberboard pads applied in a manner designed to prevent movement or damage while in transit or storage.

5.1.1.1 *Type V, class 5 and type VI dispensers.* Unless otherwise specified, type V, class 5 and type VI dispensers shall be packaged in quantities of 12 each in boxes conforming to PPP-B-566, PPP-B-665 or PPP-B-676.

5.1.2 *Level C.* Tape dispensers shall be packed in accordance with commercial practice.

5.2 **Packing.** Dispensers, packaged level A or C, shall be packed levels A, B or C, as specified in the contract or order (see 6.2).

5.2.1 *Level A.* Dispensers, packaged as specified, shall be packed in overseas-type boxes conforming to any of the following: PPP-B-585, class 3; PPP-B-591; PPP-B-601; PPP-B-621; PPP-B-636, class 2, V3c or V3s; or MIL-B-10377. Gross weight of wood and wood-cleated boxes shall not exceed 200 pounds; of fiberboard boxes, the weight limitation of the box specification. Boxes shall be provided with case liners conforming to MIL-L-10547, class 2, sealed in accordance with the appendix thereto. Case liners may be omitted when boxes conforming to PPP-B-636, class 2 are used, and have all joints and seams sealed with tape conforming to PPP-T-60 or PPP-T-76. Box closures shall be in accordance with the box specification and the appendix thereto. When specified, dispensers packaged as specified in 5.1.1 shall require no overpacking.

5.2.2 *Level B.* Dispensers, packaged as specified, shall be packed in domestic-type boxes conforming to any of the following PPP-B-585; PPP-B-591; PPP-B-601; PPP-B-621; PPP-B-636; or MIL-B-10377. Gross weight of wood and wood-cleated boxes shall not exceed 200 pounds; of fiberboard boxes, 70 pounds. The bursting strength of fiberboard boxes shall be not less than 275 pounds. Box closures shall be in accordance with the appendix to the applicable specification. When specified, dispensers packaged in accordance with 5.1.1 shall require no overpacking.

5.2.3 *Level C.* Dispensers shall be packed in containers of the type, size and kind commonly used for the purpose, in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the rules or regulations of carriers as applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any special marking specified in the contract or order, each intermediate package and shipping container shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military requirements.* In addition to any special marking required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.1.1 *Type I.* Type I dispenser is intended for dispensing standard commercial rolls of pressure-sensitive tape including filament, glass fiber, heavy paper, cellulose, and acetate fiber.

6.1.2 *Type II.* Type II dispenser is intended for dispensing pressure-sensitive tapes used to seal cartons.

6.1.3 *Type III.*

6.1.3.1 *Class 1.* Type III, class 1 dispenser is intended for dispensing cellophane, acetate, and paper tapes and, when equipped with special attachment, polyester tapes.

6.1.3.2 *Class 2.* Type III, class 2 dispenser

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:50Z
Check the source to verify that this is the current version before use.

is intended for dispensing pressure-sensitive cellulose or paper tapes.

6.1.4 *Type IV.* Type IV dispenser is intended for use in bag-sealing operations with cellulose or paper-backed tapes.

6.1.5 *Type V.*

6.1.5.1 *Class 1.* Type V, class 1 dispenser is intended for dispensing all types of pressure-sensitive tapes.

6.1.5.2 *Classes 2, 3, 4, and 5.* Type V, classes 2, 3, 4, and 5 dispensers are intended for dispensing cellophane, acetate fiber, acetate, or paper tapes.

6.1.6 *Type VI.* Type VI dispensers are intended for dispensing cellulose pressure-sensitive tapes where predetermined measured lengths are not a factor.

6.2 **Ordering data.** Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification

(*b*) Type desired and class, if applicable (see 1.2)

(*c*) Whether type III, class 1 dispensers shall be furnished with a slitter attachment, attachment for dispensing polyester tapes, anti-curl attachment for paper-backed tapes (see 3.2.3.1), or adapter for using 1-inch, core rolls (see 3.3.1)

(*d*) Whether type IV dispensers shall be equipped with an attachment for trimming bags (see 3.2.4)

(*e*) Throat size desired when type IV dispensers are ordered (see 3.3.5)

(*f*) Whether two drums are required if type V, class 2 or 3 dispensers are ordered (see 3.2.5.2)

(*g*) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 **Transportation description.** Transportation description and minimum weights applicable to this commodity are:

Rail: Holders, cellulose tape, cast and sheet iron combined. Carload minimum weight 30,000 pounds.

Motor: Holders, cellulose tape, cast and sheet iron combined. Motor volume minimum weight 30,000 pounds.

6.4 **Military standards.** Items procured under this specification for military use are to be limited to the variety shown on the applicable military standards. Personnel of the military departments are requested to refer to these documents for guidance.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY CUSTODIANS:
Army—Q
Navy—S
Air Force—MOAMA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.