GG-P-655B
September 20, 1974
SUPERSEDING
Int. Fed. Spec. GG-P-00655A (GSA-FSS)
April 19, 1971, and
Fed. Spec. GG-P-655
October 6, 1965

# FEDERAL SPECIFICATION

# PRINTING SET, RUBBER TYPE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

## 1. SCOPE

1.1 This specification covers a rubber type hand printing set (see 6.4).

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extend specified herein.

Federal Specifications:

TT-I-600 - Inking Pad, Rubber Stamp.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).
Federal Test Method Std. No. 601/GEN (General Provisions) - Rubber: Sampling and Testing.
Fed. Test Method 601/3021 - Hardness, Durometer.
Fed. Test Method 601/7001 - Accelerated Aging Tests, General.
Fed. Test Method 601/7221 - Air Heat Test, Air Heating Medium.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-116 - Preservation, Method of

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Component parts. The rubber type printing set shall consist of a 5A6a letter font, 4 figure font (see 6.3), commercial size 0 ink stamp pad, a four line and a one line type holder block, a handle, and a tweezer. The type shall be 12-point News Gothic face on a 14-point body.

3.2 Material.

3.2.1 Rubber. Rubber may be natural or synthetic or a mixture of the two. When tested as specified in 4.1.1.2 the rubber hardness in the original state shall be Shore A 60, plus or minus 5 and after aging for 70 hours at 212°F., the hardness shall be within plus or minus 15 percent of the original state hardness.

3.2.2 Stamp pad. The stamp pad shall be composed of materials in accordance with TT-I-600, type I, class 1, black ink.

3.3 Design and construction.

3.3.1 Type holder blocks. The type holder blocks shall be made of wood with metal slots designed to receive the type. The top of the holder blocks shall have a centered hole to receive the handle. The holder blocks shall be 3 inches long, plus or minus 1/8 inch.

3.3.2 Handle. Each printing set shall be provided with suitable handle designed to fit into the holder blocks. The handle shall have a flat face to indicate the front of the stamp, and handle size shall be in accordance with commercial practice.

3.3.3 Type compound for letters, numerals, and symbols. The type compound for producing impressions shall be molded from rubber specified in 3.2.1. The type characters shall be raised in relief by a minimum of 1/32 inch from 1/16 inch minimum thickness sheet-rubber. The sheet-rubber type compound shall be glued on a rubber base which shall fit, by friction, into the metal slots of the holder block. Type shall remain firmly in place and produce clear and distinct impressions, when tested as described in 4.3.3.1.

3.4 Finish. The holders and handle shall be varnished, lacquered, or enameled. Metal components shall be plated or treaded to a bright finish to resist corrosion.

3.5 Instructions. As assembly instruction sheet shall be provided with each set.

3.6 Workmanship. Rubber type shall be sharply and cleanly cut. Handle and holder blocks shall be smoothly finished. The set shall be free from defects or impressions which may impair serviceability.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Testing of basic rubber material. The supplier is responsible for performing the following tests on the basic rubber material used in manufacturing the printing set.

4.1.1.1 Sampling of basic rubber material. The rubber hardness shall be tested as specified in 4.1.1.2. The lot shall be one batch of rubber used in the fabrication of printing sets offered for inspection at one time. The sample shall be two 3 x 3 x 1/16 inch molded rubber sheets. Failure to comply with the test shall be cause to reject the batch of the rubber.

4.1.1.2 Rubber hardness test. The rubber hardness of the original state shall be tested in accordance with method 3021 of Fed. Test Method Std. No. 601, and after aging in accordance with test methods 7001 and 7221. Any nonconformance with requirements of 3.2.1 shall constitute failure to pass this test.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all printing sets offered for inspection at one time.

4.2.2 Sampling of end-item for visual defects. A random sample of printing sets shall be taken from each lot in accordance with MIL-STD-105, inspection level I. The acceptable quality level (AQL) shall be 4.0 percent defective. The sample unit shall be one printing set.

4.2.3 Sampling for preparation for delivery requirements. For examination of interior packages the sample unit shall be one shipping container fully prepared for delivery, and selected at random just prior to the closing operation. Sampling shall be in accordance with MIL-STD-105. Closure defects shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end-item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 percent defective.

4.2.4 Sampling for end-item tests. A random sample of printing sets shall be taken from each lot in accordance with MIL-STD-105, inspection level S-2. The AQL shall be 6.5 percent defective. The sample unit shall be one printing set.

4.3 Examination.

4.3.1 Visual examination of end-item. Samples taken in accordance with 4.2.2 shall be examined for defects listed in table I. Any sample containing one or more defects shall be rejected.

TABLE I. Classification of printing set defects

| Examine | Defect |
|---|---|
| Component parts | Not as specified in 3.1. |
| Holder | Not as specified in 3.3.1. |
| Handle | Not as specified in 3.3.2. |
| Type compound | Not as specified in 3.3.3. |
| Finish | Not as specified in 3.4. |
| Instruction sheet | Missing (see 3.5). |
| Workmanship | Rubber type not sharply and cleanly cut. Handle and holder blocks not smoothly finished. Defects or imperfections which impair serviceability. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

4.3.2 Examination of preparation for delivery. Samples taken in accordance with 4.2.3 shall be examined to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II.

TABLE II. Classification of preparation for delivery defects

| Examine | Defect |
|---|---|
| Markings | Omitted; incorrect; illegible; improper size, location, sequence, or method of application. |
| Materials | Any component missing or damaged. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling, or distortion of container. |
| Contents | Number per container is more or less than required. Net weight exceeds requirements. |

4.3.3 End-item test. Samples taken in accordance with 4.2.4 shall be subjected to the following end-item test.

4.3.3.1 Ink transfer and impression. The stamp shall be made up by inserting at least 10 characters on each line of each holder from each of the sample sets selected. The type face of the stamp shall be inked by pressing or tapping it firmly on the inked pad. Keeping stamp properly inked, 100 impressions shall be made upon a sheet of good-quality bond paper. The impression shall be sharp and uniformly intense. There shall be no filling of closed portions of letter or other characters and no impressions other than those determined by the type face shall be present. At the conclusion of this test, type set-up shall remain solid and show no noticeable movement of characters within slots of holder (see 3.3.3).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, or C as specified (see 6.2).

5.1.1 Level A. All components required for one complete set shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-655 or PPP-B-676. Necessary cushioning and blocking shall be utilized, as required, within the box to prevent damage to the contents. The box shall be closed and sealed in accordance with the appendix to the applicable box specification.

5.1.2 Level C. All components required for one complete set shall be packages in a close-fitting box of the type normally used for the product providing that it insures protection for the product during shipment and safe delivery to its destination.

5.2 Intermediate packaging. Intermediate packaging shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve sets packaged as specified in 5.1.1 shall be packaged in a close-fitting container conforming th Method 1A-13 of MIL-P-116.

5.2.2 Level B. Twelve sets packaged as specified in 5.1.1 shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665 or PPP-B-676. Close and seal the boxes in accordance with appendix to the applicable box specification.

5.2.3 Level C. Twelve sets packaged as specified in 5.1.2 shall be packaged in a close-fitting box of the type normally used for the product providing that it insures protection for the product during shipment and safe delivery to its destination.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

5.3 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.3.1 Level A. Six intermediate packages (72 sets) shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. Close, seal and strap the boxes as specified in the appendix to PPP-B-636.

5.3.2 Level B. Six intermediate packages (72 sets) shall be packed in a close-fitting box conforming to PPP-B-636, class-domestic. Closure of boxes shall be as specified in the appendix to PPP-B-636.

5.3.3 Level C. Six intermediate packages (72 sets) packaged as specified in 5.2.3 shall be packed in a close-fitting box of the type normally used for the product providing they will assure carrier acceptance and safe arrival at destination in compliance with the National Motor Freight Classification or the Uniform Freight Classification.

5.4 Marking. Marking shall be in accordance with 5.4.1 and 5.4.2 as specified (see 6.2).

5.4.1 Civil Agencies. In addition to any special marking required by the contract or order, all interior and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 Military requirements. In addition to any special marking required by the contract or order, all interior and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Printing sets covered by this specification are intended for use in making rubber stamps suitable for producing ink impressions on card and paper card and paper stock.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.

(b) Selection of applicable levels of packaging, intermediate packaging, packing and marking required (see 5.1, 5.2, 5.3, and 5.4).

6.3 Font designation. The 5A font designation consist of the following:

Capital letters - A-5; B-4; C-5; D-4; E-5; F-4; G-5; H-5; I-5; J-3; K-2; L-6; M-4; N-5; O-5; P-4; Q-2; R-5; S-5; T-5; U-3; V-2; W-3; X-2; Y-2; Z-2.

The 6a font designation consists of the following:

Lower case letters - a-6; b-5; c-6; d-5; e-6; f-6; g-5; h-5; i-6; j-4; k-3; l-6; m-5; n-6; o-6; p-4; q-3; r-6; s-6; t-6; u-5; v-3; w-4; x-4; y-4; z-3.

The 4 figure font consist of 4 of each numerial 1 through 9 and 0.

In addition, each set has an assortment of marks and symbols.



Source: https://assist.dla.mil --Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

6.4 The classification covered in previous issues of this specification has been deleted in this revision since the former class 1 item (16-point news gothic face condensed on an 18-point body) is not an active item.

MILITARY INTEREST:

DOD has waived coordination

User Interest:

Army-GL

PREPARING ACTIVITY: GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.