GG-T-671F
March 10, 1981
SUPERSEDING
Fed. Spec. GG-T-671E
November 24, 1975

FEDERAL SPECIFICATION

TRIANGLES, DRAFTING: LINE GUIDES, LETTERING, ADJUSTABLE AND NONADJUSTABLE

(GENERAL SPECIFICATION)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the general requirements for plastic or steel triangles and plastic lettering line guides.

1.2 Classification.

1.2.1 Types. Triangles and line guides shall be of the following types, as specified (see 6.2), and in accordance with the applicable specification sheets (see 2.1):

Type I - Triangles drafting, plastic, transparent.
Type II - Triangles, line guide, lettering, nonadjustable, plastic.
Type III - Triangles, drafting, adjustable, plastic.
Type IV - Triangles, drafting, steel, open center.
Type V - Triangles, drafting, steel, bead supports and lifting knob.
Type VI - Line guide, lettering, adjustable, plastic.

FSC 6675

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

GG-T-671/1 - Triangles, Drafting, Plastic, Transparent.
GG-T-671/2 - Triangles, Line Guide, Lettering, Nonadjustable, Plastic.
GG-T-671/3 - Triangles, Drafting, Adjustable, Plastic.
GG-T-671/4 - Triangles, Drafting: Steel, Open Center.
GG-T-671/5 - Triangles, Drafting, Steel, Bead Supports and Lifting Knob.
GG-T-671/6 - Line Guide, Lettering, Adjustable, Plastic.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston; New York; Washington, DC; Philadelphia; Atlanta; Chicago; Kansas City, MO; Fort Worth; Houston; Denver; San Francisco; Los Angeles; and Seattle, WA.

(Federal Government activities may obtain copies of Federal specifications, standards, and commercial item descriptions, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-116 - Preservation-Packaging, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM):

A 177 - High Strength Stainless and Heat-Resisting Chromium-Nickel Steel Sheet and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Description. The triangles and line guides shall be steel or plastic with the required angles as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

inspections. The government reserves the right to perform any of

3.1.1 Specification sheets. The individual item requirements shall be as specified herein and shall be in accordance with the applicable specification sheets as shown in Table I.

Table I. Triangles

Type	Specification Sheet
I	GG-T-671/1
II	GG-T-671/2
III	GG-T-671/3
IV	GG-T-671/4
V	GG-T-671/5
VI	GG-T-671/6

3.2 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

3.2.1 Plastic. The plastic material shall be acrylic, methacrylate, polystyrene, or vinyl plastic material as specified on the applicable specification sheet.

3.2.2 Steel. Corrosion-resistant steel shall conform to ASTM A 177, 1/4-hard temper, finish no. 6, (tampico brushed), both sides.

3.3 Finish. All surfaces shall be polished. All edges shall be straight and free from burrs.

3.4 Identification marking. Each triangle and line guide shall have the manufacturer's name or trademark, and unless otherwise specified (see 6.2), the letters "US" stamped or otherwise permanently marked upon the item.

3.5 Workmanship. Triangles and line guides shall be free from any defects and imperfections which affect the appearance or which might impair serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

stated requirements

specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Examination of preparation for delivery (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1, and as may be required by the applicable specification sheet. AQL shall be 2.5 percent defective for major defects and 6.5 percent for minor defects.

4.3.3 Test. Samples selected in accordance with 4.3.1 shall be tested as specified in 4.4.2 and as may be required by the applicable specification sheet. AQL shall be 2.5 percent defective.

4.4 Inspection procedure.

4.4.1 Examination. The triangles and line guides shall be examined as specified herein for the following defects:

Major

101. Dimensions not as specified.
102. Material not as specified.
103. Index and graduation marks and numbers not as specified.
104. Holes not spaced or shaped as specified.
105. Edges contain nicks or burrs.
106. Finish not as specified.

Minor

201. Identification marking not as specified.
202. Workmanship not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

given in Table I, II ... test results comply with the requirements ...

4.4.2 Tests.

4.4.2.1 Angle. The angles of each sample shall be checked with a gage block, sine bars, or equivalent means for checking angles. Variation in angles of plus or minus 2 minutes shall constitute failure of this test.

4.4.2.2 Edge straightness. The edges of the sample shall be placed against a precision straightedge, surface plate, bench block, or other precision flat. Measure the points of noncontact between the precision flat and the ruling edges. A variation greater than plus 0.003 inch shall constitute failure of this test.

4.4.2.3 Flatness. The sample shall be placed on a machinist's checking or gaging surface and checked for flatness. A variation in the surfaces from a true plane by more than 0.010 inch shall constitute failure of this test.

4.5 Examination of preparation for delivery. An examination shall be made to determine compliance with the requirements of section 5. The sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of percent defective.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or commercial, as specified (see 6.2).

5.1.1 Level A. Each triangle or line guide shall be preserved in accordance with MIL-P-116, method IC-3 or IC-1. Triangles or line guides of like description, in quantities specified in the contract or order (see 6.2), shall be further packaged in a close fitting fiberboard box conforming to PPP-B-636, W6c. The box shall be closed in accordance with method V of the appendix to the box specification.

5.1.2 Level B. The triangles or line guides shall be packaged as specified in 5.1.1, except that the boxes shall be class domestic, style optional, and the waterproof sealing shall not be required.

5.1.3 Commercial. The triangles or line guides shall be packaged in accordance with normal commercial practice. The complete package shall be designed to protect the items against damage during shipment, handling, and storage (see 6.2).

5.2 Packing. Packing shall be level A, B, or commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. The triangles or line guides, preserved and intermediate packed as specified in 5.1.1, shall be packed in close fitting boxes conforming to PPP-B-621, class 2, or PPP-B-601, overseas type. Gross weight shall not exceed 200 pounds. The boxes shall be closed and strapped in accordance with the appendix to the applicable box specification.

5.2.2 Level B. The triangles or line guides, preserved and intermediate packed as specified in 5.1, shall be packed in close fitting weather resistant fiberboard boxes conforming to PPP-B-636. The boxes shall be sealed in accordance with method V of the appendix to the box specification.

5.2.3 Commercial. Triangles or line guides of like description, packaged as specified in 5.1, shall be packed in fiberboard boxes to insure delivery at destination, provide for redistribution by the initial receiving activity, and be acceptable by common carrier under the National Motor Freight Classification and Uniform Freight Classification.

5.3 Marking.

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The triangles are for use in drafting, preparing drawings and maps, and for use on wet film or plastic sheets. Line guides are used for drawing guidelines for free-hand lettering.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Federal specification sheet part number required (see 1.2 and 3.1.1).
(c) When the letters "US" are not required (see 3.4).
(d) Degree of preservation and packing for military agencies (see 5.1.1 and 5.1.3).
(e) Intermediate pack quantities (see 5.1.1).

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army - ME
Air Force - 99

Review activity:
DLA - GS

User activities:

Navy - MC, CG, YD

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
VA - DMS

Preparing activity:

Army - ME

Project 6675-0701

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE GG-T-671F Triangles, Drafting: Line Guides, Lettering, Adjustable and Nonadjustable (General Specification)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.