MIL-C-28724A(EC)
25 October 1973
SUPERSEDING
MIL-C-28724(EC)
12 February 1970

MILITARY SPECIFICATION

CONTROL, REMOTE SWITCHING, C-7594( )/U AND C-7595( )/U GENERAL SPECIFICATION FOR

1. SCOPE

1.1 Scope. This specification covers the performance, production, and testing requirements for Remote Switching Control units C-7594( )/U and C-7595( )/U for use with shipboard secure voice communications systems.

1.2 Classification. The control units shall be of the following types, as specified:

Type I - For use with surface ships. Provides programming capability for nine telephone sets and five channels.
Type II - For use with small craft. Provides programming capability for three telephone sets and three channels.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-S-901 - Shock Tests, H.I. (High-Impact), Shipboard Machinery, Equipment and Systems, Requirements for
MIL-E-16400 - Electronic Equipment, Naval Ship and Shore; General Specification for
MIL-E-17555 - Electronic and Electrical Equipment, Accessories, and Repair Parts; Packaging and Packing of
MIL-I-45208 - Inspection System Requirements

STANDARDS

FEDERAL

FED-STD-595 - Color

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-108 - Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of
MIL-STD-471 - Maintainability Verification, Demonstration and Evaluation
MIL-STD-781 - Reliability Tests: Exponential Distribution
MIL-STD-785 - Reliability Program For Systems and Equipment Development and Production

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General requirements. The equipment shall conform to the requirements of MIL-E-16400 to the extent specified herein.

3.1.1 Equipment composition.

3.1.1.1 Type I unit. The Type I unit shall consist of a control panel, audio amplifiers, and a power supply.

3.1.1.1.1 Control panel. The control panel shall contain the necessary controls, indicators and switches required to conform to the requirements specified herein. The panel shall contain a matrix type array of 63 illuminated pushbutton switches.

3.1.1.1.2 Audio amplifier. Five plug-in, solid state audio amplifier cards shall be provided, one for each channel. Each card shall provide for amplification in the transmit and the receive mode. Characteristics of the transmit and receive amplifiers shall be controlled by the interface characteristics in 3.14.6.1, 3.14.6.2, 3.14.7.1 and 3.14.7.2 respectively.

3.1.1.1.3 Power supply. A 24 VDC regulated power supply shall be provided for providing power to external equipment connected to the Type I unit, see 3.14.8.

3.1.1.2 Type II unit. The Type II unit shall be similar to the Type I unit except that the control panel shall contain only 12 illuminated pushbutton switches and only 3 amplifier cards are required.

3.1.2 Equipment description.

3.1.2.1 Type I unit. The Type I unit shall provide for interconnection of up to nine remote telephone sets to up to five secure radio channels. The Type I unit shall be capable of being cascaded with other Type I units by transfer switches, thus providing for expanded switching capability. A monitor capability shall be provided whereby any remote unit can monitor any other remote unit. The unit shall have a lock-out feature and a lock-up feature.

3.1.2.2 Type II unit. The Type II unit shall be similar to the Type I unit except that it shall provide for interconnection of three remote telephone sets to up to three secure radio channels and the cascading feature is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

3.2 First article sample. Prior to beginning production, a sample shall be tested as specified in 4.3 (see 6.2.1).

3.3 Finish. The equipment shall conform to the coating and treatment requirements of MIL-E-16400. Finish shall be red enamel, color number 11136 in accordance with FED-STD-595.

3.4 Safety. The equipment shall conform to the safety requirements of MIL-E-16400.

3.5 Workmanship. Workmanship shall be in accordance with MIL-E-16400.

3.6 Environmental conditions.

3.6.1 Temperature. Temperature conditions shall be in accordance with Class 4 of MIL-E-16400, except the non-operating temperature shall be -55°C to +75°C.

3.6.2 Humidity. The equipment shall conform to the humidity requirements of MIL-E-16400.

3.7 Electrical design. The equipment shall conform to the electrical design requirements of MIL-E-16400.

3.7.1 Primary power supply line voltage. The equipment shall be designed to operate within the requirements of this specification when the primary power supply line voltage is 120 volts RMS ±10 percent and line frequency is 60 Hz ±5 percent.

3.7.2 Blown fuse indicators. Blown fuse indicators are not required.

3.8 Test points. Test points shall be in accordance with MIL-E-16400.

3.9 Mechanical design. The equipment shall conform to the mechanical design requirements of MIL-E-16400 and as follows:

3.9.1 Construction. All basic units shall use plug-in printed circuit cards and shall be designed for high reliability and simplicity of operation and maintenance. Mechanical design shall be such that all electrical adjustments on basic units for test and alignment may either be accomplished without need for removal of unit from equipment shelves or by using a module extender or sliding shelf, which permits the unit to operate while test and alignment is accomplished. The unit shall be housed in a ferrous metal case and the degree of enclosure shall be open protected, in accordance with MIL-E-16400 and Table I of MIL-STD-108.

3.9.2 Shock. Shock requirements shall be in accordance with Grade A, Class I, Type A of MIL-S-901.

3.9.2.1 Shock test procedures. The shock test procedures shall be as specified in MIL-E-16400.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

3.9.3 Vibration. Vibration requirements shall be in accordance with MIL-E-16400.

3.9.4 Size.

3.9.4.1 Type I unit. The Type I unit shall be capable of both standard 19 inch (482.6 mm) rack mounting and bulk head mounting and shall not exceed 12 inches (304.8 mm) in depth and 14 inches (355.6 mm) in height. Mounting brackets for rack mounting shall be furnished with each equipment.

3.9.4.2 Type II unit. The Type II unit dimensions shall not exceed 12 inches (304.8 mm) in height, 9 inches (228.6 mm) in width and 12 inches (304.8 mm) in depth. The unit shall be capable of both bulkhead and base mounting.

3.9.5 Weight. The equipment shall conform to the following weight requirements:

Type I unit - 70 pounds (31.752 kg) maximum
Type II unit - 38 pounds (17.24 kg) maximum

3.9.6 Cable entrances. Cable entrances shall be provided on top, bottom and two sides of the case, conforming to the C-7594A/U (for Type I unit), and C-7595A/U (for Type II unit).

3.9.7 Mounting dimensions. Mounting dimensions shall conform to the following:

Type I unit - Mounting dimensions for the Type I unit shall be identical to the C-7594A/U equipment.
Type II unit - Mounting dimensions for the Type II unit shall be identical to the C-7595A/U equipment.

3.10 Parts and materials. Parts and materials shall be selected in accordance with MIL-E-16400 with the exception of magnetic permeability properties which are not applicable to this equipment.

3.11 Supplementary requirements. Requirements for parts identification and markings shall be in accordance with MIL-E-16400.

3.12 Thermal design. The equipment shall conform to the thermal design requirements of MIL-E-16400.

3.13 Panel layout and arrangement of operating controls. Front panel layout and arrangement of operating controls shall conform to the following:

Type I unit - Type I unit shall be identical to the C-7594A/U equipment.
Type II unit - Type II unit shall be identical to the C-7595A/U equipment.

3.14 Functional requirements. The equipment shall conform to the following functional requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

3.14.1 Switching requirements. The circuits to be switched in the Type I and Type II units shall be identical to the switched circuits in the C-7494A/U and the C-7595A/U equipments, respectively. The circuits which are switched straight through from input to output shall conform to the following characteristics:

Resistance (switch closed) - 100 ohms maximum
Resistance (switch open) - 100 K ohms minimum
Current - 3 amperes maximum, noninductive

3.14.2 Switching function characteristics.

3.14.2.1 Type I unit. The pushbuttons with which the switching function is performed shall be arranged in a rectangular matrix consisting of 7 rows and 9 columns. Rows 2 through 6, counting from the top down, shall be associated with secure radio sets 1 through 5, respectively. Row 1 shall be associated with the monitor function and row 7 shall be associated with the transfer and release functions. Columns 1 through 9 shall be associated with remote telephone sets 1 through 9, respectively. The depressing of any one switch in rows 2 through 6 in a vertical column shall connect the radio associated with that respective row with the telephone associated with the selected column. Depressing a pushbutton in row 7 shall release any previously depressed pushbutton in that respective column except in row 1 and shall transfer the remote telephone set connected to that column to the cascaded switching unit.

3.14.2.2 Type II unit. The pushbuttons with which the switching function is performed shall be arranged in a rectangular matrix consisting of 4 rows and 3 columns. Rows 1, 2 and 3, counting from the top down, shall be associated with secure radio sets, 1, 2 and 3, respectively. Row 4 shall be associated with the release function. Columns 1, 2 and 3, counting from left to right, shall be associated with remote telephone sets 1, 2 and 3, respectively. The depressing of any one switch in rows 1, 2 and 3 in a vertical column shall connect the radio associated with that respective row with the telephone associated with the selected column. Depressing a pushbutton in row 4 shall release any depressed pushbutton in that respective column.

3.14.3 Monitor function. The Type I unit shall permit any remote telephone set to monitor any other remote telephone set. Both Push-To-Talk (PTT) lines and both audio transmit lines shall be disconnected when the monitor switch is actuated. The monitor function shall not degrade equipment performance in the transmit and receive condition.

3.14.4 Lock-out feature. The Type I and Type II units shall be so designed that only one pushbutton in a vertical column (with the exception of the monitor pushbuttons on the Type I unit) can be depressed at any time.

3.14.5 Lock-up feature. The Type I and Type II units shall be provided with a lock-up feature which shall lock the matrix in a programmed condition, thereby preventing unauthorized access of any channel by a telephone set. The lock shall be key controlled. Red and green indicator lamps shall be provided on the front panel of the matrix to indicate the locked and unlocked conditions. The red lamp shall be labeled "Locked". The green lamp shall be labeled "Unlocked".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

3.14.6 Input interface characteristics. The input interface shall be capable of operating with a remote secure telephone set. This interface is specified in 3.14.6.1 through 3.14.6.5.

3.14.6.1 Transmit audio. The transmit audio interface shall conform to the following characteristics:

Level from telephone - -20 dBm average, 0 dBm peak
Frequency characteristic of telephone - 70 Hz to 4 kHz, flat within 8 dB, peak to peak
Impedance - 600 ohms ±10 percent at 1 kHz, balanced
Open circuited when the telephone is in the monitor mode

3.14.6.2 Receive audio. The receive audio interface shall conform to the following characteristics:

Level - Average 0 dBm
Frequency response - 200 Hz to 4 kHz, flat within 12 dB peak to peak
Impedance - 600 ohms ±10 percent at 1 kHz balanced
Distortion - 5 percent maximum
Noise - The signal to noise ratio shall be greater than 40 dB referenced to a 0 dBm input signal level. Noise shall be considered hum and any other extraneous signal noise. All audio inputs and outputs including the one under test shall be terminated into 600 ohms ±10 percent.

3.14.6.3 Disconnect indicator. The disconnect indicator is used with certain, but not all, types of secure telephone sets. A disconnect signal shall be provided at the telephone interface when no connection to the telephone is made on the matrix switches. The interface shall conform to the following characteristics:

Disconnect - +24 volts ±10 percent with series resistance of 150 ohms ±20 percent
Connect - Ground with a series resistance of 150 ohms ±20 percent

3.14.6.4 +24 volts DC. +24 volts DC is supplied to each telephone, and is unswitched, and derived from the power supply described in 3.14.8. The current to each telephone will be 150 mA maximum.

3.14.6.5 Signal ground. Each telephone interface shall have a terminal for signal ground.

3.14.7 Output interface characteristics. The output interface shall be capable of operating with a secure radio system. This interface is specified in 3.14.7.1 through 3.14.7.3.

3.14.7.1 Transmit audio. The transmit audio interface shall conform to the following characteristics:

Level - -20 dBm average, 0 dBm peak
Frequency response (referenced to a selected input 3.14.6.1) - 70 Hz to 4 kHz flat within 8 dB peak to peak

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

Impedance - 600 ohms ±10 percent at 1 kHz balanced
Distortion - 3 percent maximum
Noise - The signal to noise ratio shall be greater than 40 dB referenced to 0 dBm signal level. Noise shall be considered hum and any other extraneous signal. All inputs and outputs including the one under test shall be terminated into 600 ohms ±10 percent.
Gain - The gain shall be unity ±3 dB when referenced to a selected input, see 3.14.6.1.

3.14.7.2 Receive audio. The receive audio shall conform to the following characteristics:

Level from the secure radio system - 0 dBm average, +10 dBm maximum
Frequency band from the secure radio system - 200 Hz to 4 kHz, flat within 12 dB peak to peak
Impedance - 600 ohms ±10 percent, balanced

3.14.7.3 +24 volts DC. +24 volts DC is supplied to each secure radio system and is unswitched and derived from the power supply described in 3.14.8. The current requirements are as follows:

Type I unit - 400 mA. maximum per channel
Type II unit - 120 mA. maximum per channel

3.14.8 Power supply. The Type I and Type II units shall each contain a 24 VDC regulated power supply. The power supply shall be a plug-in type, shall be removable from the front of the equipment and shall be physically interchangeable with the power supplies for the C-8151/U and the C-7594/U control, remote switching units. This interchangeability shall include maximum commonality of parts.

3.14.8.1 Short circuit protection. Short circuit overload protection shall be provided so that a direct short on the DC output will not damage the power supply. Such a provision shall allow resumption of operation immediately following removal of the overload.

3.14.8.2 Characteristics. The power supply shall conform to the following characteristics:

Voltage - +24 volts DC ±5 percent
Current - 3.5 ampere max (Type I unit)
1 ampere max (Type II unit)
Ripple - less than 10 MV RMS at full load
Regulation - ±1 percent no load to full load

3.14.9 Crosstalk. There shall be a minimum of 80 dB isolation between transmit inputs and receive circuits within the Type I and Type II units.

3.15 Reliability.

3.15.1 Quantitative reliability requirement. The specified MTBF (θ_o as defined by MIL-STD-781) of this equipment shall be 1500 hours at 50°C ambient.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

3.15.2 Reliability program. The contractor shall prepare an effective reliability program in accordance with MIL-STD-785. The program shall ensure reliability involvement through all aspects of the design, development, and production as necessary to conform to the contractual reliability requirements.

3.16 Maintainability.

3.16.1 Quantitative maintainability requirements. The equipment shall have a specified Equipment Repair Time (ERT) of 30 minutes with repair accomplished by the replacement of modules, chassis-mounted electronic, electromechanical, and mechanical parts.

3.17 Electro-magnetic compatibility (EMC). The equipment shall conform to the limit requirements for Class 1C equipment in accordance with MIL-STD-461 for the following tests only:

CE01, CE03, CS01, CS06, RE02, RS01 and RS03

The equipment shall be self-compatible and compatible with co-located equipment normally working in its intended installation.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection system requirement. The contractor shall provide and maintain a written inspection system acceptable to the Government for supplies and services covered by this specification. The inspection system shall be in accordance with MIL-I-45208.

4.1.2 Government verification. All quality assurance operations performed by the contractor will be subject to Government verification at any time. Verification will include: (a) surveillance of the operations to determine that practices, methods, and procedures of the written inspection system are being properly applied, (b) Government product inspection to measure quality of product to be offered for acceptance, and (c) Government product inspection of delivered products to assure compliance with all inspection requirements of this specification. Failure of the contractor to promptly correct deficiencies discovered by him or of which he is notified shall be cause for suspension of acceptance until corrective action has been made or until conformance of product to prescribed criteria has been demonstrated.

4.1.3 Quality assurance terms and definitions. Quality assurance terms used in this specification shall be as specified in MIL-STD-109.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The method of examination and testing of the equipment fall within the following classifications:

First article inspection (see 4.3)
Quality conformance inspection (see 4.4)
    Production inspection
    Production control inspection
Reliability tests (see 4.5)
Maintainability demonstration (see 4.6)

4.3 First article inspection. Unless otherwise specified (see 6.2), one Type I and one Type II unit shall be required for first article inspection. First article inspection shall consist of all examination and testing necessary to determine compliance with the requirements of this specification. First article inspection shall include the tests specified in Table I.

Table I. First article inspection.

Inspection	Requirement reference	Procedure reference
Surface examination	3.1.1, 3.3, 3.5, 3.9.6, 3.9.7, 3.10, 3.11, 3.13	4.7.1
Operating test	3.4, 3.14.1, 3.14.2, 3.14.3, 3.14.6, 3.14.7, 3.14.8.2	4.7.2
Size	3.9.4	4.7.1
Weights	3.9.5	4.7.1
Supply line voltage and Frequency	3.7.1	4.7.1
Heat test	3.6, 3.12	4.7.1, 4.7.3
Temperature and Humidity	3.6.1, 3.6.2	4.7.1
Power	3.7	4.7.1
Controls and controls circuit	3.14.4, 3.14.5, 3.14.8.1	4.7.1
Shock	3.9.2	4.7.1
Vibration	3.9.3	4.7.1
Electro-magnetic Compatibility	3.17	4.7.4

4.4 Quality conformance inspection.

4.4.1 Production inspection. Production inspection shall be made on every equipment offered for delivery. The inspection shall comprise such examination

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

and testing as will prove the workmanship and reveal the omissions and errors of the production process such as functional and performance tests at a limited number of points, tests which detect deviations from design, tests of adjustments, and tests which detect hidden defects of material. Production inspection shall consist of the tests approved in accordance with applicable test procedures and as shown in Table II.

Table II. Production inspection.

Inspection	Requirement reference	Procedure reference
Surface Examination	3.3, 3.5, 3.10, 3.11	4.7.1
Operating test	3.4, 3.14.1, 3.14.2, 3.14.3, 3.14.6, 3.14.7, 3.14.8.2	4.7.2

4.4.2 Production control inspection. Production control inspection including sampling, shall conform to Table III and to the procedures for special inspection levels of MIL-STD-105. The inspection level shall be S-4 for normal, tightened, and reduced inspection. Production control inspection shall be performed on equipments that have passed production inspection. The equipment shall satisfactorily conform to the requirements of production control inspection prior to release for shipment.

Table III. Production control inspection.

Inspection	Requirement reference	Procedure reference	AQL percent
Size	3.9.4	4.7.1	10
Weights	3.9.5	4.7.1	10
Supply line voltage and frequency	3.7.1	4.7.1	6.5
Heat test	3.6	4.7.1	6.5
Power	3.7	4.7.1	6.5
Controls and control circuits	3.14.4, 3.14.5, 3.14.8.1	4.7.1	6.5

4.4.2.1 Rejected lots. If an inspection lot is rejected, the supplier may withdraw the lot from further inspection. The supplier may also rework a rejected lot to correct the defective units and reinspect the lot using tightened inspection. Rejected lots shall be kept separate from new lots and shall not lose their identity.

4.4.2.2 Reinspection of conforming production control test units. Unless otherwise specified, sample units which have been subjected to and passed

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

production control inspections may be accepted on the contract provided they are refurnished to like new condition, resubjected to and pass production inspection.

4.5 Reliability tests.

4.5.1 Reliability demonstration. Reliability demonstration shall be performed in accordance with MIL-STD-781.

4.5.2 Reliability qualification tests. Qualification testing shall be performed on at least three production units. Testing shall be performed at test level C with test plan V. Testing shall proceed to a decision in accordance with the criteria specified in MIL-STD-781 for test plan V.

4.5.3 Reliability sampling tests. Reliability sampling tests shall be conducted throughout production to ensure continued production of acceptable equipment. Sampling testing shall be at test level C, with test plan VI of MIL-STD-781. At least three units shall be randomly selected from each month's production for reliability sampling tests. Testing shall proceed to a decision in accordance with the criteria specified in MIL-STD-781 for test plan VI.

4.5.4 Failure. Failure shall be defined as any malfunction or parameter deviation that prevents the equipment from performing within the operational requirements set forth in this specification.

4.5.5 Reliability test procedures. The reliability tests shall be conducted using the procedures, schedules and performance limits specified herein as a minimum.

4.5.6 Burn-in. The supplier may elect to operate the reliability test samples for a certain time prior to the initiation of reliability testing. Any such burn-in applied to test samples must be applied to all items of equipment submitted for acceptance. Failures occurring during this period may be considered non-relevant but shall be recorded and reported. Burn-in time for all items of equipment submitted for acceptance shall be at the same levels of environment and for the same integral number of cycles as the burn-in conducted on the test samples.

4.6 Maintainability demonstration. The equipment maintainability requirement shall be demonstrated in accordance with Method 3 of MIL-STD-471. The maintainability demonstration shall be successfully completed prior to the delivery of any equipment. The maintainability demonstration shall be performed after completion of first article testing and prior to reliability testing.

4.7 Inspection procedures.

4.7.1 Tests and examinations. All tests and examinations specified herein shall be conducted in accordance with the applicable inspection procedures of MIL-E-16400, except as modified below.

4.7.2 Operating test. The equipment shall be energized and subjected to an operating test to insure the proper functioning and performance at an adequate number of points in the required range to demonstrate conformance to

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

specification requirements, including safety. The operating test shall include, but not be limited to, the tests shown in Table IV.

Table IV. Operating test.

Test	Requirement reference
Input and output interface characteristics	3.14.6, 3.14.7
Switching functions characteristics	3.14.1, 3.14.2
Monitor functions	3.14.3
Cross talk	3.14.9
Power supply characteristics	3.14.8.2

4.7.3 Temperature tests. Temperature tests shall be conducted in accordance with the requirements of MIL-E-16400 for Class IV equipment, except that the non-operating temperature shall be -55°C to +75°C.

4.7.4 Electro-magnetic compatibility test. The EMC requirements of 3.17 shall be verified by tests performed in accordance with MIL-STD-462.

4.8 Inspection of preparation for delivery. Examinations shall be conducted to ensure conformance with the requirements of Section 5 of this specification.

5. PREPARATION FOR DELIVERY

(The preparation for delivery requirements specified herein apply only for direct Government procurements. Preparation for delivery requirements of referenced documents listed in Section 2 do not apply unless specifically stated in the contract or order. Preparation for delivery requirements for products procured by contractors shall be specified in the individual order).

5.1 Preservation, packaging, packing, and marking. Unless otherwise specified, preparation for delivery shall be in accordance with the applicable levels of preservation, packaging, packing, and marking specified in MIL-E-17555 (see 6.1).

6. NOTES

6.1 Intended use. The Type I unit is intended for use on surface ships and the Type II unit is intended for use on submarines and small craft. The equipment will be used in a secure voice communications system. It will provide an operator the capability or programming several remote telephone sets to secure radio channels.

6.2 Ordering data. Procurement documents should specify:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

6.2.1 Procurement requirements.

(a) Title, number, and date of this specification.
(b) Number of first article samples to be submitted if other than as specified in 4.3.
(c) Number of samples required for reliability qualification tests, if other than as specified in 4.5.1 and 4.5.3.
(d) Levels of preservation, packaging, and packing, and applicable marking (see 5.1).

Preparing activity:
NAVY - EC

(Project 5840-N153)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.