MILITARY SPECIFICATION

CONTROL, REMOTE SWITCHING, C-7594( )/U AND C-7595( )/U
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-C-28724A(EC), dated 25 October 1973.

Page 1

2.1, SPECIFICATIONS, MILITARY: Delete "MIL-I-45208-Inspection System Requirements".

Page 7

3.15.1, line 2: Delete "of this equipment shall be 1500 hours at 50°C ambient." and substitute "shall be 1500 hours at 50°C for Type I units and 3000 hours at 50°C for Type II units."

Page 8

4.1.1: Delete.

Page 9

Table I, Requirement reference column for operating test: Add ",3.14.9".

Table I, Procedure reference column for Heat test: Delete ",4.7.3".

Table I, Procedure reference column for Temperature and Humidity: Add ",4.7.3".

Page 10

Table II, Requirement reference column for Operating test: Add ",3.14.9".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.

Page 11

4.5.2, first sentence: Delete and substitute "Qualification testing shall be performed on the Type I control unit only. However, if the contract or purchase order does not require Type I control units, then qualification testing shall be performed on the Type II control unit. At least three production control units shall be tested to demonstrate reliability (see 6.2.1)."

4.5.3, line 4: After "units" insert "of the same type tested in accordance with 4.5.2".

Page 13

6.2.1,(c), line 2: Delete "and 4.5.3" and substitute "through 4.5.3".

Preparing activity:
Navy-EC
(Project 5840-N154)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.