MILITARY SPECIFICATION

CABLE, SPECIAL PURPOSE, RADIO FREQUENCY,

BUOYANT, COAXIAL, TYPE RG-384/U

This amendment forms a part of Military Specification MIL-C-28726(EC), 9 January 1970.

Page 2

3.3.7: Delete the first sentence and substitute "The jacket shall consist of two layers of black foamed polyethylene securely bonded together."

Add new paragraph:

"3.3.7.1 Jacket bonding. The cable shall satisfactorily meet the bonding test of 4.6.11."

Page 4

Add new paragraphs:

"4.6.1.2 Each length of cable shall be passed thru a three inch long block which is bored to a diameter of .674 to .675 inches. The ends of the bore shall be provided with a 1/8 inch radius to prevent damage to the cable. The cable shall pass through the block freely enough for the block to be held by hand.

"4.6.1.3 The diameter of the bore shall be checked after every 10 reels of cable have been passed through the block. When the bore is worn to a diameter of .676 the block shall be replaced."

Page 5

Add new paragraph:

"4.6.11 Jacket bonding. A knife cut 1/16 of an inch deep shall be made across one side of the cable. The cable shall be bent back on itself with the cut on the outside of the bend. There shall be no indication of separation of the inner and outer jacket."

1/ CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ECT.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

Preparing activity:
Navy - EC

(Project 6145-N187)

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:50Z
Check the source to verify that this is the current version before use.