
MILITARY SPECIFICATION SHEET

CONNECTOR, ELECTRICAL, INSERT (INSULATOR), FEMALE RECTANGULAR, POLARIZED, CENTER SCREW LOCK, FOR 20 REMOVABLE CONTACTS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-28731.




Inches	mm
.005	0 13
.044	1 12
.046	1 17
.075	1 90
.086	2 18
.093	2 36
.100	2 54
.109	2 77
.147	3 73
.150	3 81
.160	4 06
.190	4 83
.198	5 03
.205	5 21
.257	6 53
.410	10 41
.412	10 46
.500	12 70
.562	14 27
.681	17 30
.686	17 42
.750	19 05
.800	20 32
.803	20 40
.920	23 37
1.000	25 40
1.125	28 58
1.312	33 32
2.144	54 46
2.160	54 86
2.593	65 86

FIGURE 1. Connector, female rectangular.

(F) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:55Z
Check the source to verify that this is the current version before use.



POLARIZING POSITION CHANGE

Keying position on both polarizing sockets can be rotated to desired position by loosening spanner nut (counter-clockwise), resetting socket in one of six positions then retightening spanner nut (clockwise).

NOTE: Overtightening of spanner nut can fracture connector. Spanner keying wrench shown below.



CONFIGURATION
OPTIONAL DIMENSIONS
REF ONLY


Inches	mm
03	0 8
06	1 5
086	2 18
100	2.54
140	3 56
250	6 35
1 00	25 4
1 37	34 8

SPANNER WRENCH

Configuration A - Connector polarization guide (layout)

FIGURE 1. Connector, female rectangular - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:55Z
Check the source to verify that this is the current version before use.



Inches	mm
015	0.38
030	0 76
.039	0 99
040	1 02
042	1 07
.085	2.16
158	4.01
172	4.37
.588	14 94
730	18.54
920	23.37





FIGURE 1. Connector, female rectangular - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:55Z
Check the source to verify that this is the current version before use.



Configuration B - Contact hole detail

Inches	mm
.005	0 13
028	0 71
060	1 52
062	1 57
070	1 78
128	3 25
133	3 38
273	6 93
468	11 89
803	20 40

FIGURE 1 Connector, female rectangular - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:55Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Tolerances between any two contact centers shall be ±.004 (0.10 mm).
4. Flatness, squareness, and parallelism shall be within dimensional tolerances.
5. Contact hole details shall be in accordance with configuration B.
6. Mating connector information.
   M28731/10-0109, and -0112 and mate with M28731/9-0110, -0113 and -0115.
   M28731/10-0110, -0113 and -0115 mate with M28731/9-0109 and -0112.
   M28731/10-0111, -0114 mate with M28731/9-0111, -0114 and -0116.
7. Polarization information:
   Polarization sockets are provided for indexing to preclude intermixing of adjacent connectors. By using a standard type spanner wrench, polarization pins can be rotated to desired position. For parts supplied directly to the government, polarization will be in the 1-1 position. For other polarization positions see connector polarization guide configuration A (see marking, note 13d). For direct government acquisition a tool is supplied in the unit package for polarization socket adjustment.
8. Contact and terminal designations:
   Contacts and terminals shall be designated on the insulator using letters in the location shown on figure 1.
9. Tolerance shall be ±.010 (0.25 mm) unless otherwise specified.
10. Patent notice:
    Patent No. 3,248,686 owned by Elco Corporation. The government has a royalty-free license under the above patent for the benefit of manufacturers of items called for in this specification, either for the government or for use in equipment to be delivered to the government.
11. For direct government acquisition crimp contacts M28731/20-0001 are furnished in a plastic bag in each unit package (see marking, note 13a).
12. For direct government acquisition solder hole and wrappost contacts M28731/25-0001 and /26-0001 are factory installed in connector body (see marking, note 13a).
13. Marking
    a. Connectors supplied directly to the government shall be marked with the military part number (see table I). Example M28731/10-0110.
    b. Connectors supplied with contacts to government end users shall be marked with the military part number (see table I). Example M28731/10-0110.
    c. Connectors supplied without contacts to government end users shall be marked as follows Example M28731/10F (screw or socket type from table I). The user shall complete the remaining portion of the military part number as shown in table I based upon contact type he assembles. Example M28731/10F-0110.
    d. Polarization position marking is not required unless otherwise specified. When required polarization marking shall be in accordance with the connector polarization guide (see configuration A). The marking shall appear following the part number.
14. Applicable contact insertion and removal tools:

    Insertion MIL-I-81969/13-01
    Removal MIL-I-81969/11-01

15. When double wire crimp contact MIL-C-28731/23 is required for use with the connector, it shall be ordered separately.
16. Rectangular shields shall conform to MIL-C-28731/19-0001 or -0002 and must be ordered separately.
17. Recommended hardware (not furnished) for panel mounting: (4) .086-56-UNC-2A (length to suit) bolt with No. 2 washer and mating nut.

FIGURE 1. Connector, female rectangular - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:55Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration See figure 1.

Mating and unmating forces (torque) 35 inch-ounces, maximum.

Dielectric withstanding voltage. 1,250 V rms, 60 Hz, minimum

Mechanical shock High impact shock applicable.

Part number. See table I.

TABLE I. Part number information.

Military part number	Actuating hardware	Polarizing socket position		Contact type
		A .100 Dia.	B .086 Dia.	
M28731/10-0109	Jackscrew Type C	1	1	Crimp MIL-C-28731/20 1/
M28731/10-0110	Fixed socket Type F	1	1	Crimp MIL-C-28731/20 1/
M28731/10-0111	Jack socket Type H	1	1	Crimp MIL-C-28731/20 1/
M28731/10-0112	Jackscrew Type C	1	1	Solder hole MIL-C-28731/25 2/
M28731/10-0113	Fixed socket Type F	1	1	Solder hole MIL-C-28731/25 2/
M28731/10-0114	Jack socket Type H	1	1	Solder hole MIL-C-28731/25 2/
M28731/10-0115	Fixed socket Type F	1	1	Wrappost MIL-C-28731/26 2/

1/ See figure 1, note 11
2/ See figure 1, note 12

NOTE.
M28731/10-0109 supersedes M28731/10-0001 thru M28731/10-0036.
M28731/10-0110 supersedes M28731/10-0037 thru M28731/10-0072.
M28731/10-0111 supersedes M28731/10-0073 thru M28731/10-0108.

Custodians
Army - CR
Navy - EC
Air Force - 85

Review activities.
Army - AR, AT, MI
Navy - AS
Air Force - 11, 17, 99
DLA - ES

User activities.
Army - AL, AV, ME
Navy - MC, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5935-3653-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:55Z
Check the source to verify that this is the current version before use.