MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM,
(NONPOLARIZED, ETCHED FOIL), 85°C (VOLTAGE DERATED TO 125°C),
ESTABLISHED RELIABILITY,
STYLE CLR27

This amendment forms a part of Military Specification Sheet MIL-C-39006/2C, dated 10 January 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following preamble, add:

" FAILURE RATE LEVEL 'L' INACTIVE FOR DESIGN AFTER 27 May 1976 "

" CASE SIZE E1 INACTIVE FOR DESIGN AFTER 20 Oct 1978 "

FIGURE 1 (dimension table): Add G1 case size

"	G1	.688 (17.48)	.188 (4.78)	.219 (5.56)	1.188 (30.18) "

PAGE 2

* TABLE I, following part no. M39006/02-: Add "1/".

* TABLE I, part number column: Add "-" following numbers 1228 through 1339 to denote optional random vibration part numbers.

* TABLE I: Add the new G1 case size units

"

Rated voltage (85°C)	Cap.	Cap. tolerance	DC leakage (max) 25°C	DC leakage (max) 85°C 125°C	Derated voltage (125°C)	Surge voltage (85°C)	Impedance (max)	Case size	Part no. M39006/02- 1/ Failure rate level (%/1,000 hr) L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
15	10	+75,-15	2	4	10	17.2	339	G1	2500	2507-	2514-	2521-	2528-
25	5	+75,-15	2	4	15	28.8	680	G1	2501	2508-	2515-	2522-	2529-
30	4.5	+75,-15	2	6	20	34.5	754	G1	2502	2509-	2516-	2523-	2530-
50	2.5	+50,-15	2	4	30	57.5	1355	G1	2503	2510-	2517-	2524-	2531-
75	1.5	+50,-15	2	4	50	86.2	2255	G1	2504	2511-	2518-	2525-	2532-
100	1	+30,-15	2	4	65	115.0	3385	G1	2505	2512-	2519-	2526-	2533-
150	0.5	+30,-15	2	4	100	172.0	6780	G1	2506	2513-	2520-	2527-	2534-

"

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:14Z
Check the source to verify that this is the current version before use.

* Following Table I: Add "1/ Dash number for failure rate level M, P, R, and S parts will include the letter 'H' to indicate the optional random vibration requirement or '-' will be deleted."

PAGE 3

* Following vibration requirement, add new Random vibration requirement:
"Random vibration (when applicable): Method 214 of MIL-STD-202, test condition II-E (18.7 g)."

Temperature cycling: Delete "Temperature cycling: Method 102 of MIL-STD-202, condition D" and substitute "Thermal shock: Method 107 of MIL-STD-202, condition A."

PAGE 4

Life at 85°C: Delete "240-hr (group B)" requirement in its entirety; also delete "10,000-hr (group C)" and substitute "10,000-hr (group B)".

Add the following new requirement under "Life at 125°C":
"10,000-hr (group B):

DCL (125°C)	- 125% (max) of table I value.
DCL (25°C)	- See table I.
ΔCap.	- Within ±50% of initial measurement for E1 and G1 cases; within ±25% of initial measurement for all other cases.
DF	- 80% (≤30 V) or 60% (>30 V) for E1 and G1 cases; 40% (≤30 V) or 30% (>30 V) (max) for all other cases.
DWV	- 2,000 Vdc, min.
IR	- 100 megohms, min."

Marking: Delete requirement in its entirety and substitute:
"Marking: In accordance with MIL-C-39006."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR
Air Force - 17,85,99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA-ES

Preparing activity:
Navy - EC

(Project 5910-1404-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:14Z
Check the source to verify that this is the current version before use.