INCH-POUND

MIL-R-39005/10A(USAF)
27 December 1989
SUPERSEDING
MIL-R-39005/10(USAF)
19 July 1966

MILITARY SPECIFICATION

RESISTORS, FIXED, WIRE-WOUND (ACCURATE),
ESTABLISHED RELIABILITY
STYLE RBR76 1/

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for style RBR76, established reliability, accurate, wire-wound, fixed resistors.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-R-39005 - Resistors, Fixed, Wire-Wound (Accurate), Established Reliability, General Specification for.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the reference cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

1/ Not for new design, for AF replacement purposes only.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Electronic Support Division AFLC, Gentile AF Station, Dayton, OH 45444-4500 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:12Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-39005, and as specified herein.

3.2 Design and construction. The resistor shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 Applicable resistance values and tolerances. Applicable resistance values based on use of 0.0009 absolute diameter wire, and initial resistance tolerances of ±0.1 or ±1.0 percent, shall be as follows.

Ohms	Ohms
18.36	916.00
50.00	923.00
118.20	930.00
130.00	937.00
232.00	944.00
400.00	951.00
487.10	958.00
560.00	965.00
583.00	972.00
619.00	3,344.00
662.00	
681.00	
825.00	

3.4 Power rating. Power rating shall be 0.5 watt.

3.5 Maximum voltage. Maximum voltage shall be 300 volts direct current or peak.

3.6 Maximum weight. The maximum weight shall be 6 grams.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-R-39005.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-R-39005.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)


6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-R-39005 are applicable to this specification.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:12Z
Check the source to verify that this is the current version before use.



Dimension	Inches	Millimeters
A	.812 +.020 -.032	20.62 +0.51 -0.81
B	.312 ±.015	7.92 ±0.38
C	1.500 min	38.10
D	.032 ±.002	0.81 ±0.05

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

* FIGURE 1. Style RBR76 resistor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:12Z
Check the source to verify that this is the current version before use.

6.3 Supplementary insulation. Where potential to ground is over 250 volts, supplementary insulation should be provided.

6.4 Supersession data. This specification supersedes MIL-R-38101/5A(USAF) and MIL-R-38101/9A(USAF), dated 15 October 1963.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Review activities:
Air Force - 17, 85
DLA - ES

User activity:
Air Force - 19

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5905-F301)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:12Z
Check the source to verify that this is the current version before use.