INCH-POUND

MIL-C-39006D
SUPPLEMENT 1
23 December 1992

MILITARY SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM,
ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-C-39006D, dated 23 December 1992.

SPECIFICATION SHEETS

MIL-C-39006/1	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Etched Foil), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR25.
MIL-C-39006/2	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Nonpolarized, Etched Foil), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR27.
MIL-C-39006/3	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Plain Foil), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR35.
MIL-C-39006/4	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Nonpolarized, Plain Foil), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR37.
MIL-C-39006/9	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR65.
MIL-C-39006/16	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, High Etched Foil), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR71.
MIL-C-39006/17	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Nonpolarized, High Etched Foil), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR73.
MIL-C-39006/18	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR10.
MIL-C-39006/19	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR14.
MIL-C-39006/20	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR17.
MIL-C-39006/21	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR69.
MIL-C-39006/22	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR79.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:14Z
Check the source to verify that this is the current version before use.

MIL-C-39006/25	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR81.
MIL-C-39006/28	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), High Reliability, Style CLS79.
MIL-C-39006/29	-	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), High Reliability, Style CLS81.

CONCLUDING MATERIAL

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1720)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:14Z
Check the source to verify that this is the current version before use.