INCH-POUND
MIL-PRF-39006F
SUPPLEMENT 1
20 August 2004

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE),
TANTALUM, ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39006F, dated 20 August 2004.

MIL-PRF-39006/9 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR65.

MIL-PRF-39006/18 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR10.

MIL-PRF-39006/19 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR14.

MIL-PRF-39006/20 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR17.

MIL-PRF-39006/21 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR69.

MIL-PRF-39006/22 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR79.

MIL-PRF-39006/25 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR81.

MIL-PRF-39006/30 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR90

MIL-PRF-39006/31 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug), (Extended Range), 85°C (Voltage Derated to 125°C) Established Reliability, Style CLR91

MIL-PRF-39006/32 - Capacitors, Fixed, Electrolytic (Non-Solid Electrolyte) Tantalum, (Non-Polarize, Sintered Slug) 85°C (Voltage Derated to 125°C), Established, Reliability, Style CLR82

Preparing activity:
DLA - CC

(Project 5910-2266)

AMSC N/A
5910

FSC

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:13Z
Check the source to verify that this is the current version before use.