INCH-POUND

MIL-DTL-3943/228A
04 October 2012
SUPERSEDING
MIL-DTL-3943/228
30 June 1997

DETAIL SPECIFICATION SHEET


MEDAL, AMERICAN DEFENSE SERVICE

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH (-1 and -2): Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:35Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
DIAMETER (Excluding lug):
-1: 1-1/4 inches (REF)
-2: 5/8 inch (REF)

THICKNESS (At thickest point):
-1: 0.140 inch ± 0.010 inch
-2: 0.095 inch ± 0.010 inch

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/10.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force – 11
Navy – NU

Preparing activity:
Army – IH

Review activities:
Navy – MC, CG1

(Project No. 8455-2012-076)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:35Z
Check the source to verify that this is the current version before use.