INCH-POUND

MIL-DTL-3943/235A
5 January 2015
SUPERSEDING
MIL-DTL-3943/235
30 June 1997

DETAIL SPECIFICATION SHEET


MEDAL, UNITED NATION SERVICE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH (-1 and -2): Oxidized, Buffed Relieved and shall match The Institute of Heraldry Metal Finish Chip Number 4

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:38Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
WIDTH:
-1: 1-19/32 inches (REF)
-2: 11/16 inch (REF)
HEIGHT (Overall including suspension bar):
-1: 2-15/32 inches (REF)
-2: 1-5/16 inches (REF)
THICKNESS (At thickest point):
-1: 0.185 inch ± 0.010 inch
-2: 0.115 inch ± 0.010 inch

DECORATION SET: The decoration set shall consist of a regular size medal and a service ribbon. The presentation case shall be as specified by the procuring agency.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Pendant and suspension bar are one piece.

3. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/146

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC, CG1
DLA - CT

(Project No. 8455-2015-053)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:38Z
Check the source to verify that this is the current version before use.