INCH - POUND

A-A-52564A
August 27,2001
SUPERSEDING
A-A-52564
August 15, 1996

COMMERCIAL ITEM DESCRIPTION
STEREOSCOPE, LENS-PRISM-MIRROR, AERIAL PHOTOGRAPH INTERPRETATION (WITH BINOCULARS AND CASE)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies. The original issue of this CID replaced MIL-S-20660.

1. SCOPE. This specification covers a mirror stereoscope with binoculars and a carrying case.

2. SALIENT CHARACTERISTICS

2.1 Description. The stereoscope is used for the examination of stereoscopic pairs of aerial photographs. The stereoscope shall consist of lenses, prisms, mirrors, binoculars, and folding legs. The binoculars are used with the stereoscope to magnify portions of the aerial photograph for closer examination.

2.2 Materials. The contractor shall select the materials, but the materials shall be capable of meeting all of the operational and environmental requirements specified herein. Recovered materials shall be used to the maximum extent possible.

2.3 Performance characteristics.

2.3.1 Stereoscope. The stereoscope shall be of the mirrored type and shall be large enough to accommodate photographs up to 9in X 9in (22.9 cm X 22.9 cm). It shall be mounted on folding

Beneficial comments recommendations, additions, deletions, clarification, etc., and any other data which may improve this document should be sent to: ENGINEER RESEARCH AND DEVELOPMENT CENTER, CORPS OF ENGINEERS, U.S. ARMY TOPOGRAPHIC ENGINEERING CENTER, ATTN: CEERD-TS, 7701 TELEGRAPH ROAD, ALEXANDRIA, VA 22315-3864.

AMSC N/A FSC 6675

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

legs with at least one leg being adjustable to accommodate irregular surfaces. All glass surfaces shall be treated to reduce reflectivity/glare.

2.3.1.1 Lenses. The resolving power of the stereoscope lenses, without the binoculars, shall be at least 153.85 lines per inch (6 lines per mm) at the center of the field of view. The lenses, exclusive of binoculars, shall have focal lengths of 11.25 inches (28.6 cm) ± 1 percent. They shall be free of any defect that adversely affects optical quality and when mounted shall be of sufficient size to permit easy viewing by operators having inter-pupilary distances from 2.05 to 2.95 inches (52 to 75 mm). The assembly shall be sealed to prevent entry of dirt and dust between the lenses and the prisms. The optical distance from the lenses to the plane of the photographs shall be such that the eyes of an observer are accommodated to a distance between eight feet (2.44 m) and infinity.

2.3.1.2 Mirrors. Mirrors shall be provided with easily attachable, fungus resistant, soft covers. Mirrors shall be mounted in such a way as to permit easy removal or replacement. The right and left mirrors shall be interchangeable.

2.3.1.3 Prisms. The prisms shall be high-grade, right angle, 45-degree prisms, free from color and defects that would impair vision in normal use. The ends shall be fine ground.

2.3.2 Binoculars. The binoculars combined with the basic stereoscope shall have a magnification of approximately four-times power and a resolution of at least 358.98 lines per inch (14 lines per mm). All glass surfaces shall be coated to reduce reflection. The image presented shall be upright. The binoculars shall accommodate varying inter-pupillary distances and shall be adjustable. The binoculars shall be mounted on the stereoscope so that they can be easily swung into or out of position for viewing without being detached. The mounting shall permit photographs properly oriented for viewing with binoculars to be viewed without them. When in the viewing position, the axes of the binoculars shall be coincident with the lens axes of the basic stereoscope.

2.3.3 Case. A case shall be provided to protect the stereoscope and binoculars during storage and transport.

2.3.4 Power. The stereoscope shall operate from a 110 volt, 50 hertz, single phase, alternating current source.

3. QUALITY ASSURANCE PROVISIONS. The supplier shall comply with the following for certification and acceptability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

3.2 Market acceptability. The stereoscope offered shall be of the latest model of the standard product of the supplier and shall have been used in the field for at least one year by commercial organizations.

3.3 Examination. Each stereoscope shall be examined for compliance with the requirements specified in 2.3. Any modification necessary following failure to meet the specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all examinations of performance and dimensional requirements. Non-compliance with any specified requirement, or the presence of one or more defects lessening maximum efficiency shall constitute cause for rejection.

4. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

5. NOTES.

5.1 The procuring agency should specify the level of preservation, packing, and marking required.

5.2 When this Commercial Item Description is used for procurement the contractor certification clause should appear in the solicitation.

5.3 Recovered materials. For the purpose of this requirement, recovered materials are those which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. Used, rebuilt, or remanufactured component, pieces and parts shall not be incorporated in the stereoscope.

5.4 Subject term (key word) listing.

photography
viewer

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

Custodians:
Army – CE3
Air Force - 99

Preparing Activity
Army – CE3
(Project 6675-0157)

Review Activity
DLA- GS

Civil Review Activity:
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.