INCH-POUND

A-A-52570A
May 3, 2002
SUPERCEDING
A-A-52570
October 24, 1997

COMMERCIAL ITEM DESCRIPTION

TABLE, LINE-UP AND REGISTER, PRINTING, LITHOGRAPHIC

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies. The original issue of this CID replaced for MIL-T-15672.

1. SCOPE. This CID covers line-up and register tables used in the photolithographic process (herein referred to as table(s)).

2. CLASSIFICATION.

2.1. Type I. 25.50 x 36.50 inches (647.7 mm x 927.1 mm) working area.

2.2. Type II. 36.50 x 48.50 inches (927.1 mm x 1231.9 mm) working area.

3. SALIENT CHARACTERISTICS

3.1 Description. The tables are used in layout, lineup, registering, masking, and opaquing of lithographic negatives, plates, copies, prints, or other materials used in the photolithographic process.

3.2 Materials. The contractor shall select the materials, but the materials shall be capable of meeting all of the operational and environmental requirements specified herein. Recovered materials shall be used to the maximum extent possible (see 6.3.1).

3.3 Performance Characteristics.

3.3.1 Table. The table shall consist of a base frame with a shelf and lamp housing, a tabletop frame with a glass working surface, a horizontal and a vertical straightedge carriage, and precision scale. The minimum dimensions of the glass area of tables shall be as follows:

Type I – 28 x 39 inches (711.2 x 990.6 mm)
Type II – 39 x 51 inches (990.6 x 1295.4 mm)

Beneficial comments, recommendations, additions, deletions, clarifications etc., and any other data which may improve this document should be sent to: ENGINEER RESEARCH AND DEVELOPMENT CENTER, CORPS OF ENGINEERS, U.S. ARMY TOPOGRAPHIC ENGINEERING CENTER, ATTN CEERD-TS, 7701 TELEGRAPH ROAD, ALEXANDRIA, VA 22315-3864.

AMSC N/A FSC 3610

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.3.2 Base frame. The base frame shall support the table and all of its components. A control switch shall be mounted on the base frame convenient for right-hand operation.

3.3.3 Tabletop frame. The tabletop frame shall form a plane and flat surface and shall support the glass working surface and straightedges. The tabletop frame shall be adjustable for tilting up to 20° from horizontal.

3.3.4 Shelf. A shelf extending the entire length of the table shall be provided in the base frame.

3.3.5 Storage compartment. A minimum of one storage compartment or drawer shall be provided for the convenient storage of accessories and tools.

3.3.6 Power and illumination.

3.3.6.1 Electrical requirements. The table shall operate on 120 vac, 60 Hz, single-phase, electrical service and shall have a power cable not less than 5 feet long.

3.3.6.2 Lamp housing. The lamp-housing unit and reflector panels shall support and enclose the lamps and all electrical components. The unit shall provide easy access for removing and installing the lamps and shall provide a means for dissipating heat from the lamps and the glass-working surface. The interior of the lamp housing shall have a durable heat-resistant finish providing even reflection to the glass area.

3.3.6.3 Illumination. The light source shall provide uniform illumination across the entire glass working surface with sufficient intensity for use with translucent and photographic materials.

3.3.7 Sheet stops and grippers. Stops and grippers shall be provided to accurately position and firmly hold the front edge of the sheet, negative, or lithographic plate. The stops shall not interfere in any way with the motion of the vertical straightedge assembly when they are in the secured position.

3.3.8 Side guide. A means shall be provided to accurately position the edge of the sheet, negative, or lithographic plate and to measure its position on the front fixed horizontal scale (see 3.18.1). The guide shall be pivoted so that it may be rotated into a position where it will not interfere with the motion of the straightedge assemblies.

3.3.9 Glass mounting frame. A rectangular frame shall be provided to mount the glass and diffuser in a firm, cushioned support. An adjustable support for the center of the glass and diffuser shall be provided.

3.3.10 Glass plate. The working surface shall be plate or float glass or other suitable material (see 6.3.2). When specified, extra glass plates shall be provided with each table (see 6.1).

3.3.11 Light diffusion. A means of diffusing the light over the entire working surface shall be provided. An opaline or milky white plastic sheet may be used. The light diffusion sheet shall be the same size as the glass plate.

3.3.12 Straightedge carriages. Each table shall be equipped with one vertical and one horizontal straightedge carriage. Each carriage shall be provided with a straightedge, vernier scales, position lock, elevating mechanism, ruler guide track, and scales (see 3.16 and 3.18).

3.3.12.1 Straightedge. Each straightedge shall extend the full length or width of the glass working surface, and shall be moveable across the entire working surface. Movement of the straightedges shall be parallel to their respective fixed scales. The spacings of the grid intersections shall be accurate and precise to with ± 0.0015 inch (.0381 mm). Extreme diagonals shall be equal to each other with in 0.016 inch (0.406 mm) for type I tables and 0.022 inch (0.558 mm) for type II tables.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.3.13 Vernier dial. Each carriage shall be equipped with a vernier dial calibrated to read directly the movement of its respective straightedge in .02 inch (.51 mm) intervals. A vernier adjusting screw, with a positive locking device, shall be provided for precise adjustment of the vernier dial.

3.3.14 Position lock. A means shall be provided for locking either straightedge carriage in any lateral position on the working surface. The ruling edge of the straightedge shall return to its original position on the table.

3.3.15 Elevating mechanism. Each straightedge carriage shall be quipped with a 3-position, lever-operated cam for raising and lowering the straightedge from: (1) surface contact with the sheet; (2) approximately .25 inch (6.35 mm) above the sheet; and (3) high elevation for off-table position. An adjustment shall be provided for variations in the thickness of paper, plates, or negatives.

3.3.16 Ruler guide track. A track shall be provided on each straightedge carriage to accurately guide the ruling device holder and self-inking ruling mechanism (see 3.16.1 and 3.16.3). A line drawn with either the ruling device holder or the self-inking mechanism shall be straight within ± 0.0015 inch (.381 mm) per foot of length, and shall be parallel with the drawing edge of its respective straightedge.

3.3.16.1 Ruling device holder. A ruling device holder shall be provided for each straightedge carriage for ruling continuous parallel lines to within .09 inch (2.29 mm) of any edge of the working surface of the table. The holders shall be constructed for drawing lines on paper, tracing cloth, photographic film, and lithographic offset plates. The horizontal ruling device holder shall rule from left to right, and the vertical ruling device holder shall rule from back to front. Horizontal and vertical ruling divide holders shall be provided with conspicuous, distinguishing marks.

3.3.16.2 Ruling pen. Each ruling device holder shall be provided with a ruling pen. The pen shall draw clean, unbroken uniform lines from 0.006 to 0.060 inch (.1524 mm to 1.524 mm) in width, without cutting into the drawing medium. The ruling pen shall have a 0.003 inch (.076 mm) and a 0.01 inch (.25 mm) stylus point.

3.3.16.3 Self-inking ruling mechanism. In addition to the ruling device holder specified in 3.16.1, a self-inking mechanism shall rule continuous hairlines 0.003 inch (.076 mm) width to within 0.003 in (.076 mm) of any edge of the working surface of the table. The self-inking ruling mechanism shall be provided with an ink pad, a roll assembly, and an ink wheel.

3.3.17 Stops. Four movable and detachable stops, two for each straightedge carriage, shall be provided. Each stop shall be provided with an index for positioning the stop on the scale, and fine adjustment for limiting the stroke of either the ruling device holder or the self-inking ruling mechanism. The stops for the straightedge carriages shall be interchangeable.

3.3.18 Scales. All scales shall be corrosion-resistant steel, shall be graduated in metric and inch divisions, and each inch graduation shall be numbered. In addition, the .12 inch (3.05 mm) graduations shall be marked with the proper figures expressed as the number of .03 inch (.76 mm). All graduations shall be machine divided, clear and distinct, and of a definite length for easy legibility.

3.3.18.1 Horizontal scales. One horizontal scale shall be fastened in front of the front edge of the glass working surface, and one on the horizontal straightedge carriage. Both horizontal scales shall have the zero graduation at the center of the glass working surface. Numbering shall increase to the right and left, and shall extend to the ends of the glass working surface.

3.3.18.2 Vertical scales. One vertical scale shall be fastened on the left-hand side (of the operator in a normal working position) of the glass working surface, and one scale shall be fastened to the vertical

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

straightedge carriage. Both vertical scales shall be numbered from front to back throughout the width of the glass working surface.

3.3.19 Lubrication. All moving parts shall be provided with suitable means of lubrication.

3.3.20 Treatment and painting. Unless otherwise specified (see 6.1), or unless the material is inherently corrosion resistant, the table shall be treated and painted for corrosion protection using the contractor's standard practice.

3.3.21 Fungus and moisture resistance. Materials used in the construction of this table shall resist mildew, rot, fungus and moisture encountered in tropical climates.

3.3.22 Interchangeability. All parts having the same part number shall be functionally and dimensionally interchangeable (see 6.3.3).

3.3.23 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

3.3.24 Ease of maintenance. Components requiring adjustment, maintenance, repair, or replacement shall be readily accessible, without requiring removal of major components or assemblies.

4 QUALITY ASSURANCE PROVISIONS

4.1 Product Conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards and quality assurance practices, and are the same sinks offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

4.2 Market acceptability. The table offered shall be the latest model of the standard product of the supplier and shall have been used in the field for at least one year by the commercial organizations.

4.3 Examinations. Each table examined, shall be examined for compliance with the requirements specified in 3.3. Each element of inspection shall encompass all visual and functional examinations. Nonconformance to any specified requirement or the presence of one or more defects, lessening required efficiency, shall constitute cause for rejection. Any redesign or modification following failure to meet the specified requirements shall receive particular attention for adequacy and suitability.

5 PACKAGING

5.1 Preservation, packing, and marking shall be as specified in the contract or order.

6 NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this CID.

b. Type of table required (see section 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

c. When extra glass plates are required and number required (see 3.3.10).

d. When treatment and painting shall be other than the standard practice. (see 3.3.20).

e. Level of preservation and packing required (see 5.1).

6.2 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

This example describes a part numbering system for CID A-A-XXXXX

AAXXXXX-2
└── Type II

6.3 Definitions. For the purposes of this CID, the following definitions apply.

6.3.12 Recovered materials. For the purpose of this requirement, recovered materials are those that have been collected from solid waste and processed to become a source of raw materials, as distinguished from virgin raw materials. Used, rebuilt, or remanufactured components, pieces, or parts shall not be incorporated in the sinks.

6.3.13 Glass. For the purpose of this requirement, glass is any hard, more or less transparent substance.

6.3.14 Interchangeable parts. Interchangeable parts are defined as two or more parts possessing such functional and physical characteristics as to be equivalent in performance and durability. These parts are capable of being exchanged one for the other without alteration of the parts; of mating or adjoining parts, except for adjustment; and without selection for fit or performance.

6.4 National Stock Numbers (NSN). NSN 3610-00-289-7234 has been used in the past.

6.5 Subject term (key word) listing.

Compartment
Drawer
Glass top
Light
Lit
Photo Lithographic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

Custodian:
Army – CE3
Navy – SA

Preparing activity:
Army – CE3

Review activity:
Navy – MC
DLA – GS

Civilian Coordinating Activity:
GSA-FSS
(Project 3610-0429)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.